

CA-Easytrieve[®]

Plus

For OS/390, VSE

SQL Interface Option Guide

6.3

**COMPUTER[®]
ASSOCIATES**
Software superior by design.

R0J7E863SIE

Release 6.3, February 2001

This documentation and related computer software program (hereinafter referred to as the "Documentation") is for the end user's informational purposes only and is subject to change or withdrawal by Computer Associates International, Inc. ("CA") at any time.

THIS DOCUMENTATION MAY NOT BE COPIED, TRANSFERRED, REPRODUCED, DISCLOSED OR DUPLICATED, IN WHOLE OR IN PART, WITHOUT THE PRIOR WRITTEN CONSENT OF CA. THIS DOCUMENTATION IS PROPRIETARY INFORMATION OF CA AND PROTECTED BY THE COPYRIGHT LAWS OF THE UNITED STATES AND INTERNATIONAL TREATIES.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CA PROVIDES THIS DOCUMENTATION "AS IS" WITHOUT WARRANTY OF ANY KIND, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT. IN NO EVENT WILL CA BE LIABLE TO THE END USER OR ANY THIRD PARTY FOR ANY LOSS OR DAMAGE, DIRECT OR INDIRECT, FROM THE USE OF THIS DOCUMENTATION, INCLUDING WITHOUT LIMITATION, LOST PROFITS, BUSINESS INTERRUPTION, GOODWILL OR LOST DATA, EVEN IF CA IS EXPRESSLY ADVISED OF SUCH LOSS OR DAMAGE.

THE USE OF ANY PRODUCT REFERENCED IN THIS DOCUMENTATION AND THIS DOCUMENTATION IS GOVERNED BY THE END USER'S APPLICABLE LICENSE AGREEMENT.

The manufacturer of this documentation is Computer Associates International, Inc.

Provided with "Restricted Rights" as set forth in 48 C.F.R. Section 12.212, 48 C.F.R. Sections 52.227-19(c)(1) and (2) or DFARS Section 252.227.7013(c)(1)(ii) or applicable successor provisions.

© 1996-2001 Computer Associates International, Inc., One Computer Associates Plaza, Islandia, New York 11749. All rights reserved.

All trademarks, trade names, service marks, or logos referenced herein belong to their respective companies.

Contents

Chapter 1: About This Guide

| | |
|---|-----|
| Purpose and Audience | 1-1 |
| Organization | 1-1 |
| Other CA-Easytrieve Plus Publications | 1-2 |
| Related Publications | 1-3 |
| Documentation Conventions | 1-3 |
| Variable Parameters | 1-4 |

Chapter 2: Overview

| | |
|--|-----|
| Introduction | 2-1 |
| Revision Summary for DB2 for OS/390 Elements | 2-2 |
| Programming Methods | 2-2 |
| Native SQL Statements | 2-2 |
| Automatic Cursor Management | 2-3 |
| CA-Easytrieve Plus SQL Statement Rules | 2-3 |

Chapter 3: Program Environment

| | |
|---------------------------------|-----|
| Overview | 3-1 |
| Units of Work | 3-1 |
| PARM Statement Parameters | 3-2 |
| All SQL Environments | 3-2 |
| SQLSYNTAX FULL | 3-3 |
| SQLSYNTAX PARTIAL | 3-3 |
| SQLSYNTAX NONE | 3-3 |
| DB2 for OS/390 | 3-3 |
| SQLID | 3-3 |
| SSID Parameter | 3-4 |
| Static SQL | 3-4 |

| | |
|--|------|
| DB2 for VSE | 3-4 |
| USERID | 3-4 |
| PREPNAME | 3-5 |
| SSID | 3-5 |
| CA-Datcom/DB | 3-5 |
| PLANOPTS | 3-5 |
| PREPNAME | 3-5 |
| ORACLE | 3-5 |
| USERID | 3-5 |
| SSID | 3-6 |
| CA-IDMS | 3-6 |
| USERID | 3-6 |
| Qualifying DB2 for OS/390 Tables | 3-6 |
| Qualification with Automatic Processing | 3-7 |
| DYNAMIC SQL | 3-7 |
| STATIC SQL | 3-7 |
| Qualification with Controlled Processing | 3-8 |
| DYNAMIC SQL | 3-8 |
| STATIC SQL | 3-8 |
| SQL Error Handling | 3-9 |
| SQL Error Message Format | 3-9 |
| SQL Error Message Text | 3-10 |

Chapter 4: Library Section Definition

| | |
|------------------------------------|-----|
| Overview | 4-1 |
| SQL Catalog INCLUDE Facility | 4-1 |
| SQL INCLUDE Statement | 4-2 |
| Parameters | 4-2 |
| Field Reference | 4-4 |
| Qualifying SQL Column Names | 4-5 |
| Processing NULLable Fields | 4-6 |
| Manual NULL Processing | 4-6 |
| SQL Data Types | 4-7 |
| Decimal Data Types | 4-8 |
| SQL Syntax Checking | 4-9 |
| System-Defined File Fields | 4-9 |
| RECORD-COUNT | 4-9 |
| RECORD-LENGTH | 4-9 |

| | |
|--------------------------------------|------|
| SQL Communications Area Fields | 4-9 |
| Sample Database | 4-12 |
| Working Storage Definitions | 4-12 |

Chapter 5: Automatic Processing

| | |
|--|-----|
| Introduction | 5-1 |
| CA-Easytrieve Plus Files | 5-1 |
| Automatic Retrieval Without a File | 5-1 |
| Specifying Automatic Input | 5-2 |
| FILE Statement | 5-3 |
| JOB Statement | 5-4 |
| SELECT Statement | 5-4 |
| Select-Clause Syntax | 5-5 |
| Select-Clause Operation | 5-7 |
| Generated Code | 5-8 |

Chapter 6: Controlled Processing

| | |
|-------------------------------------|-----|
| Overview | 6-1 |
| GET Statement | 6-1 |
| Native SQL | 6-2 |
| Processing Requirements | 6-6 |
| Operation | 6-6 |
| CALL Statement | 6-6 |
| CALL, ASSOCIATE, and ALLOCATE | 6-7 |

Chapter 7: Executing Your SQL Program

| | |
|--|------|
| DB2 for OS/390 Execution | 7-1 |
| Dynamic SQL Mode | 7-1 |
| Static SQL Mode | 7-1 |
| Sample Job Stream | 7-2 |
| PAN\$SQL DD File | 7-2 |
| EZTPDB2 Procedure | 7-4 |
| Procedure Overrides | 7-8 |
| JCL Modifications | 7-8 |
| Mixed IMS and DB2 for OS/390 Execution | 7-9 |
| DB2 for VSE Execution | 7-10 |

| | |
|-------------------------------|------|
| CA-IDMS/SQL Execution | 7-11 |
| CA-Datcom/SQL Execution | 7-12 |
| ORACLE Execution | 7-13 |

Chapter 8: Examples

| | |
|--|-----|
| Automatic Retrieval | 8-1 |
| Automatic Retrieval - All Columns | 8-1 |
| Automatic Retrieval - Selected Columns | 8-1 |
| Automatic Retrieval - Multiple Tables | 8-2 |
| Automatic Retrieval - SQL FILE | 8-2 |
| Automatic Retrieval - SQL FILE | 8-3 |
| Automatic Retrieval - SQL FILE Using SQL Functions | 8-3 |
| Automatic Retrieval - SQL FILE With NULL Indicators | 8-3 |
| Automatic Retrieval - SQL FILE With Synchronized File Processing | 8-4 |
| Controlled Retrieval | 8-5 |
| Native SQL - All Columns | 8-5 |
| Native SQL - Reassign Departments | 8-6 |
| Native SQL - Update Phone Numbers | 8-7 |
| Native SQL - SQL FILE | 8-7 |

Index

About This Guide

Purpose and Audience

This guide explains the optional CA-Easytrieve Plus facilities that interface with SQL databases:

- DB2 for OS/390
- DB2 for VSE (SQL/DS)
- CA-Datcom/DB
- CA-IDMS
- ORACLE

Organization

This guide is divided into several chapters:

- “Overview” introduces you to the SQL Interface Option.
- “Program Environment” explains the working environments for SQL.
- “Library Section Definition” defines the host variables.
- “Automatic Processing” describes automatic table processing.
- “Controlled Processing” describes the Native SQL commands and the GET command as used in controlled processing.
- “Executing Your SQL Program” describes the uses of JCL.
- “Examples” provides examples for automatic and controlled retrieval.
- The Index provides a listing to facilitate references to terms and procedures.

Other CA-Easytrieve Plus Publications

In addition to this *CA-Easytrieve Plus SQL Interface Guide*, Computer Associates provides the following CA-Easytrieve Plus documentation:

| Name | Contents |
|---|--|
| <i>CA-Easytrieve Plus Getting Started</i> | Describes the process of installing the CA-Easytrieve Plus system in all environment. You can find the most current step-by-step procedures for installing CA-Easytrieve Plus in your environment on the product tape. |
| <i>CA-Easytrieve Plus Reference Guide</i> | Contains descriptions of all product features and functions and summaries of each CA-Easytrieve Plus version. |
| <i>CA-Easytrieve Plus User Guide</i> | Provides new users with the information they need to become productive quickly. It includes a six-lesson tutorial and a format designed to make the material more interesting and easier to comprehend. |
| <i>CA-Easytrieve Plus Application Guide</i> | Describes basic syntax (a subset of the syntax in the <i>CA-Easytrieve Plus Reference Guide</i>) and operation, and provides a series of actual applications, from single examples to full systems. The <i>Application Guide</i> is an excellent tool for the business-oriented professional. |
| <i>CA-Easytrieve Plus Extended Reporting Facility Guide</i> | Describes support of extended reporting capabilities for Impact Dot, Ink Jet, and Electro Photographic printers. |
| <i>CA-Easytrieve Plus Interface Option Guides</i> | Short guides available for users of various system options. They consist of guides for IMS/DLI processing, CA-IDMS and IDD processing, TOTAL processing, SQL processing, CA-Datcom/DB processing, SUPRA processing, and other CA-Easytrieve Plus options. |

Related Publications

The following publication, produced by Computer Associates, is either referenced in this documentation or is recommended reading:

- *CA-Pan/SQL SQL Interface Getting Started*

The following publications, not produced by Computer Associates, are either referenced in this documentation or are recommended reading:

- *ORACLE Installation and System Administration Guide*
- *IBM DB2 Reference Manual*

Documentation Conventions

The following conventions are used throughout this guide for illustrative purposes.

| Notation | Meaning |
|---------------|--|
| {braces} | Mandatory choice of one of these entries. |
| [brackets] | Optional entry or choice of one of these entries. |
| (or bar) | Choice of one of these entries. |
| (parentheses) | Multiple parameters must be enclosed in parentheses. |
| ... | Ellipses indicate that you can code the immediately preceding parameters multiple times. |
| CAPS | All capital letters indicate a keyword, name, or field used in a program example. |
| lowercase | Lowercase letters represent variable information in statement syntax. If the same variable types recur in a statement, they are made unique by adding a numeric suffix, such as literal-2. |

Variable Parameters

| Parameter | Meaning |
|--------------|--|
| field-name | Data field defined in your program. |
| file-name | Unique file name defined in the library section of your program. |
| index name | Name of an INDEX data item. |
| integer | Numeric literal (a whole number greater than zero). |
| job-name | Name of a JOB activity. |
| letter | Single alphabetic character (such as an edit mask identifier). |
| literal | Text string enclosed in quotes or a numeric constant. |
| proc-name | Name of a procedure. |
| program-name | Name of a program written in a language other than CA-Easytrieve Plus, such as COBOL or Assembler. |
| record-name | Name of an IMS/DLI or CA-IDMS entity. |
| report-name | Name of a REPORT. |
| sort-name | Name of a SORT activity. |

Introduction

CA-Easytrieve Plus provides optional processing facilities for SQL databases. The following SQL databases are supported:

- IBM DB2 for OS/390
- IBM DB2 for VSE (SQL/DS)
- CA-Datcom/DB for SQL
- CA-IDMS SQL
- ORACLE

Before CA-Easytrieve Plus can process these databases, the CA-Pan/SQL Interface product, version 2.4, must be correctly installed. See the *CA-Pan/SQL SQL Interface Getting Started* for complete information.

To use this facility effectively, you should have a basic knowledge of SQL and the given database management system to be processed.

Revision Summary for DB2 for OS/390 Elements

The SQL interface for CA-Easytrieve Plus has the following enhancements:

1. Support of DSNALI Above The Line

Release 4.1 of DB2 for OS/390 linked DSNALI as AMODE 31. This caused DSNALI to be loaded Above The Line.

2. Validation of Host Variable Datatypes at Compile Time

3. Support of CALL, ALLOCATE, and ASSOCIATE statements for STATIC-ONLY processing..

The CALL procedure, ALLOCATE cursor, and ASSOCIATE LOCATORS statements are now supported by PanSQL for a BIND option of STATIC-ONLY.

4. Support specification of a PLAN and SSID at execution time

You can specify an execution time PLAN and SSID with a PAN\$SQL DD file. This enables you to run with a different planname on different subsystems.

5. Support for Execution of Statically Bound Applications under the TSO Terminal Monitor Program

This enables your called subroutines to be linked with DSNELI for both CA-Easytrieve applications and other language applications.

Programming Methods

There are two programming methods supported for processing SQL databases:

- Using native SQL statements to manually manage the SQL cursor.
- Permitting CA-Easytrieve Plus to automatically manage the SQL cursor.

Native SQL Statements

CA-Easytrieve Plus supports most of the SQL statements available for a given DBMS. The exceptions are those statements that are compiler directives and statements that cannot be dynamically *prepared*. Using these native SQL statements, you can code fully SQL-compliant programs in which you control the SQL cursor operation. All native SQL statements are prefixed with the *SQL* keyword. A list of all supported and unsupported SQL commands is provided later in this chapter.

Automatic Cursor Management

There are two ways that CA-Easytrieve Plus can manage the SQL cursor for you:

- CA-Easytrieve Plus files
- Automatic retrieval without a file.

CA-Easytrieve Plus SQL Statement Rules

There are several differences in the rules when coding SQL control statements in CA-Easytrieve Plus. The following syntax rules apply:

- Operators must be separated by blanks.
- Standard CA-Easytrieve Plus continuation conventions are followed.
- Commas are **not** ignored.
- The period is used as a qualification separator, not to signify end-of-statement.
- The colon is used to identify host/indicator variables, not as a qualification separator.
- An SQL statement cannot be followed by another statement on the same source record.

Program Environment

Overview

CA-Easytrieve Plus processes SQL statements using the CA-Pan/SQL Interface product. A specific implementation exists for each supported database:

- For DB2 for OS/390, a dynamic and static interface are supported.
- For DB2 for VSE, *extended dynamic SQL* is supported. SQL statements are dynamically prepared during the compilation of your CA-Easytrieve Plus program and an access module or package is created. At runtime, SQL statements are executed from the access module or package.
- The CA-Datcom/DB SQL interface is very similar to the DB2 for VSE interface. An access plan is created at compile time from which SQL statements are executed.
- The CA-IDMS SQL interface is strictly a dynamic interface for both compilation and execution.
- The ORACLE interface is strictly a dynamic interface for both compilation and execution.

Units of Work

Each CA-Easytrieve Plus activity is considered a separate SQL unit of work.

A COMMIT is executed following each JOB activity that contains SQL statements. A ROLLBACK is automatically executed if CA-Easytrieve Plus detects an error condition or if you code a STOP EXECUTE statement in your program.

PARM Statement Parameters

The following PARM statement parameters set the SQL environment for the program:

For DB2 for OS/390:

- SQLID
- SSID
- PLAN
- BIND
- SQLSYNTAX.

For DB2 for VSE:

- USERID
- PREPNAME
- SQLSYNTAX.

For CA-Datcom/DB:

- PLANOPTS
- PREPNAME
- SQLSYNTAX.

For ORACLE:

- USERID
- SSID
- SQLSYNTAX.

For CA-IDMS:

- USERID
- SQLSYNTAX.

All SQL Environments

In all environments, use the SQLSYNTAX parameter to specify the level of SQL syntax checking to perform on the SQL statements in your program.

SQLSYNTAX FULL

SQLSYNTAX FULL indicates that SQL statements undergo detail-level syntax checking. An SQL PREPARE statement executes for those SQL statements that can be dynamically prepared. Your DBMS must be available to CA-Easytrieve Plus.

SQLSYNTAX PARTIAL

SQLSYNTAX PARTIAL checks your SQL statements for valid commands and secondary keywords. No connection is made to your DBMS unless you coded an SQL INCLUDE statement in your program. Your program cannot execute until it undergoes FULL syntax checking.

SQLSYNTAX NONE

You can use the SQLSYNTAX NONE parameter on the PARM statement with a static bind if you want the DB2 for OS/390 preprocessor to perform syntax checking in a batch environment. An option of NONE performs partial syntax checking on your program. If no partial level compile errors are found and a BIND option of STATIC-ONLY is specified and no other non-SQL syntax errors are found, your program continues to execution.

You can use SQLSYNTAX NONE with BIND STATIC-ONLY to process unqualified tables. With SQLSYNTAX NONE, you eliminate the dynamic bind which qualifies all unqualified tables. You can then set a qualifier when you BIND the DBRM of the static-command-program.

DB2 for OS/390

SQLID

The SQLID parameter of the PARM statement results in the SQL interface executing the SQL SET CURRENT SQLID command at compile time. The SQL SET CURRENT SQLID command is executed at runtime for automatic processing. Execution of the SQL SET CURRENT SQLID command is valid for sites that have an external security package that supports group IDS. It sets the qualification of unqualified tables for dynamic SQL processing. See “Qualifying DB2 for OS/390 Tables” later in this chapter for more information.

It is recommended to use SQLSYNTAX NONE with BIND STATIC-ONLY rather than SQLID to set the qualification for tables.

SSID Parameter

The SSID parameter of the PARM statement can explicitly specify the DB2 for OS/390 subsystem. If the SSID parameter is not coded, the SQL interface gets the DB2 for OS/390 subsystem ID from the DB2 for OS/390 system default module DSNHDECP. DSNHDECP is made available through the JOBLIB or STEPLIB libraries.

The valid format is *xxxx/yyyyyyyy*, where *xxxx* is a valid DB2 for OS/390 subsystem ID and *yyyyyyyy* is a valid DB2 for OS/390 location ID. Neither value is required. You can specify either one. If you specify a location ID, you must precede it with a slash, such as *SSID=/yyyyyyyy*.

Static SQL

Static SQL improves the performance of an SQL program. In a static SQL program, all SQL statements are known ahead of time and an optimized plan is created before execution time.

Static SQL is specified by two parameters on the PARM statement, PLAN and BIND.

- A PLAN parameter specifies the name of the DB2 for OS/390 static-command-program and its planname. The command program is linked as a separate load module.
- A BIND parameter of STATIC-ONLY or ANY generates the static-command-program. Execution can be static or dynamic.

To execute your program statically, you must run special steps to create and link the static command program and plan. See the “Executing Your SQL Program” chapter for more information.

DB2 for VSE

USERID

Specify the DB2 for VSE user ID and password to use for compiling the program on the USERID parameter of the PARM statement.

- For automatic processing, CA-Easytrieve Plus executes a CONNECT using the same parameters.
- For controlled processing, you must code a CONNECT statement to be the first SQL statement the program executes.

PREPNAME

Specify the name of the DB2 for VSE access module for this program on the PREPNAME parameter of the PARM statement. When an SQL program is compiled, an access module is created or replaced. You should use unique access module names for each application program to avoid using the default access module.

In a high volume system, using the default PREPNAME can result in catalog contention and a -911 SQLCODE resulting from a rollback.

SSID

Provide a database ID on the SSID parameter to connect to a non-default database.

The valid format is *yyyyyyyyyy*, where *yyyyyyyyyy* is a valid database ID.

CA-Datacom/DB**PLANOPTS**

Use the PLANOPTS parameter on the PARM statement to specify the name of a CA-Pan/SQL plan options module to override the default plan module DQSMPLN@. See the *CA-Pan/SQL SQL Interface Getting Started* for more information about defining your own options module.

PREPNAME

Specify the name of the plan and authorization ID to create the SQL plan for CA-Datacom/DB. The plan is created using the options defined by the CA-Pan/SQL plan options module.

ORACLE**USERID**

Specify the user ID to use for compiling the ORACLE program on the USERID parameter of the PARM statement. For more details on the USERID parameter, refer to the “System Overview” chapter of the *CA-Easytrieve Plus Reference Guide*.

SSID

- The SSID parameter of the PARM statement can specify the appropriate subsystem. Refer to the “System Overview” chapter and the “Options Table” appendix in the *CA-Easytrieve Plus Reference Guide* for more details on the SSID parameter.
- You can also specify the subsystem through an ORA@ssid DD statement. Refer to your *ORACLE Installation and System Administration Guide* for more details on using the ORA@ssid DD statement.

CA-IDMS

USERID

Specify the user ID to use for compiling the CA-IDMS program on the USERID parameter of the PARM statement. For more details on the USERID parameter, refer to the “System Overview” chapter of the *CA-Easytrieve Plus Reference Guide*.

Qualifying DB2 for OS/390 Tables

Unqualified tables are implicitly qualified by the primary authorization ID of the program. This ID is usually established by the USER parameter of your JCL JOB card. You can modify qualification in one of three ways:

- SQLID keyword on the CA-Easytrieve PARM statement
- SQL SET CURRENT SQLID command
- OWNER or QUALIFIER parameter on the DB2 for OS/390 BIND statement.

Use of the SQLID and its affect on table qualification depends on whether automatic or controlled processing is performed and if STATIC or DYNAMIC SQL is used.

To eliminate the authorization problems encountered with the use of SQLID, use SQLSYNTAX NONE with BIND STATIC-ONLY. This enables the use of unqualified table names and bypasses the dynamic prepare of SQL statements. Unqualified table names can then be qualified by the BIND process.

Qualification with Automatic Processing

DYNAMIC SQL

Use the SQLID on the PARM statement to set the table qualification. SQLID sets the qualification at compile time when table validation is performed. Also, it executes a SET CURRENT SQLID at runtime.

The primary authorization ID must have the proper DB2 for OS/390 authority to issue the SET CURRENT SQLID command. This authority is established through the implementation of an external security system.

In the following example, the use of SQLID sets the current SQLID to 'SYSIBM' during compilation, thus DB2 for OS/390 verifies that the table called 'SYSIBM.SYSPLAN' exists.

A SET CURRENT SQLID command automatically executes at runtime to establish the qualification of SYSIBM for table SYSPLAN.

```
PARM SQLID('SYSIBM')
DEFINE WKNAME      W   18  A
DEFINE WKCREATOR    W    8  A
JOB INPUT SQL
  SELECT NAME, CREATOR FROM SYSPLAN ORDER BY NAME
                                     +
                                     INTO :WKNAME, :WKCREATOR
```

STATIC SQL

To modify for static execution, you change the PARM statement as follows:

```
PARM PLAN (TESTPLAN TESTPGM) LINK (EZTPGM R)      +
  BIND STATIC-ONLY SQLID('SYSIBM')
```

The SQLID acts as it does for dynamic processing during the compilation of the program. It executes a SET CURRENT SQLID = 'SYSIBM'.

Since we are using automatic processing, CA-Easytrieve Plus generates the SET CURRENT SQLID command for runtime execution. However, since we are running static SQL, the SET CURRENT SQLID has no affect on the qualification of tables. The OWNER and QUALIFIER parameters of the BIND process establish the qualification of unqualified tables. Refer to your *IBM DB2 Reference Manual* for more information on the SET and BIND commands.

For both STATIC and DYNAMIC processing, the primary authorization ID of the compile or runtime process must have the authority to execute the SET CURRENT SQLID command. Invalid authorization results in an SQLCODE of -553.

Qualification with Controlled Processing

DYNAMIC SQL

Consider the partial program in the following example. The SQLID on the PARM statement generates a SET CURRENT SQLID = 'SYSIBM' during the compilation process. Thus, the table 'SYSIBM.SYSPLAN' is validated.

During the execution phase, the SET CURRENT SQLID = 'SYSIBM' is the first SQL statement executed, so the DECLARE CURSOR and the FETCH is for the table 'SYSIBM.SYSPLAN'.

If you did not code the SET CURRENT SQLID command in your program, the DECLARE CURSOR is executed for the table *userid*.SYSPLAN and a -514 SQLCODE occurs, since this table does not exist.

```
PARM SQLID('SYSIBM')
DEFINE WKNAME      W      18 A
DEFINE WKCREATOR   W       8 A
SQL  DECLARE C1 CURSOR FOR          +
      SELECT  NAME, CREATOR          +
      FROM    SYSPLAN               +
      ORDER BY NAME
JOB INPUT NULL
SQL SET CURRENT SQLID='SYSIBM'
SQL OPEN C1
PERFORM CHECK-SQL-CODE
DO WHILE SQLCODE EQ 0
  SQL  FETCH C1 INTO :WKNAME, :WKCREATOR
  PERFORM CHECK-SQL-CODE
  IF SQLCODE = 0
    PRINT REPORT1
  END-IF
END-DO
SQL CLOSE C1
PERFORM CHECK-SQL-CODE
STOP
```

STATIC SQL

To modify for Static SQL processing, you change the PARM statement to look like:

```
PARM PLAN (TESTPLAN TESTPGM) LINK (EZTPGM R)      +
      BIND STATIC-ONLY SQLID('SYSIBM')
```

You also remove the SET CURRENT SQLID = 'SYSIBM' statement. The SET CURRENT command is a dynamic only command and thus has no affect on a STATIC program.

With these modifications, the SQLID on the PARM statement still generates the SET CURRENT SQLID command during compilation and then validates the table SYSIBM.SYSPLAN.

To qualify the tables at execution, however, you must use the appropriate parameters, OWNER and QUALIFIER, on the BIND statement. A sample BIND statement is shown below. Refer to your *IBM DB2 Reference Manual* for information on the DB2 for OS/390 Bind statement.

```
BIND PLAN (TESTPLAN) MEMBER (TESTDBRM) VALIDATE (RUN) -  
      ACT(REPLACE) ISOLATION (CS) OWNER(TESTUSER) QUALIFIER(SYSIBM)
```

SQL Error Handling

At CA-Easytrieve Plus compilation time, the SQL statements in your program undergo detail syntax checking by the underlying database management system unless `SQLSYNTAX=NONE` is coded. Detail syntax checking means that the SQL statement is processed by an SQL PREPARE statement that the SQL interface manages. If the database detects an error, the SQL interface returns error information with an appropriate error message.

At runtime, CA-Easytrieve Plus checks the `SQLCODE` in the `SQLCA` for you and issues an appropriate error message if an error was detected during automatic processing. It is the user's responsibility to check the `SQLCODE` after each SQL statement to determine its success or failure when using Native SQL. The user can display the various `SQLCA` fields and obtain the information to determine the cause of any SQL error.

SQL Error Message Format

The format of the message containing the `SQLCA` error information returned to the program, varies with the underlying database management system. The format for each SQL database is shown below.

DB2 for OS/390, DB2 for VSE and ORACLE:

```
SQLCODE FROM SQLCA IS sqlcode
```

CA-Datcom:

```
SQL ERROR, SQLCODE IS sqlcode, DBC=(sqldbcex,sqldbcin),  
DSF=(sqldsfc), PGM=(sqlerrp), QMCD=(q-command)
```

CA-IDMS:

```
SQL ERROR, SQLCODE IS sqlcode, SQLCER is sqlcer.
```

SQL Error Message Text

For each SQL error condition reported in the above format, the message associated with the SQLCODE is also returned. The actual message text is obtained from the following:

DB2 for OS/390:

The message returned is obtained from the DB2 for OS/390 module DSNTIAR.

DB2 for VSE:

The message is obtained from the CA-Pan/SQL module DQSMMTB. This module extracts messages from the DB2 for VSE help tables as part of the CA-Pan/SQL installation process.

ORACLE:

The message is obtained from an internal ORACLE facility.

CA-Datcom:

The message is obtained from the SQLERRM field of the SQLCA.

CA-IDMS:

The message is obtained from the SQLCERM field of the SQLCA. For SQL syntax errors, field SQLCER contains the displacement into the SQL statement where the error was found.

Library Section Definition

Overview

Before SQL data can be accessed, you must define the fields to hold the columns to retrieve. These fields are known as host variables.

If you are using native SQL commands or using automatic retrieval without a file, you usually define the fields as working storage fields. Alternatively, you can define the fields in an active output file. This is an effective method to select SQL data into a sequential file for extraction purposes. You must specify which columns to retrieve and which host variables are to receive the data.

When using a CA-Easytrieve Plus file, however, fields defined in the file correspond to the selected columns of the SQL table. The table columns are retrieved into the file fields.

SQL Catalog INCLUDE Facility

You can use the SQL catalog INCLUDE facility to automatically generate CA-Easytrieve Plus field definitions directly from the SQL catalog. This eliminates the need to code host variable definitions in the library section of your program.

The SQL INCLUDE statement names the SQL table or view from which column names and data types are obtained, and defines the location at which the field definitions are generated. The SQL INCLUDE statement must precede any other SQL or SELECT statements and must be coded in the library section of your CA-Easytrieve Plus program.

Note: ORACLE does not provide a catalog INCLUDE facility.

SQL INCLUDE Statement

The CA-Easytrieve SQL INCLUDE statement indicates that SQL table information generates CA-Easytrieve field definitions. It names the table and gives the location where the field definitions are generated.

Syntax

```
SQL INCLUDE +  
  [(column ...)] +  
  [  
    {starting-position} ]  
  [ {* [+offset] } ]  
  [ LOCATION { } ] +  
  [ {W } ]  
  [ {S } ]  
  
  [HEADING] +  
  
  [UPDATE] +  
  
  [NULLABLE] +  
  
FROM [owner.] table
```

Parameters

[(column ...)]

Specify a list of one or more column names for which field definitions are generated. The column names must be enclosed in parentheses. If no column names are specified, all columns from the table are used.

```
[ {starting-position} ]  
[ {* [+offset] } ]  
[ LOCATION { } ]  
[ {W } ]  
[ {S } ]
```

Use this optional parameter to specify the location at which the field definitions are generated.

Starting-position specifies the starting position relative to position one of the record or file.

The * (asterisk) indicates that the field begins in the next available starting position (highest position assigned so far, plus 1). The optional *+offset* is an offset you want added to the * value. There must be at least one blank between the * and the optional *+offset*.

Coding W or S establishes a working storage field. W fields are spooled to report (work) files, S fields are not. W is the default location if the LOCATION parameter is not coded.

[HEADING]

Optionally, code **HEADING** to copy *LABEL* from the DBMS system catalog column entry into a **HEADING** parameter on the generated **DEFINE** statement for the column.

[UPDATE]

Code **UPDATE** to designate a modifiable column.

When a CA-Easytrieve SQL file does not contain the **UPDATE** parameter, only the specific columns defined with **UPDATE** can be modified with an **UPDATE** statement. If **UPDATE** is coded on the **FILE** statement, you can modify all columns in the file, provided you have the proper authorization.

Note: You can only use **UPDATE** when the field definitions are generated for a CA-Easytrieve file.

[NULLABLE]

Optionally, code **NULLABLE** to define default indicator fields for columns that contain **NULL**. The indicator field is defined as a 2 B 0 field preceding the field being defined. CA-Easytrieve automatically uses the default null indicator whenever the associated column is referenced. You can override the use of the default null indicator by explicitly coding and referencing another indicator variable.

The indicator variable precedes the data portion of the field in storage. This field cannot be directly referenced. To check this indicator variable, you must use the **IF NULL** statement.

FROM [owner.] table

FROM identifies the table definition to define to CA-Easytrieve. Owner is the optional 1 to 18-character alphanumeric qualifier, and table is the 1 to 32-character alphanumeric name. You must use the period as the qualification separator for owner-qualified tables.

Note: If the owner is not specified, the current authorization ID is used.

Notes

The generated CA-Easytrieve field names are the same as the SQL column names. If a name matches a reserved word, the field definition is allowed, but all references to it must be qualified using any applicable qualification.

Mask information is not retrieved from the DBMS system catalog.

Group qualification structures of owner.table are defined before the first INCLUDED definition. The fields are defined under the table entity, which is, in turn, under the owner-level entity. This ensures that multiple tables with duplicate column names do not produce duplicate field names.

Fields with SQL data types that do not have equivalent CA-Easytrieve data types are defined as shown in the following table. You cannot use fields of DATE, TIME, TIMESTAMP, and BINARY in arithmetic operations. Fields of FLOAT, DOUBLEPRECISION, REAL, and LONGINTEGER are defined as packed decimal fields. Non-zero FILE-STATUS and SQLCODE values are returned if the data is truncated.

| SQL Data Type | CA-Easytrieve Data Type | Length | Decimals |
|-----------------|-------------------------|---------------------|----------|
| DATE | Alphanumeric | 10 | |
| TIME | Alphanumeric | 8 | |
| TIMESTAMP | Alphanumeric | 26 | |
| BINARY | Alphanumeric | Length of SQL field | |
| FLOAT | Packed Numeric | 10 | 3 |
| DOUBLEPRECISION | Packed Numeric | 10 | 3 |
| REAL | Packed Numeric | 10 | 3 |
| LONGINTEGER | Packed Numeric | 10 | 0 |

The DBMS system catalog must be referenced each time the program is compiled or interpreted. Therefore, to reduce catalog contention and to improve performance, you should always create link-edited programs.

Field Reference

One of the advantages of using the SQL INCLUDE interface is the ability to reference host-variable (CA-Easytrieve fields) using the group level TABLE definition.

When specifying the *INTO* clause on a native *SQL FETCH* or non-file *SQL SELECT* statement or the *VALUES* clause of the native *SQL INSERT* statement, you can substitute the host variable TABLE definition in place of coding all host-variables in the table.

If you require access to an indicator variable other than its use for NULL checking, you must define your own variable and reference it with its host-variable. For some DBMSs, the indicator variable is examined to detect truncation.

If NULLABLE is not coded on the INCLUDE statement, an indicator variable can be passed along with the host variable for NULLABLE columns. When the host-variable is a CA-Easytrieve group level definition of a table name, specify an array of type 2 B 0 immediately following the host-table-name-variable. The number of array elements should match the number of fields in the CA-Easytrieve table name definition. Array elements are matched one-to-one with the fields defined in the table name.

Qualifying SQL Column Names

The following example shows how to qualify SQL fields and how to use the keyword NULLABLE.

Table PANSQL.PERSNL3 is defined exactly the same as table PANSQL.PERSNL. To reference a column of table PANSQL.PERSNL, you must qualify it with the table name PERSNL followed by a colon (:).

When you code NULLABLE on an SQL INCLUDE statement, CA-Easytrieve Plus generates the two-byte binary field in front of the column field in the file or record layout. When you code NULLABLE, you can then test the field for being null rather than testing a null indicator.

```

PARM  DEBUG(PMAP DMAP)  ABEXIT  NO
*****
***  TABLE PANSQL.PERSNL CONTAINS NULLABLE COLUMNS
*****
FILE SQLFILE SQL
SQL INCLUDE LOCATION W NULLABLE FROM PANSQL.PERSNL
*****
***  TABLE PANSQL.PERSNL3 IS IDENTICAL TO PANSQL.PERSNL
***  AND IS INCLUDED FOR THE PURPOSE OF DEFINING SAME NAMED FIELDS
*****
SQL INCLUDE LOCATION W FROM PANSQL.PERSNL3
JOB INPUT SQLFILE
      SELECT * FROM PANSQL.PERSNL
      INTO :PANSQL.PERSNL
IF PERSNL:EMP_PAY_NET NULL
  PERSNL:EMP_PAY_NET = 0
END-IF
IF PERSNL:EMP_PAY_GROSS NULL
  PERSNL:EMP_PAY_GROSS = 0
END-IF
IF SQLCODE NE 0 AND SQLCODE NE +100
  DISPLAY 'SQLCODE = ' SQLCODE
  STOP EXECUTE
END-IF
PRINT RPT
REPORT RPT
SEQUENCE PERSNL:EMP_REGIONS
LINE PERSNL:EMP_SSN PERSNL:EMP_NBR PERSNL:EMP_PHONE_NBR

```

Processing NULLable Fields

CA-Easytrieve Plus supports the SQL concept of a null data value.

Null is a value that denotes the absence of a known value for a field. Specify the keyword `NULLABLE` on the `SQL INCLUDE` statement to generate the null indicator variables. CA-Easytrieve Plus does the rest of the processing for you when processing the SQL table as a file.

When a field is defined as nullable, you can use special processing statements:

- You can use `IF NULL` to determine if the field contains a null value.
- You can use `MOVE NULL` to set a field's value to null.

Manual NULL Processing

When you use native SQL statements or automatic retrieval without a file, you define null values differently.

You define an indicator variable as a two-byte quantitative binary field (2 B 0). This indicator variable is then used in the `INTO` clause of the native or automatic `SELECT` statement. SQL returns a negative value to the indicator variable when the field's value is null. See the native SQL examples for the use of manual indicator values.

SQL Data Types

The following table illustrates SQL data types and corresponding CA-Easytrieve Plus field definitions. SQL provides some data conversion in SQL assignments and comparisons. Refer to your SQL guides for more information on SQL data conversions.

| SQL | CA-Easytrieve Plus | DB2 | CA-Datacom/ DB SQL | ORACLE | CA-IDMS SQL |
|------------------------|------------------------|-----|--------------------|--------|-------------|
| INTEGER | 4 B 0 4 I 0 | Y | Y | Y | Y |
| SMALL INTEGER | 2 B 0 2 I 0 | Y | Y | Y | Y |
| DECIMAL (x,y) | x P y | Y | Y | Y | Y |
| UNSIGNED DECIMAL (x,y) | x P y | N | N | N | Y |
| CHARACTER (x) | x A | Y | Y | Y | Y |
| VARCHAR (x) | x A VARYING (x <= 254) | Y | Y (8.1) | Y | Y |
| LONG VARCHAR (x) | x A VARYING (x > 254) | Y | Y (8.1) | Y | Y |
| NUMERIC (x,y) | x N y | N | Y | Y | Y |
| UNSIGNED NUMERIC (x,y) | x N y | N | N | N | Y |
| FLOAT | 10 P 3 | Y | Y | Y | Y |
| REAL | 10 P 3 | Y | Y | N | Y |
| DOUBLE PRECISION | 10 P 3 | Y | Y | N | Y |
| GRAPHIC (x) | x M x K | Y | N | N | Y |

| SQL | CA-Easytrieve Plus | DB2 | CA-Datcom/ DB SQL | ORACLE | CA-IDMS SQL |
|---------------------|---------------------------------------|-----|-------------------|--------|-------------|
| VARGRAPHIC (x) | x M VARYING x K VARYING (x <= 254) | Y | N | N | Y |
| LONG VARGRAPHIC (x) | x M VARYING x K VARYING (x > 254) | Y | N | N | Y |
| DATE | 10 A | Y | Y | N | Y |
| DATE (ORACLE) | 12 A | N | N | Y | N |
| RAW | x A | N | N | Y | N |
| LONGRAW | x A VARYING | N | N | Y | N |
| TIME | 8 A | Y | Y | N | Y |
| TIMESTAMP | 26 A | Y | Y | N | Y |
| LONG INTEGER | 10 P 0 | N | N | N | Y |
| BINARY | x A y | N | N | N | Y |
| none | x U y | - | - | - | - |

Decimal Data Types

For SQL DECIMAL data types, the scale is the same as the decimal places of a CA-Easytrieve Plus field. SQL precision refers to the total number of digits that can occur in the packed field.

A CA-Easytrieve Plus length refers to the number of bytes occupied by the packed field.

A CA-Easytrieve Plus field that is 5 P 2 is the equivalent of an SQL DECIMAL data type of precision = 9 and scale = 2. Depending on your SQL release, SQL might not support CA-Easytrieve Plus packed fields with lengths > 8.

To ensure even precision in CA-Easytrieve Plus, you should specify the keyword EVEN on the DEFINE for user-coded host variables.

SQL Syntax Checking

When an SQL statement is passed to SQL for syntax checking, CA-Easytrieve Plus converts host variables to question marks (?). It is possible that when an SQL error is detected, the question mark is identified as the field in error. In this case, you are responsible for looking up the error message and identifying which host variable is in error.

Because host variables are replaced with question marks, their use in arithmetic expressions can result in compile errors. For DB2 for OS/390 and DB2 for VSE, an SQLCODE of -418 can occur.

System-Defined File Fields

When using a CA-Easytrieve Plus file to process an SQL database, two system-defined fields are used:

- RECORD-COUNT
- RECORD-LENGTH.

RECORD-COUNT

RECORD-COUNT contains the number of rows returned to the CA-Easytrieve Plus program. This is the number of rows fetched either by automatic or controlled processing.

RECORD-LENGTH

RECORD-LENGTH is the length of the SQL file. The length is the sum of the maximum lengths of all fields in the file.

SQL Communications Area Fields

All of the SQL Communication Area fields (SQLCA) are automatically created in S (static) working storage when any of the following occurs:

- The first SQL-managed FILE IS ENCOUNTERED
- The first SQL INCLUDE statement is encountered
- The first native SQL statement is found
- The first JOB INPUT SQL statement is found.

The fields, generated for SQLCA for the supported SQL database management systems, are shown below.

| | | | | |
|------------------|------------|-----|---|------------|
| DEFINE SQLCA | S | 136 | A | |
| DEFINE SQLCAID | SQLCA | 8 | A | |
| DEFINE SQLCABC | SQLCA +8 | 4 | B | 0 |
| DEFINE SQLCODE | SQLCA +12 | 4 | B | 0 |
| DEFINE SQLERRM | SQLCA +16 | 72 | A | |
| DEFINE SQLERRML | SQLCA +16 | 2 | B | 0 |
| DEFINE SQLERRMC | SQLCA +18 | 70 | A | |
| DEFINE SQLERRP | SQLCA +88 | 8 | A | |
| DEFINE SQLERRD | SQLCA +96 | 4 | B | 0 OCCURS 6 |
| DEFINE SQLWARN | SQLCA +120 | 8 | A | |
| DEFINE SQLWARN0 | SQLCA +120 | 1 | A | |
| DEFINE SQLWARN1 | SQLCA +121 | 1 | A | |
| DEFINE SQLWARN2 | SQLCA +122 | 1 | A | |
| DEFINE SQLWARN3 | SQLCA +123 | 1 | A | |
| DEFINE SQLWARN4 | SQLCA +124 | 1 | A | |
| DEFINE SQLWARN5 | SQLCA +125 | 1 | A | |
| DEFINE SQLWARN6 | SQLCA +126 | 1 | A | |
| DEFINE SQLWARN7 | SQLCA +127 | 1 | A | |
| DEFINE SQLEXT | SQLCA +128 | 8 | A | |
| DEFINE SQLWARN8 | SQLCA +128 | 1 | A | |
| DEFINE SQLWARN9 | SQLCA +129 | 1 | A | |
| DEFINE SQLWARNA | SQLCA +130 | 1 | A | |
| DEFINE SQLSTATE | SQLCA +131 | 5 | A | |
| | | | | |
| SQLCA | S | 196 | A | |
| SQLCA-EYE-CATCH | SQLCA | 8 | A | |
| SQLCAID | SQLCA | 8 | A | |
| SQLCA-LEN | SQLCA +8 | 4 | B | 0 |
| SQLCABC | SQLCA +8 | 4 | B | 0 |
| SQLCA-DB-VRS | SQLCA +12 | 2 | A | |
| SQLCA-DB-RLS | SQLCA +14 | 2 | A | |
| SQLCA-LUWID | SQLCA +16 | 8 | A | |
| SQLCODE | SQLCA +24 | 4 | B | 0 |
| SQLCA-ERROR-INFO | SQLCA +28 | 82 | A | |
| SQLCA-ERR-LEN | SQLCA +28 | 2 | B | 0 |
| SQLCA-ERR-MSG | SQLCA +30 | 80 | A | |
| SQLERRM | SQLCA +28 | 72 | A | |
| SQLERRML | SQLCA +28 | 2 | B | 0 |
| SQLERRMC | SQLCA +30 | 70 | A | |
| SQLCA-ERROR-PGM | SQLCA +110 | 8 | A | |
| SQLERRP | SQLCA +110 | 8 | A | |
| SQLCA-FILLER-1 | SQLCA +118 | 2 | A | |
| SQLCA-ERROR-DATA | SQLCA +120 | 24 | A | |
| SQLCA-DSFCODE | SQLCA +120 | 4 | A | |
| SQLCA-INFCODE | SQLCA +124 | 4 | B | 0 |
| SQLCA-DBCODE | SQLCA +128 | 4 | A | |
| SQLCA-DBCODE-EXT | SQLCA +128 | 2 | A | |
| SQLCA-DBCODE-INT | SQLCA +130 | 2 | B | 0 |
| SQLCA-MISC-CODE1 | SQLCA +132 | 4 | A | |
| SQLCA-MISC-CODE2 | SQLCA +136 | 4 | B | 0 |
| SQLCA-MISC-CODE3 | SQLCA +140 | 4 | A | |
| SQLCA-WRN-AREA | SQLCA +144 | 8 | A | |
| SQLCA-WARNING | SQLCA +144 | 1 | A | OCCURS 8 |
| SQLWARN | SQLCA +144 | 8 | A | |
| SQLWARN0 | SQLCA +144 | 1 | A | |
| SQLWARN1 | SQLCA +145 | 1 | A | |
| SQLWARN2 | SQLCA +146 | 1 | A | |
| SQLWARN3 | SQLCA +147 | 1 | A | |

| | | | |
|-----------------|------------|----|---|
| SQLWARN4 | SQLCA +148 | 1 | A |
| SQLWARN5 | SQLCA +149 | 1 | A |
| SQLWARN6 | SQLCA +150 | 1 | A |
| SQLWARN7 | SQLCA +151 | 1 | A |
| SQLCA-PGM-NAME | SQLCA +152 | 8 | A |
| SQLCA-AUTHID | SQLCA +160 | 18 | A |
| SQLCA-PLAN-NAME | SQLCA +178 | 18 | A |

| | | | | |
|----------|------------|-----|---|------------|
| SQLCA | S | 344 | A | |
| SQLCAID | SQLCA | 8 | A | |
| SQLCODE | SQLCA +8 | 4 | B | 0 |
| SQLCSID | SQLCA +12 | 4 | B | 0 OCCURS 2 |
| SQLCERC | SQLCA +20 | 4 | B | 0 |
| SQLCNRP | SQLCA +28 | 4 | B | 0 |
| SQLCSER | SQLCA +36 | 4 | B | 0 |
| SQLCLNO | SQLCA +44 | 4 | B | 0 |
| SQLCMCT | SQLCA +48 | 4 | B | 0 |
| SQLCOPTS | SQLCA +52 | 4 | B | 0 |
| SQLCFJB | SQLCA +56 | 4 | B | 0 |
| SQLCPCID | SQLCA +60 | 4 | B | 0 |
| SQLCLCID | SQLCA +64 | 4 | B | 0 |
| SQLCERL | SQLCA +68 | 2 | B | 0 |
| SQLCERM | SQLCA +72 | 256 | A | |
| SQLSTATE | SQLCA +328 | 5 | A | |

| | | | | |
|-----------------|------------|-----|---|------------|
| DEFINE SQLCA | S | 136 | A | |
| DEFINE SQLCAID | SQLCA | 8 | A | |
| DEFINE SQLCABC | SQLCA +8 | 4 | B | 0 |
| DEFINE SQLCODE | SQLCA +12 | 4 | B | 0 |
| DEFINE SQLERRM | SQLCA +16 | 72 | A | |
| DEFINE SQLERRML | SQLCA +16 | 2 | B | 0 |
| DEFINE SQLERRMC | SQLCA +18 | 70 | A | |
| DEFINE SQLERRP | SQLCA +88 | 8 | A | |
| DEFINE SQLERRD | SQLCA +96 | 4 | B | 0 OCCURS 6 |
| DEFINE SQLWARN | SQLCA +120 | 8 | A | |
| DEFINE SQLWARN0 | SQLCA +120 | 1 | A | |
| DEFINE SQLWARN1 | SQLCA +121 | 1 | A | |
| DEFINE SQLWARN2 | SQLCA +122 | 1 | A | |
| DEFINE SQLWARN3 | SQLCA +123 | 1 | A | |
| DEFINE SQLWARN4 | SQLCA +124 | 1 | A | |
| DEFINE SQLWARN5 | SQLCA +125 | 1 | A | |
| DEFINE SQLWARN6 | SQLCA +126 | 1 | A | |
| DEFINE SQLWARN7 | SQLCA +127 | 1 | A | |
| DEFINE SQLWARN8 | SQLCA +128 | 1 | A | |
| DEFINE SQLWARN9 | SQLCA +129 | 1 | A | |
| DEFINE SQLWARNA | SQLCA +130 | 1 | A | |
| DEFINE SQLEXT | SQLCA +131 | 5 | A | |

Sample Database

The following example illustrates the two tables used for all the examples in this chapter:

| | | | | | |
|----------|---------------------------|--------|----------|----------|--------|
| TABLE: | PERSONNEL | | | | |
| COLUMNS: | EMPNAME | | WORKDEPT | EMPPHONE | SALARY |
| DATA: | NORIDGE | DEBBIE | 901 | 5001 | 32400 |
| | OSMON | SAMUEL | 901 | 5004 | 62800 |
| | MILLER | JOAN | 950 | 6034 | 31360 |
| | EPERT | LINDA | 950 | null | 31040 |
| | STRIDE | ANN | 901 | null | 38640 |
| | ROGERS | PAT | 921 | 2231 | 32900 |
| EMPNAME | - CHAR(20) (NOT NULL) | | | | |
| WORKDEPT | - DECIMAL(3,0) (NOT NULL) | | | | |
| EMPPHONE | - DECIMAL(5,0) (NULL) | | | | |
| SALARY | - DECIMAL(8,2) (NOT NULL) | | | | |

| | | |
|---|-----------------|-------------------------|
| TABLE: | DEPARTMENTS | |
| COLUMNS: | DEPTNAME | DEPTNUMBER |
| DATA: | SHIPPING | 901 |
| | HUMAN RESOURCES | 921 |
| | ACCOUNTING | 950 |
| | DATA PROCESSING | 951 |
| DEPTNAME | - | VARCHAR(20) (NOT NULL) |
| DEPTNUMBER | - | DECIMAL(3,0) (NOT NULL) |
| WORKDEPT in the PERSONNEL table corresponds with the DEPTNUMBER in the DEPARTMENTS table. | | |

Working Storage Definitions

The following example shows working storage field definitions for the sample tables in the previous example:

```

DEFINE EMPNAME      W 20 A
DEFINE WORKDEPT     W  2 P 0
DEFINE EMPPHONE     W  3 P 0
DEFINE DEPTNAME     W 22 A   VARYING
DEFINE DEPTNUMBER   W  2 P 0
DEFINE NULLPHONE    W  2 B 0 . * NULL INDICATOR
DEFINE SYS-USERID   W  8 A   VALUE('SQLDBA')   . * SQL/DS USERID
DEFINE PASSWORD     W  8 A   VALUE('SQLDBAPW')  . * SQL/DS PASSWORD

```

Automatic Processing

Introduction

This chapter describes automatic table processing. With automatic processing, you can retrieve selected data (or all data) from every row in a table or view.

CA-Easytrieve Plus Files

CA-Easytrieve Plus can automate SQL cursor management when you associate an SQL cursor with a CA-Easytrieve Plus file. The SQL file can then be accessed with the JOB INPUT statement. With each iteration of the JOB statement or activity, another row from the table is automatically retrieved into the file's data area. Even if you only have a basic knowledge of SQL, you can report on data contained in an SQL database.

Automatic Retrieval Without a File

Automatic retrieval does not require that you define a CA-Easytrieve Plus file. In this read-only method, SQL must be coded on the JOB statement in place of a file name. You must code a SELECT statement directly after the JOB statement to specify the columns to retrieve and the host variables to receive the data. Each time the JOB activity is iterated, another row of SQL data is retrieved. This is a simple way to retrieve SQL data into working storage or into an extract file for subsequent output.

Specifying Automatic Input

Automatic input is specified using the JOB statement and either the SELECT statement with the select-clause, the FILE statement with the SQL keyword plus select-clause, or a combination of these statements. The possible approaches are as follows:

1. JOB INPUT SQL
SELECT select-clause

The JOB statement uses the SQL keyword to indicate that input is coming from an SQL table. The SELECT statement specifies the select-clause, which identifies the table and provides other parameters for automatic input.

2. FILE filename SQL (select-clause)
JOB INPUT filename

The FILE statement uses the SQL keyword to indicate that filename is an SQL file and uses the select-clause to specify parameters for automatic input. The JOB statement names the SQL file.

3. FILE filename SQL
JOB INPUT filename
SELECT select-clause

The FILE statement uses the SQL keyword to indicate that filename is an SQL file. The JOB statement names the SQL file. The SELECT statement identifies the information to retrieve. The SELECT statement is required since no select-clause was coded on the FILE statement.

4. FILE filename SQL (select-clause)
JOB INPUT filename
SELECT select-clause

This is the same as approach 2 above, except that the select-clause on the SELECT statement overrides the select-clause on the FILE statement.

Note: If the select-clause is not coded on the FILE statement, the SELECT statement must immediately follow the JOB statement.

FILE Statement

The CA-Easytrieve Plus FILE statement can identify a file as an SQL file and specify the select-clause. When used in this way, the FILE statement is limited to the following syntax.

| | | |
|---------------|-----------------------|---|
| FILE filename | SQL [(select-clause)] | + |
| | [DEFER] | + |
| | [{IBM }] | |
| | [{IBMKOREA}] | |
| | [{JEF }] | |
| | [{JEF4040 }] | |
| | [DBCSCODE {JIPSE }] | |
| | [{JIS }] | |
| | [{KEIS }] | |
| | [{MELCOM }] | |
| | [{SHOWA }] | |
| | [{TORAY }] | |

filename

This is the SQL filename. This filename can subsequently be referenced on the JOB statement or on a GET statement. Filename can be used as a synchronized file.

SQL [(select-clause)]

SQL identifies filename as an SQL file. Select-clause is specified in the same manner as the select-clause used on the SELECT statement (see Select-Clause in the description of the SELECT statement).

- If select-clause is coded, it must be in parentheses.
- If select-clause is not coded, a SELECT statement containing the select-clause must be coded following the JOB statement.
- If select-clause is not coded, you cannot use filename on a GET statement.

[DEFER]

DEFER opens an SQL cursor at the execution of the first GET statement. This means that the cursor is opened after the user-specified start procedure. If DEFER is not coded, the cursor is opened before the user-specified start procedure.

[DBCSCODE]

DBCSCODE defines the CA-Easytrieve Plus code system that is associated with all CA-Easytrieve Plus fields defined for this file.

- If you do not code this option, then CA-Easytrieve Plus uses the Processing code system. The DBCS Options module identifies this code system. You can alter the code system by using the DBCSCODE option of the PARM statement.
- If your site does not support the DBCS option, then this option is invalid.
- If the file being defined is associated with an extended reporting printer that does not support DBCS data, then this keyword is invalid. Should the extended reporting printer support DBCS data, then you can use the DBCSCODE keyword to modify the DBCS code system of the printer.

Refer to the *CA-Easytrieve Plus Getting Started* for more information.

JOB Statement

The syntax of the JOB statement for SQL is as follows.

| | | |
|-----------|-------------------------|-------|
| JOB INPUT | {filename} {SQL { | . . . |
|-----------|-------------------------|-------|

When an SQL filename is specified on a JOB statement, input is based on the select-clause given on the FILE statement. If the keyword SQL is coded on the JOB statement, input is based on the select-clause given on the SELECT statement immediately following the JOB statement. Any nonzero SQLCODE condition from the select-clause terminates the CA-Easytrieve Plus execution.

Coding SQL or an SQL filename on the JOB statement opens an SQL cursor at the start of the job activity. An SQL FETCH command or statement executes for each execution of the JOB statement (including the first).

SELECT Statement

Code the SELECT statement immediately following the:

- JOB INPUT SQL statement, in which case the SELECT statement is required.
- JOB INPUT filename statement where:
 - The select-clause was not coded on the FILE statement. In this case, the SELECT statement is required.
 - You want to override the select-clause that was given on the FILE statement. In this case, the SELECT statement is optional.

The SELECT statement, or the select-clause on the FILE statement if coded, identifies the rows and columns that are to be input to the JOB activity. You can code only one SELECT statement in each JOB activity.

Select-Clause Syntax

The select-clause identifies the rows and columns that are input to the JOB activity.

```

SELECT      [ [DISTINCT] ] [ { { * } } ]
            [ [ ALL ] ] [ { { expression } } ] +
            [ { { table-name.* } } ]
            [ { { correlation-name.* } } ]

            [ { { expression } } ] [ ] } +
            [ [ , { { table-name.* } } ] ... ] } } +
            [ { { correlation-name.* } } ] [ ] }
            [ { } ] [ ] }

FROM table-name [correlation-name] +
    [ , table-name [correlation-name] ... ] +

[WHERE search-condition] +

[
  [GROUP BY column-name + ] +
  [ [ , column-name ... ] ]
]

[HAVING search-condition] +

[
  [
    [
      [DISTINCT] [ { { * } } ]
    ]
    [UNION SELECT [ ALL ] [ { { table-name.* } } ] + ]
    [ [ { { correlation-name.* } } ] ]
  ]
  [
    [ { { expression } } ] [ ] }
    [ [ , { { table-name.* } } ] ... ] } } +
    [ { { correlation-name.* } } ] [ ] }
  ]
  [
    FROM table-name [correlation-name] +
    [ [ , table-name [correlation-name] ... ] + ] +
    [ [WHERE search-condition] + ]
    [
      [
        [GROUP BY column-name + ] +
        [ [ , column-name ... ] ]
      ]
      [ [HAVING search-condition] ]
    ]
  ]
]

[
  [ORDER BY { { column-name } } [ASC] + ]
  [ { { integer } } [DESC] ]
  [ ]
  [
    [ { { column-name } } [ASC] ]
    [ [ , { { column-name } } [ASC] ] ]
    [ { { integer } } [DESC] ... ]
    [ { } [DESC] ]
  ]
] +

INTO :host-variable [ , :host-variable...]
```

```
[
]
[DISTINCT]
[ALL
]
[
]
```

DISTINCT eliminates duplicate rows. ALL specifies that duplicate rows are not eliminated. ALL is the default.

```
{ *
}
{expression
}
{table-name.*
}
{correlation-name.*}
```

These identify the columns to retrieve from the specified table.

FROM table-name [correlation-name]

Table-name specifies the table from which data is retrieved.

Correlation-name can define an alias for the table-name that immediately precedes the correlation-name.

[WHERE search-condition]

Search-condition specifies conditions for the retrieval of data. The search-condition is applied to the result of the FROM clause. Refer to your SQL guides for a description of the search-condition.

[GROUP BY column-name]

GROUP BY groups data from the FROM and WHERE clauses. Column-name cannot be a long string (more than 254 bytes in length).

[HAVING search-condition]

Search-condition also specifies the data provided to the user. HAVING can compare the results of all the returned data with a specific value in the data provided, such as the minimum or maximum value. Refer to your SQL guides for a description of the search-condition.

[UNION...]

The UNION verb includes rows from another table.

```
[
{
} [
] ]
[ORDER BY {column-name} [ASC ] ]
[
{integer
} [DESC] ]
[
{
} [
] ]
```

ORDER BY returns the rows of the result table in the order of the values of the specified column-names. ASC returns the rows in ascending order and is the default. DESC returns the rows in descending order. Integer references a column by its position rather than by a column-name.

INTO :host-variable

The INTO clause identifies where the column values are placed. The INTO clause must be the last clause coded in the select-clause.

Select-Clause Operation

If this execution is for an DB2 for VSE or ORACLE system, CA-Easytrieve Plus generates and executes a CONNECT statement. This means that the user does not need to include an SQL CONNECT statement when using CA-Easytrieve Plus automatic processing. The user ID and password values are those that were specified in the USERID parameter of the PARM statement.

CA-Easytrieve Plus checks the SQLCODE field following each execution of the select-clause.

- If the SQLCODE is a value other than a zero (0) or a no more rows found condition, CA-Easytrieve Plus issues an error message based on the SQL error and terminates execution.
- A no more rows found condition causes CA-Easytrieve Plus to initiate end of input processing: the FINISH PROC (if any) executes, spooled reports are printed, and the current JOB activity ends.

The select-clause on a FILE statement permits references to fields not yet defined, but all references must be defined by the first JOB or SORT statement.

The SQL cursor that is automatically defined by a SELECT statement or a FILE statement (with the SQL option) is closed following the JOB activity referencing it.

For FILE statements with the SQL option:

- When the select-clause encounters no more rows found condition, the SQL file is marked EOF (end-of-file). In the case where the JOB statement references the SQL file, execution of the JOB activity stops and the FINISH procedure (if present) executes.
- The system-defined field RECORD-COUNT contains the number of rows returned to CA-Easytrieve Plus.
- The length of the SQL file is the sum of the maximum lengths of all the fields in the file. The system-defined field RECORD-LENGTH contains this value.
- Fields are defined to the SQL file using any available means.
- The select-clause cannot reference a CA-Easytrieve Plus group level definition of a table name as a host variable.
- File statistics are produced at the end of execution of each JOB activity.

Generated Code

The pseudo-code, generated for automatic SQL processing, is:

```
* IF SQL/DS, ORACLE, OR CA-IDMS
  SQL CONNECT . . .
* END-IF
SQL DECLARE cursor CURSOR FOR select clause
SQL OPEN cursor
DO WHILE SQLCODE NE 100
  SQL FETCH cursor INTO :host-variable +
                        [, :host-variable...]
  process EZT+ code
END-DO
SQL CLOSE cursor
```

Controlled Processing

Overview

Controlled SQL Processing can be performed using the Native SQL commands or the GET statement if SQL files are used.

GET Statement

The syntax for the GET statement for SQL is as follows.

Syntax

```
GET filename [STATUS]
```

When an SQL filename is specified on a GET statement, an SQL FETCH statement is issued, and the next available row is returned from the SQL cursor. The STATUS keyword returns the SQLCODE in the system-defined field FILE-STATUS (defined as 4 B 0). If STATUS is not coded, FILE-STATUS contains zeros. To use an SQL filename on GET, code the select-clause on the FILE statement.

An SQL filename on the GET statement opens an SQL cursor at the start of the job activity, unless DEFER is coded on the FILE statement. If DEFER is coded, an SQL cursor opens at the execution of the first GET statement.

If the STATUS keyword is not coded on the GET statement for an SQL file, a nonzero SQLCODE condition terminates the CA-Easytrieve Plus execution.

Remember, for FILE statements with the SQL options:

- When the select-clause encounters an SQL no more rows condition, the SQL file is marked EOF.
- The system-defined field RECORD-COUNT contains the number of rows returned to CA-Easytrieve Plus.

- The length of the SQL file is the sum of the maximum lengths of all the fields in the file. The system-defined field RECORD-LENGTH contains this value.
- Fields are defined to the SQL file using any available means.
- The select-clause cannot reference a CA-Easytrieve Plus group-level definition of a table name as a host variable.
- File statistics are produced at the end of each JOB activity execution.

Native SQL

This method of processing uses native SQL statements that are equivalent to many of those used in COBOL. By using these native SQL statements, you control the SQL cursor operation. All native SQL statements are prefixed with the SQL keyword.

Syntax

`SQL native-sql-statement`

Usage Notes

See the specific database management system guide for information about syntax for native database statements. Listed below are the SQL statements currently supported by the SQL interface.

DB2 for OS/390 SQL Statements:

- `ALLOCATE cursor-name *(for static-only processing)`
- `ALTER`
- `ASSOCIATE *(for static-only processing)`
- `CALL procedure-name *(for static-only processing)`
- `CLOSE cursor-name`
- `COMMENT ON`
- `COMMIT {work}`
- `CONNECT`
- `CREATE`
- `DECLARE cursor-name {with hold}`
- `DELETE {where current of cursor-name}`
- `DROP`
- `EXPLAIN`

- FETCH cursor-name
- GRANT
- INSERT
- LABEL
- LOCK
- OPEN cursor-name
- RELEASE
- REVOKE
- ROLLBACK {work}
- SELECT INTO *(for static-only processing)
- SET CONNECTION
- SET CURRENT DEGREE
- SET CURRENT PACKAGESET
- SET CURRENT SQLID
- SET host-variable
- UPDATE {where current of cursor-name}.

* Refer to SQLSYNTAX in the PARM statement.

DB2 for VSE SQL Statements:

- ACQUIRE
- ALTER
- CLOSE cursor-name
- COMMENT
- COMMIT {work}
- CONNECT :userid
- CONNECT TO :database
- CREATE
- DECLARE CURSOR-NAME
- DELETE {where current of cursor-name}
- DROP
- EXPLAIN
- FETCH cursor-name
- GRANT

- INSERT
- LABEL
- LOCK
- OPEN cursor-name
- PUT
- REVOKE
- ROLLBACK {work}
- UPDATE {where current of cursor-name}.

CA-Datacom/DB SQL Statements:

- ALTER
- CLOSE cursor-name
- COMMENT
- COMMIT {work}
- CREATE
- DECLARE cursor-name
- DELETE {where current of cursor-name}
- DROP
- FETCH cursor-name
- GRANT
- INSERT
- LOCK
- OPEN cursor-name
- REVOKE
- ROLLBACK {work}
- SELECT INTO
- UPDATE {where current of cursor-name}.

CA-IDMS SQL Statements:

- ALTER
- CLOSE cursor-name
- COMMIT {work} {continue} {release}
- CONNECT TO dictionary-name
- CREATE

- DECLARE cursor-name
- DELETE where search-condition *
- DROP
- EXPLAIN
- FETCH cursor-name
- GRANT
- INSERT
- OPEN cursor-name
- RELEASE
- RESUME
- REVOKE
- ROLLBACK {work}
- SUSPEND
- UPDATE where search-condition *.
- The DELETE and UPDATE can only execute using a search condition on the where clause. The “where current of cursor-name” syntax is not supported using dynamic SQL processing.

ORACLE Statements:

- DECLARE
- OPEN
- FETCH
- CLOSE
- UPDATE
- INSERT
- DELETE
- CONNECT (by parms or identified by password)
- COMMIT
- ROLLBACK
- ALTER
- COMMENT
- CREATE
- DROP
- GRANT

- LOCK
- REVOKE
- AUDIT
- NOAUDIT
- RENAME
- VALIDATE SET

Processing Requirements

- The SQL DECLARE statement must be coded in the Library Definition section of a CA-Easytrieve Plus program. All other SQL statements, except SQL INCLUDE, must be coded in the Activity Definition section.
- You should test the SQLCODE field in the SQLCA to determine if the execution of each controlled processing statement is successful.

If the SQLCODE field contains a zero (0), you should test the SQLWARN0 field to ensure that no warning conditions were issued during processing of the SQL statement. Refer to the appropriate SQL reference guide to determine acceptable values for SQLWARN0.

- All SQL INCLUDE statements and SQL-managed file definitions must be coded before any controlled SQL statements.

Operation

Coding native SQL statements requires an advanced knowledge of SQL statements and of the database to process. Native SQL statements can be coded in any JOB activity. You cannot code them in SORT or REPORT procedures.

CALL Statement

The syntax for the CALL statement as supported by DB2 for OS/390 is as follows.

Format A

| |
|----------------------------------|
| CALL procedure-name (parmlist) |
|----------------------------------|

Format B

```
CALL :procedure-name ( parmlist )
```

where the procedure name is provided as a host variable

Format A is the only supported format for the CALL Statement.

Format B is **not** supported by CA-Easytrieve Plus. CA-Easytrieve Plus performs some syntax checking of SQL statements, replacing host variable identifiers with a question mark. In the case of Format B, CA-Easytrieve Plus identifies the parameter list as a subscript of the variable procedure name and flags this as an error.

CALL, ASSOCIATE, and ALLOCATE

To use the CALL, ASSOCIATE, and ALLOCATE statements, you must have a BIND option of STATIC-ONLY. This requires the JCL shown for the EXTPDB2 procedure. (This JCL is shown in the EXTPDB2 Procedure section of the "Executing Your SQL Program" chapter.

These statements undergo partial syntax checking by the PanSQL interface. They undergo complete syntax checking when the static-command-program is processed by the DB2 for OS/390 preprocessor DSNHPC. The output from the DB2 for OS/390 preprocessor must be examined for any possible SQL errors.

Refer to the Static SQL Mode section in the "Executing Your SQL Program" chapter of this guide for a detailed explanation of the steps executed to run the program statically.

Executing Your SQL Program

DB2 for OS/390 Execution

Dynamic SQL Mode

The following example illustrates the JCL necessary to execute CA-Easytrieve Plus with DB2 for OS/390, using the Dynamic SQL mode.

OS/390 JCL:

```
//jobname JOB accounting.info,USER=userid
//stepname EXEC PGM=EZTPA00
//STEPLIB DD DISP=SHR,DSN=your.eztp.loadlib
// DD DISP=SHR,DSN=your.pansql.loadlib
// DD DISP=SHR,DSN=your.db2.sspgm.lib
//SYSPRINT DD SYSOUT=A
//SYSOUT DD SYSOUT=A
//SORTWK01 DD UNIT=SYSDA,SPACE=(CYL,1)
//SYSSNAP DD SYSOUT=A
//SYSUDUMP DD SYSOUT=A
//EZTVFM DD UNIT=SYSDA,SPACE=(4096,(100,100))
//SYSIN DD *
... CA-Easytrieve Plus DB2 source statements ...
/*
```

Note: The value of `sspgm` names your IBM DB2 for OS/390 load library, which contains the programs `DSNHLI2` and `DSNALI`.

Static SQL Mode

This topic describes the additional steps that must run to create the Static application plan.

Note: The JCL procedure (EZTPDB2) for building the static application plan is in the SAMPJCL library downloaded during installation.

Sample Job Stream

The procedure for building the Static application plan follows these steps:

1. The Pan/SQL interface called by CA-Easytrieve Plus writes the SQL statements, along with other control information, to a command program generation file (ddname = GENDATA).
2. The GENDATA file is processed by Pan/SQL to generate a valid assembler program for the IBM DB2 for OS/390 preprocessor.
3. The DB2 for OS/390 precompiler translates the command program assembler source and creates a DBRM (database request module) entry in the DBRMLIB.
4. The command program can then be assembled and link edited to produce the static command program.
5. The DBRM can then be bound into an application plan or package. The sample JCL creates a plan. You can modify this JCL to bind the DBRM into a package. The final planname must match the planname specified for the PLAN parameter.

PAN\$SQL DD File

You can code a PAN\$SQL DD statement to provide a plan name and DB2 for OS/390 subsystem to be used at the time of your execution. The PAN\$SQL DD file is processed only when executing statically and if the DB2 for OS/390 Call Attach Facility is used to establish a connection.

The PAN\$SQL file can also be used to indicate that you want to execute under the TSO Terminal Monitor Program in background mode. If TSO execution is specified, then the plan name and subsystem ID parameters are ignored.

Valid parameters for the PAN\$SQL file are the following:

- PLAN – provide the name of the DB2 for OS/390 plan to use for execution
- SSID – provide the name of the DB2 for OS/390 subsystem to use for the DB2 for OS/390 Call Attach Facility for a connection..
- TSO – indicates that you want to execute your CA-Easytrieve Plus program under the TSO Terminal Monitor Program in background mode. You must code the correct JCL.

The following is sample JCL for the PAN\$SQL statement:

```
//PAN$SQL DD *  
    PLAN=TESTPLAN,SSID=D510
```

The ability to specify a planname for execution enables you to compile and link your CA-Easytrieve Plus DB2 for OS/390 application program once. The DBRM can then be bound into any DB2 for OS/390 subsystem with any planname.

Execution under TSO resolves the problem of called DB2 for OS/390 subroutines that previously had to be linked with DSNALI, the DB2 for OS/390 Call Attach Facility module. This restriction required subroutines to be linked one way for other applications.

If your CA-Easytrieve Plus Program contains SQL statements and it also calls COBOL (or other language) subroutines, you can now share those subroutines with CA-Easytrieve Plus applications and other non-CA-Easytrieve Plus applications. You can link your COBOL subroutines once with DSNELI and it can be used by all of your applications..

Sample JCL for Execution Under TSO

```
//EXECEZT      EXEC  PGM=IKJEFT01,DYNAMBR=20
//STEPLIB      DD   DISP=SHR,DSN=your.ezt.target.library
//             DD   DISP=SHR,DSN=your.ezt.db2.application.library
//             DD   DISP=SHR,DSN=your.pansql.tso.load.library
//             DD   DISP=SHR,DSN=your.db2.sdsnload.library
//PAN$SQL      DD   *
//             TSO                                     <=== Indicate TSO execution
//SYSPRINT     DD   SYSOUT=*
//SYSTSPRT     DD   SYSOUT=*
//SYSUDUMP     DD   SYSOUT=*
//SYSOUT       DD   SYSOUT=*
//REPORT       DD   SYSOUT=*
//SYSIN        DD   DUMMY
//SYSTSIN      DD   *
DSN SYSTEM(D510)
RUN PROGRAM(eztpgm) PLAN(testplan)
END
/*
```

EZTPDB2 Procedure

The EZTPDB2 procedure is installed as member DB2BINDP in your SAMPJCL dataset. The EZTPDB2 procedure builds the static application program and plan.

```

//*****
//*
//*   PROC TO:  1)  Compile the CA-Easytrieve Plus program
//*             2)  Link the CA-Easytrieve Plus program
//*             3)  Process the Pan/SQL DB2 static command program
//*             4)  Preprocess the static command program by DB2
//*             5)  Assemble the static command program
//*             6)  Link the static command program
//*             7)  Run TSO to BIND and GRANT authorization
//*
//*****
//EZTPDB2      PROC  DBRMLIB=,          /*DBRMLIB                      */
//              DB2LIB=,                /*DB2 LOAD LIB                  */
//              RUNLIB=,                 /*DB2 RUNLIB                    */
//              EZTPLIB=,                /*EZTP LOAD LIB                 */
//              EZTPPGM=,                /*EZTP LINKED PGM LIB          */
//              PSQLLIB=,                /*PAN/SQL LOAD LIB             */
//              DBRMNME=,                /*DBRMNAME                      */
//              STCPGMN=                  /*STATIC.CMD.PROGRAM           */
//*
//*****
//*
//*           STEP 1:  Compile CA-Easytrieve Plus program
//*
//*****
//EZTPLUS      EXEC  PGM=EZTPA00
//STEPLIB      DD   DISP=SHR,DSN=&EZTPLIB
//              DD   DISP=SHR,DSN=&PSQLLIB
//              DD   DISP=SHR,DSN=&DB2LIB
//SYSPRINT     DD   SYSOUT=*
//SYSLIN       DD   DISP=(NEW,PASS),DSN=&&SYSLIN,
//              UNIT=SYSDA,
//              DCB=(BLKSIZE=3120,LRECL=80,RECFM=FB),
//              SPACE=(3120,(100,50),RLSE)
//GENDATA      DD   DISP=(NEW,PASS),DSN=&&EZTPDB2,
//              UNIT=SYSDA,
//              DCB=(BLKSIZE=3120,LRECL=80,RECFM=FB),
//              SPACE=(3120,(100,50),RLSE)
//EZTVFM       DD   UNIT=SYSDA,SPACE=(CYL,(1,5))
//*****
//*
//*           STEP 2:  CA-Easytrieve Plus Link
//*
//*****
//LKEDEZT      EXEC  PGM=IEWL,COND=(0,NE,EZTPLUS)
//SYSPRINT     DD   SYSOUT=*
//SYSLIN       DD   DISP=(OLD,DELETE) DSN=&&SYSLIN
//SYSMOD       DD   DISP=SHR,DSN=&EZTPPGM
//SYSUT1       DD   UNIT=SYSDA,SPACE=(CYL,(1,5))

```

```

//*****
//*
//*          STEP 3:  Generate static command program statements
//*
//*****
//GEN      EXEC  PGM=DQSCGEN,COND=(0,NE,EZTPLUS)
//STEPLIB  DD   DISP=SHR,DSN=&PSQLLIB
//GENDATA   DD   DISP=(OLD,DELETE),DSN=&&EZTPDB2
//CMDPGM1   DD   DISP=(NEW,PASS),DSN=&&CPGM1,
//           UNIT=SYSDA,
//           DCB=(BLKSIZE=3120,LRECL=80,RECFM=FB),
//           SPACE=(TRK,(1,1))
//CMDPGM2   DD   DISP=(NEW,PASS),DSN=&&CPGM2,
//           UNIT=SYSDA,
//           DCB=(BLKSIZE=3120,LRECL=80,RECFM=FB),
//           SPACE=(TRK,(2,1))
//CMDPGM3   DD   DISP=(NEW,PASS),DSN=&&CPGM3,
//           UNIT=SYSDA,
//           DCB=(BLKSIZE=3120,LRECL=80,RECFM=FB),
//           SPACE=(TRK,(2,1))
//CMDPGM4   DD   DISP=(NEW,PASS),DSN=&&CPGM4,
//           UNIT=SYSDA,
//           DCB=(BLKSIZE=3120,LRECL=80,RECFM=FB),
//           SPACE=(TRK,(2,1))
//SYSPRINT  DD   SYSOUT=*
//ERRREPT   DD   SYSOUT=*
//*****
//
//*          STEP 4:  Preprocess the static command program by DB2
//*                  (DB2 Precompile)
//*
//*****
//DB2PRE    EXEC  PGM=DSNHPC,COND=(0,NE,EZTPLUS),
//              PARM='HOST(ASM),XREF ,SOURCE'
//STEPLIB    DD   DISP=SHR,DSN=&DB2LIB
//DBRMLIB    DD   DISP=SHR,DSN=&DBRMLIB(&DBRMNME)
//SYSIN      DD   DISP=(OLD,DELETE),DSN=&&CPGM1
//           DD   DISP=(OLD,DELETE),DSN=&&CPGM2
//           DD   DISP=(OLD,DELETE),DSN=&&CPGM3
//           DD   DISP=(OLD,DELETE),DSN=&&CPGM4
//SYSCIN     DD   DSN=&&DB2OUT,DISP=(NEW,PASS),
//           UNIT=SYSDA,DCB=BLKSIZE=3120,
//           SPACE=(TRK,(3,3))
//SYSUT1     DD   SPACE=(800,(1000,1000)),UNIT=SYSDA
//SYSUT2     DD   SPACE=(800,(1000,1000)),UNIT=SYSDA
//SYSPRINT   DD   SYSOUT=*
//SYSTEM     DD   SYSOUT=*
//*****
//
//*          STEP 5:  Assemble the static command program
//*
//*****
//ASMCMDS    EXEC  PGM=IEV90,COND=(0,NE,EZTPLUS),
//              PARM='OBJECT,NODECK,RENT,LIST'
//SYSIN      DD   DISP=(OLD,DELETE),DSN=&&DB2OUT
//SYSLIN     DD   DISP=(MOD,PASS),DSN=&&LOADSET,
//           UNIT=SYSDA,DCB=BLKSIZE=3120,
//           SPACE=(TRK,(10,5))
//SYSLIB     DD   DISP=(NEW,DELETE),DSN=&&SYSLIB,
//           UNIT=SYSDA,DCB=BLKSIZE=80,
//           SPACE=(TRK,(1,1,1))
//SYSUT1     DD   DSN=&&SYSUT1,UNIT=SYSDA,
//           SPACE=(TRK,(10,5))
//SYSPUNCH   DD   DUMMY
//SYSPRINT   DD   SYSOUT=*

```

```

//*****
//*
//*          STEP 6: Link edit the static command program
//*
//*****
//LINK      EXEC PGM=IEWL,COND=(0,NE,ASMCMD) ,
//          PARM='LET,LIST,CALL,RENT,MAP'
//SYSLIB    DD DISP=SHR,DSN=&DB2LIB
//SYSLIN    DD DISP=(OLD,DELETE),DSN=&&LOADSET
//SYSLMOD    DD DISP=SHR,DSN=&EZTPPGM(&STCPGMN)
//SYSUT1    DD UNIT=SYSDA,SPACE=(CYL,(1,1))
//SYSPRINT  DD SYSOUT=*
//*****
//*
//*          STEP 7: Bind and grant authorization to the
//*                  static command program's application plan
//*
//*****
//AUTH      EXEC PGM=IKJEFT01,DYNAMNBR=20,COND=(0,NE,ASMCMD)
//STEPLIB   DD DISP=SHR,DSN=&RUNLIB
//          DD DISP=SHR,DSN=&DB2MLIB
//DBRMLIB   DD DISP=SHR,DSN=&DBRMLIB
//SYSPRINT  DD SYSOUT=*
//SYSTSPRT  DD SYSOUT=*
//SYSOUT    DD SYSOUT=*
//REPORT    DD SYSOUT=*
//*
//          PEND

```

Execution JCL

The sample execution JCL is installed as member DB2BINDX into your SAMPJCL dataset. DB2BINDX executes the EZTPDB2 procedure shown on the previous pages. Step EXTPGO requires you to provide values for the program name to execute and the required libraries needed for STEPLIB.

```
//jobname JOB accounting.info,USER=userid,COND=(8,LT)
//*****
//*
//*      STEP A:  Execute the EZTPDB2 procedure
//*
//*****
//EZTPDB2 EXEC EZTPDB2,
//          DBRMLIB='your.dbrmlib'
//          DB2LIB='your.DB2.loadlib',
//          RUNLIB='your.DB2.runlib',
//          EZTPLIB='your.eztp.loadlib',
//          EZTPPGM='your.linked.eztpgm.loadlib',
//          PSQLLIB='your.pansql.loadlib',
//          DBRMNME='dbrmname',
//          STCPGMN='static.command.program.name'
//*****
//*
//*      DD statements for STEP 1 - EZT Compile
//*
//*****
//EZTPLUS.SYSIN DD *
PARM LINK(eztpgm) PLAN (planname stcpgm) BIND STATIC-ONLY ...
... CA-Easytrieve Plus source statements ...
/*
//*****
//*
//*      DD statements for STEP 7 - - Bind and Grant
//*
//*****
//AUTH.SYSTSIN DD *
DSN SYSTEM(ssid)
BIND PLAN(planname) MEMBER(dbrmname) -
ACT(REPLACE) ISOLATION(CS)
RUN PROGRAM(DSNTIAD) PLAN(DSNTIADs)
END
/*
//AUTH.SYSIN DD *
GRANT EXECUTE ON PLAN planname TO PUBLIC;
/*
//*****
//*
//*      STEP B:  Execute the linked EZTP program
//*
//*****
//EZTPGO EXEC PGM=eztpgm
//STEPLIB DD DSN=your.EZTPLIB.dataset,DISP=SHR
//          DD DSN=your.EZTPPGM.dataset,DISP=SHR
//          DD DSN=your.PSQLLIB.dataset,DISP=SHR
//          DD DSN=your.DB2LIB.dataset,DISP=SHR
//SYSPRINT DD SYSOUT=*
//EZTVFM DD UNIT=SYSDA,SPACE=(CYL,(1,5))
// ... Other DD statements as needed by the program
```

Procedure Overrides

| Procedure | Action |
|-----------|--|
| DBRMLIB | Must name a library to contain the DBRM for the CA-Easytrieve Plus static application plan. |
| DB2LIB | Names your IBM DB2 <i>load library</i> that contains the program DSNHPC. |
| RUNLIB | Names your IBM DB2 <i>runlib</i> containing the program DSNTIAD. |
| EZTPLIB | Names the CA-Easytrieve Plus <i>loadlib</i> . |
| EZTPPGM | Names a <i>user loadlib</i> to contain the linked CA-Easytrieve Plus program and the static command program. |
| PSQLLIB | Names your Pan/SQL <i>load library</i> . |
| DBRMNME | Identifies the DBRM. |
| STCPGMN | Identifies the generated static command program. The name must match the <i>stcpgm</i> specified on the PARM statement in your CA-Easytrieve Plus program source. If no <i>stcpgm</i> is specified on the PARM statement, STCPGMN must be the same as the <i>planname</i> specified on the PARM statement. |

JCL Modifications

AUTH.SYSTSIN binds the STATIC SQL program plan.

- Change *ssid* to reference the default DB2 for OS/390 subsystem you are using.
- Change *planname* to be the same value you specified on the PARM statement.
- Change *dbrmnme* to be the same value you specified on the DBRMNME parameter of the procedure overrides.
- Change DSNTIADs to reference the correct PLAN for the DB2 for OS/390 utility program DSNTIAD.

AUTH.SYSIN grants access to the static SQL program plan to PUBLIC. Change *planname* to be the same as that specified on the BIND for AUTH.SYSTSIN.

Step DP2PRE ends with a return code of 4. This is a normal operation.

Mixed IMS and DB2 for OS/390 Execution

If your CA-Easytrieve Plus program accesses an IMS database and DB2 for OS/390 database, you should run your program under the control of DB2-DL/I BATCH SUPPORT.

This ensures synchronization of checkpoints and rollbacks across both IMS and DB2 for OS/390.

Under this control, SQL COMMITs and SQL ROLLBACKs are not permitted.

To do this, change your execution JCL to execute Module DSNMTV01 instead of EZTPA00 or your linked application program. DSNMTV01 then loads the real program.

The following is sample JCL:

```
//EZIMSD2 EXEC PGM=DFSRR00,
//          PARM='DLI,DSNMTV01,PSBNAME,,,,,,,,,O,N,N,'
//STEPLIB DD DSN=IMSVS.RESLIB,DISP=SHR
//          DD DSN=IMSVS.PGMLIB,DISP=SHR
//          DD DSN=your.ibm.db2.sspgm.library,DISP=SHR
//          DD DSN=your.eztp.loadlib,DISP=SHR
//          DD DSN=your.pansql.loadlib,DISP=SHR
//IMS      DD DSN=IMSVS.PSBLIB,DISP=SHR
//          DD DSN=IMSVS.DRDLIB,DISP=SHR
//SYSOUT DD SYSOUT=*
//EZTVFM DD UNIT=SYSDA,SPACE=(4096,(100,100))
//DDOTV02 DD DSN=##TEMP,DISP=(NEW,PASS),SPACE=(TRK,(5,5),
//          UNIT=SYSDA,DCB=(RECFM=VB,LRECL=4092,BLKSIZE=4096)
//DDITV02 DD *
//          SSN,LIT,ESMT,RTT,ERR,CRC,CONNECTION_NAME,PLAN,PROG
/*
//SYSIN DD *
//          CA-Easytrieve Plus statements follow
//          .
//          .
/*
//
```

Note: Under the control of DB2 for OS/390 or DLI batch support, your STEPLIB must define the IMS RESLIB before the DB2 for OS/390 library.

The DDITV02 DD defines the following parameters:

| Parameter | Description |
|-----------------|--|
| SSN | DB2 for OS/390 subsystem |
| LIT | Language Interface token value |
| ESMT | Initialization module name, must be DSNMIN10 |
| RTT | Resource Translation Table |
| ERR | Region Error Option |
| CRC | Command Recognition Character |
| CONNECTION_NAME | A unique one-to-eight-character name |
| PLAN | DB2 for OS/390 plan name |
| PROG | Application program name to execute—either EZTPA00 or linked program name. |

Refer to your IBM DB2 guides for a detailed explanation of these parameters.

DB2 for VSE Execution

The following example illustrates the JCL necessary to execute CA-Easytrieve Plus with DB2 for VSE.

VSE JCL

```
* $$ JOB JNM=jobname
// JOB      jobname
// UPSI     b
// DLBL     EZTP,'your.eztp.library'
// EXTENT   ,volser
// ASSGN    SYS001,DISK,VOL=volser,SHR
// DLBL     SORTWK1,,0
// EXTENT   SYS001,volser,,start,lgh
// ASSGN    SYS010,DISK,VOL=volser,SHR
// DLBL     EZTVFM,,0,SD
// EXTENT   SYS010,volser,,start,lgh
// DLBL     SQLLIB,'your.pansql.library',0,SD
// EXTENT   ,volser
// LIBDEF   PHASE,SEARCH=(SQLLIB.sublib,EZTP.sublib)
// EXEC     EZTPA00,SIZE=512K
// PARM     USERID('user-id' 'password')
//          ... CA-Easytrieve Plus SQL/DS source statements ...
/*
* $$ E0J
```

Note: When executing a CA-Easytrieve Plus program with DB2 for VSE, no JCL changes are required for Multiple User Mode. For the Single User Mode of DB2 for VSE, you should specify the SIZE=(AUTO,xxxK) parameter on your JCL EXEC statement, where xxxK is the amount of storage required for normal CA-Easytrieve Plus execution. The xxxK value is usually between 256K and 512K.

CA-IDMS/SQL Execution

The following example illustrates the OS/390 JCL to execute CA-Easytrieve Plus with IDMS/SQL under central version.

OS/390 JCL

```
//jobname JOB accounting.info
//stepname EXEC PGM=EZTPA00
//STEPLIB DD DISP=SHR,DSN=your.eztp.loadlib
// DD DISP=SHR,DSN=your.idms.loadlib
// DD DISP=SHR,DSN=pansql.idms.loadlib
//SYSPRINT DD SYSOUT=A
//SYSOUT DD SYSOUT=A
//SORTWK01 DD UNIT=SYSDA,SPACE=(CYL,1)
//SYSCTL DD DISP=SHR,DSN=idms.sysctl
//SYSIDMS DD DISP=SHR,DSN=your.sysidms.parm.file
//EZTVFM DD UNIT=SYSDA,SPACE=(4096,(100,100))
//SYSIN DD *
...CA-Easytrieve Plus source statements ...
/*
```

Note: To run in local mode, you must make the CA-IDMS dictionary and database available to CA-Easytrieve Plus through IDMS Dynamic Allocation services by defining them in the DMCL or through DD statements in the JCL.

VSE JCL

The following example illustrates the VSE JCL to execute CA-Easytrieve Plus with IDMS/SQL under central version.

```
* $$ JOB JNM=jobname
// JOB      jobname
// UPSI     b
// DLBL     EZTP,'your.eztp.library'
// EXTENT   ,volser
// DLBL     IDMS,'idms.library'
// EXTENT   ,volser
// DLBL     SQLLIB,'your.pansql.library'
// EXTENT   ,volser
// DLBL     SYSIDMS,'your.idms.sysidms.file'
// EXTENT   ,volser
// DLBL     SYSCTL,'your idms.sysctl.file'
// EXTENT   ,volser
// LIBDEF   PHASE,SEARCH=(EZTP.sublib,SQLLIB.sublib,IDMS.sublib)
// ASSGN    SYS001,DISK,VOL=volser,SHR
// DLBL     SORTWK1,,0
// EXTENT   SYS001,volser,,,start,length
// DLBL     EZTVFM,,0,SD
// EXTENT   SYS010,volser,,,start,length
// EXEC     EZTPA00
... CA-Easytrieve Plus source statements ...
```

Note: To run in local mode, you must make the CA-IDMS dictionary and database file available to CA-Easytrieve Plus. This can be done either through IDMS dynamic allocation service in the DMCL or by specifying DLBLs in the JCL.

CA-Datacom/SQL Execution

The following example illustrates the JCL necessary to compile and go with CA-Datacom/SQL.

OS/390 JCL

```
//jobname    JOB accounting.info
//stepname   EXEC  PGM=EZTPA00,REGION=512K
//STEPLIB   DD  DISP=SHR,DSN=your.eztp.loadlib
//          DD  DISP=SHR,DSN=your.pansql.loadlib
//          DD  DISP=SHR,DSN=your.datacom.CUSLIB
//          DD  DISP=SHR,DSN=your.datacom.CAILIB
//SYSPRINT  DD  SYSOUT=A
//SYSSNAP   DD  SYSOUT=A
//SYSOUT    DD  SYSOUT=A
//SORTWK01  DD  UNIT=SYSDA,SPACE=(CYL,1)
//EZTVFM    DD  UNIT=SYSDA,SPACE=(4096,(100,100))
//userfile  DD  dd-parms
//SYSIN     DD  *
... CA-Easytrieve Plus source statements ...
```

VSE JCL Examples

The following example illustrates the JCL necessary to compile and go with CA-Datcom/SQL.

```
* $$ JOB JNM=jobname
// JOB jobname
// DLBL EZTP,'your.eztp.library,0,SD
// EXTENT SYS003,volser,1,0,start,lgh
// ASSGN SYS003,nnn
// DLBL SQLLIB,'your.pansql.library'
// EXTENT ,volser
// DLBL DATACOM,'your.datacom.library'
// EXTENT ,volser
// LIBDEF *,SEARCH(EZTP.sublib,SQLLIB.sublib,DATACOM.sublib)
// ASSGN SYSOUT,...
// ASSGN SYS010,...
// ASSGN SYS008,...
// DLBL SORTWK1,,0,DA
// EXTENT SYS001,volser,,start,lgh
// DLBL EZTVFM,,0,SD
// EXTENT SYS010,volser,,start,lgh
// DLBL INREC,,0,SD
// EXTENT SYS008,volser,,start,lgh
// EXEC EZTPA00,SIZE=512K
      CA-Easytrieve Plus source statement
/*
/&
* $$ EOJ
```

ORACLE Execution

The following JCL illustrates how to run a CA-Easytrieve program with ORACLE.

ORACLE JCL

```
//jobname      JOB accounting.info
//stepname     EXEC PGM-EZTPA00,REGION-512K
//STEPLIB      DD DISP=SHR,DSN=your.eztp.loadlib
//             DD DISP=SHR,DSN=your.oracle.pansql.loadlib
//             DD DISP=SHR,DSN=your.oracle.SQLLIB
//             DD DISP=SHR,DSN=your.oracle.CMDLOAD
//SYSPRINT     DD SYSOUT=A
//SYSSNAP      DD SYSOUT=A
//SYSOUT       DD SYSOUT=A
//SORTWK01     DD UNIT=SYSDA,SPACE=(CYL,1)
//EZTVFM       DD UNIT=SYSDA,SPACE=(4096,(100,100))
//userfile     DD dd-parms
//SYSIN        DD *
              CA-Easytrieve Plus source statements
```


Examples

The following examples illustrate the functions of the various SQL statements.

For information concerning %SQLTABLE, see the Sample Database section in the “Library Section Definition” chapter.

Automatic Retrieval

Automatic Retrieval - All Columns

The code in the following example retrieves all columns and all rows from the PERSONNEL table. A report is generated showing WORKDEPT, EMPNAME, and EMPPHONE. CA-Easytrieve Plus sorts the report by WORKDEPT.

```
%SQLTABLE .
JOB INPUT SQL
  SELECT * FROM PERSONNEL
    INTO :EMPNAME, :WORKDEPT, :EMPPHONE :NULLPHONE +
  IF NULLPHONE < 0 .* PHONE PRESENT?
    EMPPHONE = 0 .* NO, SET TO 0
  END-IF
  PRINT PERSNL
REPORT PERSNL LINESIZE 65
SEQUENCE WORKDEPT
LINE WORKDEPT EMPNAME EMPPHONE
```

Automatic Retrieval - Selected Columns

The code in the following example retrieves all rows of selected columns from the PERSONNEL table and generates a report showing WORKDEPT and EMPNAME. SQL orders the rows by WORKDEPT.

```
%SQLTABLE .
JOB INPUT SQL
  SELECT EMPNAME, WORKDEPT +
    FROM PERSONNEL +
    ORDER BY WORKDEPT +
    INTO :EMPNAME, :WORKDEPT
  PRINT PERSNL
REPORT PERSNL LINESIZE 65
LINE WORKDEPT EMPNAME
```

Automatic Retrieval - Multiple Tables

The code in the following example retrieves an employee name and the corresponding department name from the PERSONNEL and DEPARTMENTS tables. The PARM statement parameters are needed only for DB2 for VSE processing.

```
PARM USERID('SQLDBA' 'SQLDBAPW') +
      PREPNAME(EASYPLUS 'SQLDBA')
%SQLTABLE .
JOB INPUT SQL
  SELECT EMPNAME, DEPTNAME          +
     FROM PERSONNEL, DEPARTMENTS    +
     WHERE WORKDEPT = DEPTNUMBER    +
     INTO :EMPNAME, :DEPTNAME
  PRINT PERSNL
REPORT PERSNL LINESIZE 65
LINE EMPNAME DEPTNAME
```

Automatic Retrieval - SQL FILE

The following example demonstrates the use of an SQL file as automatic input in a JOB activity. Also, it demonstrates the use of the SQL catalog INCLUDE facility.

Note: The host variables on the select-clause cannot reference the table name.

```
DEFINE NULLPHONE W 2 B 0
FILE FILES SQL
  (SELECT * FROM PERSONNEL          +
   INTO :EMPNAME, :WORKDEPT, :EMPPHONE :NULLPHONE)
SQL INCLUDE LOCATION * FROM PERSONNEL
JOB INPUT FILES
  IF NULLPHONE < 0
    EMPPHONE = 0
  END-IF
  PRINT PERSNL
REPORT PERSNL LINESIZE 65
SEQUENCE WORKDEPT
LINE WORKDEPT EMPNAME EMPPHONE
```

Automatic Retrieval - SQL FILE

The following example demonstrates the use of an SQL file as automatic input in a JOB activity. The select-clause is not coded on the FILE statement. The SELECT statement must be coded immediately following the JOB statement. In this example, the select-clause can reference the table name as a host variable.

Note: The DEPTNAME field is a VARYING field.

```
FILE FILES SQL
SQL INCLUDE LOCATION * FROM DEPARTMENTS
JOB INPUT FILES
SELECT * FROM DEPARTMENTS          +
      INTO :DEPARTMENTS
PRINT DEPT
REPORT DEPT LINESIZE 65
SEQUENCE DEPTNUMBER
LINE DEPTNUMBER DEPTNAME
```

Automatic Retrieval - SQL FILE Using SQL Functions

The following example shows using the SQL-supplied functions COUNT, AVG and SUM to produce information for use in the program.

```
FILE FILES SQL
SQL INCLUDE LOCATION * FROM PERSONNEL
*
NUM-IN-DEPT W 4 P 0
AVG-SALARY W 4 P 2
TOT-SALARY W 4 P 2
*
JOB INPUT FILES
SELECT WORKDEPT, COUNT(*), AVG(SALARY), SUM(SALARY) +
FROM PERSONNEL +
GROUP BY WORKDEPT +
HAVING DEPT < 80 +
INTO :WORKDEPT, :NUM-IN-DEPT, :AVG-SALARY, :TOT-SALARY
...
```

Automatic Retrieval - SQL FILE With NULL Indicators

The following example shows how to test for null indicators with the SQL INCLUDE statement. An indicator array is coded following the SQL INCLUDE. The indicator array occurs four times because there are 4 columns being defined through the SQL INCLUDE. In this case, only the third field is tested for NULL.

```
FILE FILES SQL
SQL INCLUDE LOCATION * FROM PERSONNEL
*
INDARRAY W 2 B 0 OCCURS 4. * Null indicator array
*
JOB INPUT FILES
SELECT * FROM PERSONNEL +
INTO :PERSONNEL :INDARRAY
IF INDARRAY(3) < 0. * Is the phone number(3rd column)null?
...
```

Automatic Retrieval - SQL FILE With Synchronized File Processing

The following example demonstrates using synchronized file processing to match a selected group of SQL rows to a flat file.

```
FILE PERSNL
EMP#   9   5  A
NAME  17  16  A
*
FILE PERSDB2 SQL +
  (SELECT DISTINCT NAME, EMPNO, REGION, ADDRSTREET +
    FROM DEMO.PERSNL +
    WHERE REGION IN ('2') +
    ORDER BY EMPNO +
    INTO :NAME, :EMPNO, :REGION, :ADDRSTREET)
  SQL INCLUDE LOCATION * FROM DEMO.PERSNL
*
JOB  INPUT  (PERSNL      KEY (EMP#)      +
            PERSDB2     KEY (EMPNO))
*
      IF MATCHED
      ...
```

Note: *SQL INCLUDE LOCATION ** must be coded after *SELECT* with Synchronized File Processing.

Controlled Retrieval

Native SQL - All Columns

The code in the following example retrieves all columns from the PERSONNEL table. The PARM statement parameters are needed only for DB2 for VSE processing.

```

PARM USERID('SQLDBA' 'SQLDBAPW') +
      PREPNAME(EASYPLUS 'SQLDBA')
%SQLTABLE .
SQL DECLARE CURSOR1 CURSOR FOR      +
SELECT *                             +
      FROM PERSONNEL
JOB INPUT NULL
* BELOW FOR SQL/DS ONLY
SQL CONNECT :SYS-USERID IDENTIFIED BY :PASSWORD
PERFORM CHECKSQL
* ABOVE FOR SQL/DS ONLY
SQL OPEN CURSOR1
PERFORM CHECKSQL
DO WHILE SQLCODE NE 100
  SQL FETCH CURSOR1                  +
      INTO :EMPNAME, :WORKDEPT, :EMPPHONE :NULLPHONE
  PERFORM CHECKSQL
  IF NULLPHONE < 0      .* PHONE PRESENT?
  EMPPHONE = 0          .* NO, SET TO 0
  END-IF
  IF SQLCODE NE 100    .* NOT END OF TABLE
  PRINT PERSNL
  END-IF
END-DO
SQL CLOSE CURSOR1
PERFORM CHECKSQL
STOP
CHECKSQL.PROC
IF SQLCODE NE 0 AND SQLCODE NE 100
  DISPLAY 'SQLCODE = ' SQLCODE
  STOP EXECUTE
END-IF
END-PROC
REPORT PERSNL LINESIZE 65
LINE EMPNAME WORKDEPT EMPPHONE

```

Native SQL - Reassign Departments

The code in the following example reassigns all employees in department 901 to department 109 and displays the names of those employees involved. The PARM SSID is necessary only if you want to access a DB2 for OS/390 subsystem other than the default.

```
PARM SSID('DB2B')
%SQLTABLE .
SQL DECLARE CURSOR1 CURSOR FOR      +
SELECT EMPNAME                      +
FROM PERSONNEL                      +
WHERE WORKDEPT = 901                +
FOR UPDATE OF WORKDEPT
JOB INPUT NULL
SQL OPEN CURSOR1
PERFORM CHECKSQL
DO WHILE SQLCODE NE 100
  SQL FETCH CURSOR1                  +
  INTO :EMPNAME
  PERFORM CHECKSQL
  IF SQLCODE NE 100                  + * NOT END OF TABLE
  PRINT PERSNL
  SQL UPDATE PERSONNEL               +
  SET WORKDEPT = 109                 +
  WHERE CURRENT OF CURSOR1
  PERFORM CHECKSQL
  END-IF
END-DO
SQL CLOSE CURSOR1
PERFORM CHECKSQL
STOP
CHECKSQL.PROC
IF SQLCODE NE 0 AND SQLCODE NE 100
  DISPLAY 'SQLCODE = ' SQLCODE
  STOP EXECUTE
END-IF
END-PROC
REPORT PERSNL LINESIZE 65
LINE EMPNAME
```

Native SQL - Update Phone Numbers

The following example illustrates the installation of a new phone system. All phone numbers have become five digits. The first character has become seven (7) and the remaining digits are the same as the old phone system.

If an employee did not previously have a phone number, his record is not updated. No update report is necessary.

```
JOB INPUT NULL
  SQL UPDATE PERSONNEL          +
    SET EMPPHONE = 70000 + EMPPHONE +
    WHERE EMPPHONE IS NOT NULL
  PERFORM CHECKSQL
  STOP
CHECKSQL. PROC
  IF SQLCODE NE 0 AND SQLCODE NE 100
    DISPLAY 'SQLCODE = ' SQLCODE
  STOP EXECUTE
END-IF
END-PROC
```

Native SQL - SQL FILE

The following example demonstrates the use of an SQL file as controlled input.

Note: The SQL FILE has the options of DEFER and DBCSCODE specified.

The SQL cursor (that is automatically defined) is not opened until the first GET statement is issued, thereby permitting the host variable in the into clause of the select-clause to initialize.

Note: The no-more-rows condition (EOF) could have been tested in various ways.

```
DEFINE DEPTNO W 3 P 0
FILE FILES DEFER DBCSCODE IBM          +
  SQL                                  +
  (SELECT * FROM PERSONNEL              +
    WHERE DEPTNUMBER > :DEPTNO          +
    INTO :EMPNAME, :WORKDEPT, :EMPPHONE :NULLPHONE)
SQL INCLUDE LOCATION * FROM PERSONNEL START START-UP
JOB INPUT NULL
GET FILES
IF EOF FILES      . *COULD HAVE BEEN: IF SQLCODE = +100
                  *OR                      IF FILES:FILE-STATUS = +100
  STOP
END-IF
IF NULLPHONE < 0
  EMPPHONE = 0
END-IF
PRINT PERSNL
START-UP. PROC
  DEPTNO = 945
END-PROC
REPORT PERSNL LINESIZE 65
SEQUENCE WORKDEPT
LINE WORKDEPT EMPNAME EMPPHONE
```


Index

A

Access module, 3-5
ALLOCATE locators, 2-2, 6-7
ASSOCIATE cursors, 2-2, 6-7
Automatic retrieval, 8-1
Automatic retrieval example, 8-1

C

CA-Datcom/DB, 3-5
CA-Datcom/SQL execution, 7-12
CA-Easytrieve Plus SQL statement rules, 2-3
CA-IDMS/SQL execution, 7-11
CALL statement, 6-6
Catalog INCLUDE facility
 ORACLE, 4-1
Controlled retrieval, 8-5
Controlled retrieval example, 8-5

D

Data types, 4-7, 4-8
DB2 for OS/390 execution, 7-1
DB2 for OS/390 revision summary, 2-2
DB2 for OS/390 static-command-program, 3-4
DB2 for VSE, 3-4

DB2 for VSE execution, 7-10
DDITV02 DD, 7-10
Default access module, 3-5
Documentation conventions, 1-3

E

End-of-File (EOF), 5-7
EVEN precision, 4-8
Execution under TSO, 7-3
EZTPA00, 7-9

F

FILE statement, 5-3

G

GET statement, 6-1

H

Host variables, 4-1
 definitions, 4-1

I

IMS and DB2 for OS/390 execution, 7-9

J

JOB statement, 5-4

M

Manual NULL processing, 4-6

Mixed IMS and DB2 for OS/390 execution, 7-9

Module DSNMTV01, 7-9

N

Native database statements, 6-2

Native SQL, 6-2

Native SQL command, 6-1

Native SQL commands, 4-1

Null data value, 4-6

Null, defined, 4-6

O

ORACLE execution, 7-13

P

PAN\$SQL JCL, 7-2

PAN\$SQL statement, 7-2

PARM statement parameters, 3-2

PLAN parameter, 3-4

Planname, 3-4

Planname, specifying for execution, 7-2

PREPNAME parameter
 PARM statement, 3-5

Processing NULLable fields, 4-6

Programming methods, 2-2

Publications

 CA-Easytrieve Plus, 1-2
 related, 1-3

Q

Qualifying DB2 for OS/390 tables, 3-6

S

Sample database, 4-12

SELECT statement, 5-4

Select-clause, 5-3, 5-7, 6-1

Specifying automatic input, 5-2

SQL catalog, 4-1

SQL catalog INCLUDE facility, 4-1

SQL communications area fields, 4-9

SQL data types, 4-7

SQL INCLUDE statement, 4-2

SQLID parameter, 3-3, 3-6, 3-7, 3-8

SQLSYNTAX parameter, 3-3

SSID, 7-2
 DB2 for VSE, 3-5

SSID parameter
 DB2 for OS/390, 3-4

Static application plan, 7-1

Subsystem ID, specifying for execution, 7-2

Synchronized file, 5-3

System-Defined file fields, 4-9

T

TSO execution, 7-2, 7-3

U

Unique access module, 3-5

Units of work, 3-1

USERID parameter

 PARM statement, 3-4

W

Working storage fields, 4-1