

CA OPS/MVS® Event Management and Automation

Quick Reference

Release 12.2



This Documentation, which includes embedded help systems and electronically distributed materials, (hereinafter referred to as the "Documentation") is for your informational purposes only and is subject to change or withdrawal by CA at any time. This Documentation is proprietary information of CA and may not be copied, transferred, reproduced, disclosed, modified or duplicated, in whole or in part, without the prior written consent of CA.

If you are a licensed user of the software product(s) addressed in the Documentation, you may print or otherwise make available a reasonable number of copies of the Documentation for internal use by you and your employees in connection with that software, provided that all CA copyright notices and legends are affixed to each reproduced copy.

The right to print or otherwise make available copies of the Documentation is limited to the period during which the applicable license for such software remains in full force and effect. Should the license terminate for any reason, it is your responsibility to certify in writing to CA that all copies and partial copies of the Documentation have been returned to CA or destroyed.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CA PROVIDES THIS DOCUMENTATION "AS IS" WITHOUT WARRANTY OF ANY KIND, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT WILL CA BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY LOSS OR DAMAGE, DIRECT OR INDIRECT, FROM THE USE OF THIS DOCUMENTATION, INCLUDING WITHOUT LIMITATION, LOST PROFITS, LOST INVESTMENT, BUSINESS INTERRUPTION, GOODWILL, OR LOST DATA, EVEN IF CA IS EXPRESSLY ADVISED IN ADVANCE OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The use of any software product referenced in the Documentation is governed by the applicable license agreement and such license agreement is not modified in any way by the terms of this notice.

The manufacturer of this Documentation is CA.

Provided with "Restricted Rights." Use, duplication or disclosure by the United States Government is subject to the restrictions set forth in FAR Sections 12.212, 52.227-14, and 52.227-19(c)(1) - (2) and DFARS Section 252.227-7014(b)(3), as applicable, or their successors.

Copyright © 2014 CA. All rights reserved. All trademarks, trade names, service marks, and logos referenced herein belong to their respective companies.

CA Technologies Product References

This document referenced the following CA products:

- CA OPS/MVS® Event Management and Automation (CA OPS/MVS)
- CA SYSVIEW® Performance Management (CA SYSVIEW)

Contact CA Technologies

Contact CA Support

For your convenience, CA Technologies provides one site where you can access the information that you need for your Home Office, Small Business, and Enterprise CA Technologies products. At <http://ca.com/support>, you can access the following resources:

- Online and telephone contact information for technical assistance and customer services
- Information about user communities and forums
- Product and documentation downloads
- CA Support policies and guidelines
- Other helpful resources appropriate for your product

Providing Feedback About Product Documentation

If you have comments or questions about CA Technologies product documentation, you can send a message to techpubs@ca.com.

To provide feedback about CA Technologies product documentation, complete our short customer survey which is available on the CA Support website at <http://ca.com/docs>.

Contents

Chapter 1: About This Guide	7
Chapter 2: Common OPSVIEW Menus	9
Chapter 3: Host Commands	11
ADDRESS OPER—Perform Automated Tasks	11
ADDRESS OPSCTL—Control Components	12
STATESET Command—Set the State for a Resource	16
ADDRESS SQL—Create and Maintain SQL Tables.....	17
ADDRESS WTO—Issue WTO Messages	18
Chapter 4: OPSLOG Browse Primary Commands	21
Chapter 5: POI Command Processors	23
OPSDOM—Delete an Operator Message.....	23
OPSQL Command—Invoke SQL Statements	23

Chapter 1: About This Guide

This Quick Reference provides both new and experienced users with a visual reminder of the most commonly used menus, commands, and actions. It will help new CA OPS/MVS users become more productive with CA OPS/MVS more quickly.

Additional information about the topics presented in this reference can be found in the following CA OPS/MVS guides:

- *AOF Rules User Guide*
- *Command and Function Reference*
- *OPSVIEW User Guide*
- *Parameter Reference*
- *User Guide*

Chapter 2: Common OPSVIEW Menus

To quickly navigate the OPSVIEW menus, use the ISPF jump function followed by the option specification. For example, enter =2.1 to jump to the AOF Edit menu. The following table provides jumps to the most frequently used OPSVIEW menus:

■ AOF

Jump	Menu	Lets You...
=2.1	AOF Edit	Edit and test AOF rules before putting them into production
=2.2	AOF Compile	Maintain the AOF test compiled rules library
=4.5.1	AOF Control	Control your production rules and rule sets
=4.5.3	AOF Enabled	Create an interactive list of enabled rules

■ Editors

Jump	Menu	Lets You...
=2.1	AOF Edit	Edit and test AOF rules before putting them into production
=2.2	AOF Compile	Maintain the AOF test compiled rules library
=2.3	Easy Rule	Create or modify rules using panels
=2.4	REXX Edit	Edit, compile, and test REXX programs
=2.6	Table Edit	Create and edit tables used by the Relational Data Framework (RDF)

■ Product Control

Jump	Menu	Lets You...
=4.1.1	Product Parameters	View and modify parameter settings
=4.3	OSF Information	View detailed execution statistics from the OSF panel
=4.5.1	AOF Control	Control your production rules and rule sets
=4.5.3	AOF Enabled	Create an interactive list of enabled rules
=4.6	Start the Main Product	Start CA OPS/MVS
=4.8	Global Variables	Control global variables
=4.11.1	SSM Control	Set and display SSM parameters and resource tables

■ **Messages**

Jump	Menu	Lets You...
=5.5	Message ID Lookup	Display information about CA OPS/MVS and SOF messages

■ **Product Levels**

Jump	Menu	Lets You...
=5.6	Product Releases	Display product releases

■ **Utilities**

Jump	Menu	Lets You...
=7.1	OPSLOG Utilities	Browse or restore archived OPSLOGs
=7.2	Automation Analyzer	Analyze the messages in an OPSLOG
=7.5	Global Variable Backup	Create a backup copy of your global variables
=1.3	ISPF Utility Selection	Use the ISPF utility selection panel

■ **Primary Access**

Jump	Menu	Lets You...
=I	ISPF/PDF	Use the ISPF/PDF services
=S	SYSVIEW	Access the CA SYSVIEW Performance Management product

Chapter 3: Host Commands

This section contains frequently used host commands. The default keywords are underscored.

ADDRESS OPER—Perform Automated Tasks

Use the ADDRESS OPER host environment to perform automated tasks with your CA OPS/MVS AOF rules and OPS/REXX programs. These tasks include issuing z/OS, JES, subsystem, or product specific commands.

```
ADDRESS OPER "keywords"
```

```
/* optional keywords */  
BMPCMDOUT(OPSLOG|WTO|NONE)  
COMMAND(text)  
CAPTURE(msgtextlist)  
CMDECHO(YES|NO)  
CMDLOG(YES|NO)  
CMDWAIT(seconds)  
CONTYPE(ANY|EXTCONS|MIGCONS|SSCONS)  
DELAY(seconds)  
IMSID(imsid)  
IMSREPLY  
INTERVAL(centiseconds)  
LOCALONLY  
LOG(YES|NO|OFF)  
MAXCMDOUT(number)  
NAME|CONNAME(consolename)  
OUTPUT|NOOUTPUT  
PROPRES  
STOPEND(YES|NO)  
STOPMSG(msgtextlist)  
STOPRESP(msgtextlist)  
SYSID|SYSTEM(systemids)  
SYSWAIT(seconds)  
WAIT(seconds)
```

ADDRESS OPSTCL—Control Components

Use the ADDRESS OPSTCL commands to control the ECF, MSF, COF, and OSF components.

- ECF Component

ECF LIST

Returns information about each ECF user logged onto a console.

- MSF Component

MSF DEFAULT

Specifies a default system name and system wait value for the currently executing REXX program or rule.

MSF START

Tells CA OPS/MVS to initialize the MSF on the local MSF system.

MSF STOP

Instructs the local copy of CA OPS/MVS to end its sessions with the remote CA OPS/MVS copies.

- MSF and COF Components

MSF|COF ACTIVATE

Causes MSF to activate a VTAM session with MSF on another system.

Associates a transient data queue and the COF.

MSF|COF DEACTIVATE

Ends the MSF session between the local and remote copies.

Ends the association between a transient data queue and the COF.

MSF|COF DEFINE

Defines to the MSF the systems it can communicate with.

Defines to COF a list of CICS transient data queue names to be selected for AOF processing.

MSF|COF DELETE

Deletes MSF or COF defined resources.

MSF|COF LIST

Displays all MSF or COF resources currently defined and their status.

Note: You can permanently add queues to the CICS Operations Facility using ADDRESS OPSTCL COF commands in an AOF rule or an OPS/REXX program.

- OSF Component

OSF EXECSTATS

Returns performance information about the OSF server.

OSF LIST

Returns information about active servers to the external data queue.

OSF QUEUES

Returns status and historical information about the server execution queue to the external data queue.

OSF RESETQ

Discards all pending commands waiting on the OSF execute queue.

OSF STOP *nnnn*

Stops the specified server.

- OPSLOG Component

DEFINE

Defines a new OPSLOG.

ACTIVATE

Makes an OPSLOG active.

SETLIVE

Makes a previously active OPSLOG the live log.

RESET

Empties an active OPSLOG of data content and resets the message number (MSGNO) back to zeroes. This cannot be the live log.

LIST

Lists all defined OPLOGs.

DEACTIVATE

Changes the status of a currently activated OPSLOG back to defined.

DELETE

Deletes an OPSLOG definition.

Examples: ADDRESS OPSCTL COF Define, Activate, and List Commands

- To create a list of CICS transient data queue names, use the following ADDRESS OPSCTL COF DEFINE command:

```
ADDRESS OPSCTL "COF DEFINE keywords"
  JOBNAME(jobname)
/* optional keywords */
STEPNAME(stepname|taskid)
STATUS
DESTIDS(destidlist)
OUTPUT|NOOUTPUT
SYSTEM(sysname)
SYSWAIT(seconds)
```

- To add the specified transient data queue names to any destination list that matches the selection criteria, use the following ADDRESS OPSCTL COF ACTIVATE command:

```
ADDRESS OPSCTL "COF ACTIVATE keywords"
  JOBNAME(jobname)
/* optional keywords */
STEPNAME(stepname|taskid)
STATUS(ACTIVE|INACTIVE)
DESTIDS(destidlist)
OUTPUT|NOOUTPUT
SYSTEM(sysname)
SYSWAIT(seconds)
```

- To display the contents of any transient data destination list that matches the selection criteria, use the following ADDRESS OPSCTL COF LIST command:

```
ADDRESS OPSCTL "COF LIST keywords"
  JOBNAME(jobname)
/* optional keywords */
STEPNAME(stepname|taskid)
STATUS(ACTIVE|INACTIVE)
OUTPUT|NOOUTPUT
SYSTEM(sysname)
SYSWAIT(seconds)
SUMMARY
```

Example: Define Multiple MSF Links between Systems

The following example defines multiple MSF links between systems. One link uses CA OPS/MVS native APPC session protocol. The second link uses CCI and its session protocol, which could be XES, XCF, or TCP/IP.

```
ADDRESS OPSCTL
IF SYSID = OPS11L
THEN DO
  "MSF DEFINE MSFID(OPS11L) APPLID(A11IOPSL)" /* local */
  "MSF DEFINE MSFID(OPS31L) APPLID(A31SENF) CCI" /* remote CCI */
  "MSF DEFINE MSFID(OPS31LVT) APPLID(A31IOPSL) APPC" /* remote APPC */
END

IF SYSID = OPS31L
THEN DO
  "MSF DEFINE MSFID(OPS31L) APPLID(A31IOPSL)" /* local */
  "MSF DEFINE MSFID(OPS11L) APPLID(A11SENF) CCI" /* remote CCI */
  "MSF DEFINE MSFID(OPS11LVT) APPLID(A11IOPSL) APPC" /* remote APPC */
END
```

Note: The MSFID for the CCI DEFINE must match the local MSFID for the remote system.

STATESET Command—Set the State for a Resource

Use the STATESET command to change the current state and desired state values specified for a resource.

```
STATESET (keywords)
```

```
/* Specify one of the following required keywords. */
```

```
tablename.resourcename  
resourcename
```

```
/* optional keywords */
```

```
ACTMODE(mode)  
CMDRESP(TERMINAL|NOWHERE|XDQ)  
CURRENT(currentstate)  
DESIRED(desiredstate)  
MODE(mode)  
PREMODE(mode)  
PREREQ(prereqstate)  
REFMODE(mode)  
SUBREQ(subreqstate)  
SUBSYS(OPSS,ssid)  
SYSTEM(msfids)  
SYSWAIT(seconds)  
TNGNOTIFY(ALWAYS|NEVER)  
WAIT(0,seconds)
```

Examples: STATESET command

- Set the state of all resources that depend on VTAM to down:
STATESET VTAM SUBREQ(DOWN)
- List the current and desired states, and the mode of VTAM:
STATESET VTAM
- Change the state of VTAM to down:
STATESET VTAM DESIRED(DOWN)

Examples: STATESET command invoked from REXX, TSO, and UNIX REXX environments

- Invoke from a REXX program using an AOF rule or automation procedure in either TSO/E REXX or OPS/REXX:
CALL 'STATESET' *resourcename* [*options*]
- Invoke from a TSO environment using the CA OPS/MVS OI command:
OI STATESET *resourcename* [*options*]

- Invoke from the TSO command line, such as ISPF option 6 or TSO Ready mode:

```
STATESET resourcename [options]
```

- Invoke from a UNIX REXX statement:

```
Address H "tso 'OI STATESET STCTBL.CICSUSS CURRENT(DOWN)'"
```

ADDRESS SQL—Create and Maintain SQL Tables

Use the ADDRESS SQL host environment to create and maintain SQL tables in the CA OPS/MVS RDF component. You invoke an SQL statement from an AOF rule or an OPS/REXX program.

ADDRESS SQL

sqlstatement

SQL Statements:

ALTER TABLE
CLOSE
CREATE TABLE.
DECLARE CURSOR
DELETE FROM
DROP TABLE
FETCH
INSERT
OPEN
SELECT
UPDATE

Examples: ADDRESS SQL create and update table statements

- To create a table named TESTTBL and insert two rows into it, use the following series of SQL statements:

ADDRESS SQL

```
"CREATE TABLE TESTTBL (ACTION_NAME CHAR(17) NOT NULL PRIMARY KEY,",  
"ACTION_TYPE CHAR(8) NOT NULL PRIMARY KEY, ACTION_TEXT CHAR(200))"
```

ADDRESS SQL

```
"INSERT INTO TESTTBL (ACTION_NAME, ACTION_TYPE, ACTION_TEXT)",  
"VALUES ('UNKNOWN', 'TEST1', 'TSOCMD(OPSWTO TEXT('UNKNOWN FIRED')))"
```

ADDRESS SQL

```
"INSERT INTO TESTTBL (ACTION_NAME, ACTION_TYPE, ACTION_TEXT)",  
"VALUES ('DOWN_UP', 'TEST1', 'TSOCMD(OPSWTO TEXT('DOWN_UP FIRED')))"
```

- To change the current state, desired state, and mode values specified for a resource, invoke the following SQL UPDATE statement from a rule or OPS/REXX program:

```
ADDRESS SQL
"UPDATE tablename SET columnname = 'state' WHERE NAME = 'name'"
```

ADDRESS WTO—Issue WTO Messages

Use ADDRESS WTO instructions in any section of any type of rule to issue WTO messages.

- To issue a single-line WTO message, use the following instructions:

```
ADDRESS WTO "TEXT(messagetext) keywords"
AREAID(areaid)
CNID(consoleids)
CNAME(consolenames)
DELAY(delaytime)
DESC(desccode)
HILITE|LOWLITE
MCSFLAGS(flagvalues)
MSGID(messageid)
NOLOG
OPTION(value)
REPLY
ROUTE(routecode)
SUBSYS(ssid)
SYSTEM(ALL|EXT|sysnames)
SYSWAIT(seconds)
TOKEN(dom token)
WAIT(waittime)
WTOID(wtoid)
```

- To issue a multiline WTO message, use the following instructions:

ADDRESS WTO "TEXTVAR(stem-name) *keywords*"
AREAID(*areaid*)
CNID(*consoleids*)
CNNAME(*consolenames*)
DELAY(*delaytime*)
DESC(*desccode*)
HILITE|LOWLITE
LINETYPE(*linetype*)
MCSFLAGS(*flagvalues*)
MSGID(*messageid*)
NOLOG
OPTION(*value*)
REPLY
ROUTE(*routecode*)
SUBSYS(*ssid*)
SYSTEM(ALL|EXT|*sysnames*)
SYSWAIT(*seconds*)
TOKEN(*dom token*)
WAIT(*waittime*)
WTOID(*wtoid*)

Chapter 4: OPSLOG Browse Primary Commands

Use the OPSLOG Browse primary commands to change the display format and navigate OPSLOG data.

To change the OPSLOG Browse display format, use the DISPLAY command

DISPLAY *keyword*

/ optional keywords */*

ADdress, AFlags, ASid, AUTOTokn, AUTOTOKX, COLor, CONSNAME, CouNt, Date, Disp, DSpname, ELapsedtime, Event, EVENTId, EXittype, Flags, IMsid, IMSType, JES3clas, JOBId, Jobname, JobNm, Length, MSFDest, MSFid, Msgid, MSGNo, NONE, Opsflags, RELease, Route, RouteX, RULeset, SPecial, Sysid, SYSName, TErnname, Time, TimeStrp, TOKen, User, USERId, USERX, Wtoid, and XCONID

To position the display at a specific event, use the LOCATE command

Locate *evtnum*{*date*|*time*}[*date time*][[*time date*)]*label*

To locate character strings in event text, use the FIND command

FIND *string**
FIRST|LAST|NEXT|PREV
startcol{*startcol* *endcol*}
evtnum

To repeat the FIND command, use the RFIND command

RFIND

To place OPSLOG Browse in automatic update mode, use the GOMODE command

GOMODE *seconds*

To issue z/OS and JES commands from the OPSLOG Browse command line, use the OC and OPSCMD commands

OC

OPSCMD

To set or clear option values, use the PROFILE command

PROFILE

{criteria {newvalue1 {newvalue2 {newvalue3 {newvalue4}}}}

LIST

SET *{profilid}*

CLEAR

To exclude option values, use the PROFILEX command

PROFILEX

To access the OPSLOG of a remote system, use the SYSTEM command

SYSTEM *sysname[?]**

To set the maximum number of seconds to wait for a response from a remote system, use the SYSWAIT command

SYSWAIT *seconds*

Chapter 5: POI Command Processors

This section contains frequently used POI commands.

OPSDOM—Delete an Operator Message

Use the OPSDOM command processor to delete a message from the operator console.

```
OPSDOM  
{AMRFID(amrfid)|DOMID(domid)|TOKEN(tokenid)}  
[DELAY(seconds)]  
[SUBSYS(ssid)]
```

OPSQL Command—Invoke SQL Statements

Use the OPSQL command to invoke SQL statements from a TSO terminal, a TSO CLIST, or a TSO/E REXX program.

```
OPSQL statement
```

Examples: OPSQL Statements

- To create a relational table named DAILY_SCHEDULE, use the following TSO CLIST:

```

PROC 0
CONTROL MSG CONLIST SYMLIST
OPSQL CREATE TABLE DAILY_SCHEDULE      +
(NAME CHAR(8) NOT NULL PRIMARY KEY,    +
EVENT CHAR(4) NOT NULL,                +
TYPE CHAR(1) UPPER CASE,               +
STATUS CHAR(1) UPPER CASE,             +
SCHED_DATE DATE,                       +
SCHED_TIME TIME,                       +
REPEAT_TIME TIME,                      +
RUN_DATE DATE,                         +
RUN_TIME TIME,                         +
END_DATE DATE,                         +
END_TIME TIME,                         +
MAX_CC CHAR(4),                        +
PREREQ1 CHAR(20),                      +
PRETYPE1 CHAR(1),                      +
PREREQ2 CHAR(20),                      +
PRETYPE2 CHAR(1),                      +
PREREQ3 CHAR(20),                      +
PRETYPE3 CHAR(1)) SUB(OPSF)
WRITE &SQLCODE
WRITE &SYSOUTLINE
WRITE &LASTCC
    
```

- To change the current state, desired state, and mode values specified for a resource, invoke a CLIST or REXX program that contains the following clause:

```
OPSQL UPDATE tablename SET columnname = 'state' WHERE NAME = 'name'
```