

# CA Application Quality and Testing Tools

Symbolic Guide

Release 9.1.00



Fourth Edition

This Documentation, which includes embedded help systems and electronically distributed materials (hereinafter referred to as the "Documentation"), is for your informational purposes only and is subject to change or withdrawal by CA at any time.

This Documentation may not be copied, transferred, reproduced, disclosed, modified or duplicated, in whole or in part, without the prior written consent of CA. This Documentation is confidential and proprietary information of CA and may not be disclosed by you or used for any purpose other than as may be permitted in (i) a separate agreement between you and CA governing your use of the CA software to which the Documentation relates; or (ii) a separate confidentiality agreement between you and CA.

Notwithstanding the foregoing, if you are a licensed user of the software product(s) addressed in the Documentation, you may print or otherwise make available a reasonable number of copies of the Documentation for internal use by you and your employees in connection with that software, provided that all CA copyright notices and legends are affixed to each reproduced copy.

The right to print or otherwise make available copies of the Documentation is limited to the period during which the applicable license for such software remains in full force and effect. Should the license terminate for any reason, it is your responsibility to certify in writing to CA that all copies and partial copies of the Documentation have been returned to CA or destroyed.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CA PROVIDES THIS DOCUMENTATION "AS IS" WITHOUT WARRANTY OF ANY KIND, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT WILL CA BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY LOSS OR DAMAGE, DIRECT OR INDIRECT, FROM THE USE OF THIS DOCUMENTATION, INCLUDING WITHOUT LIMITATION, LOST PROFITS, LOST INVESTMENT, BUSINESS INTERRUPTION, GOODWILL, OR LOST DATA, EVEN IF CA IS EXPRESSLY ADVISED IN ADVANCE OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The use of any software product referenced in the Documentation is governed by the applicable license agreement and such license agreement is not modified in any way by the terms of this notice.

The manufacturer of this Documentation is CA.

Provided with "Restricted Rights." Use, duplication or disclosure by the United States Government is subject to the restrictions set forth in FAR Sections 12.212, 52.227-14, and 52.227-19(c)(1) - (2) and DFARS Section 252.227-7014(b)(3), as applicable, or their successors.

Copyright © 2015 CA. All rights reserved. All trademarks, trade names, service marks, and logos referenced herein belong to their respective companies.

## CA Technologies Product References

This document references the following CA Technologies products:

- CA Endeavor® Software Change Manager (CA Endeavor SCM)
- CA InterTest™ Batch
- CA InterTest™ for CICS
- CA Librarian®
- CA Optimizer®
- CA Optimizer®/II
- CA Panvalet®
- CA Realia® II
- CA SymDump® Batch
- CA SymDump® for CICS

# Contact CA Technologies

## **Contact CA Support**

For your convenience, CA Technologies provides one site where you can access the information that you need for your Home Office, Small Business, and Enterprise CA Technologies products. At <http://ca.com/support>, you can access the following resources:

- Online and telephone contact information for technical assistance and customer services
- Information about user communities and forums
- Product and documentation downloads
- CA Support policies and guidelines
- Other helpful resources appropriate for your product

## **Providing Feedback About Product Documentation**

If you have comments or questions about CA Technologies product documentation, you can send a message to [techpubs@ca.com](mailto:techpubs@ca.com).

To provide feedback about CA Technologies product documentation, complete our short customer survey which is available on the CA Support website at <http://ca.com/docs>.

## Documentation Changes

We made the following updates to this guide since the last release:

- Changed the release number to Release 9.1.00.
- [CAVHPROT](#) (see page 17)—Updated substitutions.
- [Adding Symbolic Information](#) (see page 21)—Removed the the section IN25CPPR and references to IBM C.
- [IN25UTIL](#) (see page 63)—Updated to include additional IN25UTIL PRINT function parameters and the UPDATE function.
- [Dynamic Symbolic Support Messages](#) (see page 81)—Updated to add messages SYM070 and SYM099.
- [UTIL Messages](#) (see page 171)—Updated to add messages UTIL102-UTIL119.
- Added the USEDSPACEMSG parameter and the UPDATE function.
- Added messages SYM070, UTIL102, UTIL103, UTIL119, UTIL120, UTIL121. and UTIL122
- [CAVHPROT](#) (see page 17)—Updated with instructions on how to modify the default password for protected functions.
- [IN25UTIL Functions](#) (see page 64)—Updated with descriptions for the RELOAD and UNLOAD statements, the AFTERDATETIME, BEFOREDATETIME, and DATETIME parameters, multiversion support parameters, and new examples.



# Contents

---

Chapter 1: Introduction to Symbolic Support	11
What is Symbolic Support? .....	11
How Does Symbolic Support Work?.....	12
Symbolic Support for Optimized Applications .....	12
Supported Compilers and Assemblers .....	13
Considerations for Using the Integrated Preprocessors .....	14
The PROTSYM File .....	14
Sharing PROTSYM Files.....	15
Loading Symbolic Information .....	15
Chapter 2: Creating a PROTSYM File	17
CAVHPROT.....	17
Chapter 3: Adding Symbolic Information	21
IN25SYMC.....	21
IN25SYMC JCL.....	22
IN25SYMC Options .....	22
Required OS/VS COBOL Options .....	25
Executing IN25SYMC as a Standalone Program .....	26
Adding IN25SYMC to Your OS/VS COBOL Procedure .....	27
IN25COB2 .....	29
IN25COB2 JCL .....	29
IN25COB2 Options .....	30
Required COBOL Options .....	32
Executing IN25COB2 as a Standalone Program .....	33
Adding IN25COB2 to Your COBOL Procedure .....	34
Controlling Printed Output with the CUTPRINT Option .....	35
IN25SYMP .....	37
IN25SYMP JCL.....	37
IN25SYMP Options .....	38
Required PL/I Options .....	40
Executing IN25SYMP as a Standalone Program .....	42
Adding IN25SYMP to Your PL/I Procedure.....	43
IN25SYMA.....	45
IN25SYMA JCL .....	45
IN25SYMA Options.....	45

---

Required Assembler Options .....	48
Executing IN25SYMA as a Standalone Program .....	49
Adding IN25SYMA to Your Assembler Procedure .....	50
IN25LINK .....	52
IN25LINK JCL .....	52
IN25LINK Options .....	53
Required Linkage Editor Options .....	55
Executing IN25LINK as a Standalone Program .....	56
Adding IN25LINK to Your Link-Edit Procedure .....	56
IN25SYMD .....	59
IN25SYMD Options .....	59
Examples .....	60

## Chapter 4: Maintaining a PROTSYM File 63

IN25UTIL .....	63
IN25UTIL JCL .....	63
IN25UTIL Functions .....	64
IN25UTIL Parameters .....	71

## Chapter 5: Dynamic Symbolic Support for CA Endeavor Software Change Manager 73

Testing Tools Supporting Dynamic Symbolic File Updating .....	73
Dynamic Symbolic Support Activation .....	74
Dynamic Symbolic Support Execution .....	74
Single Site ID .....	74
Multiple Site IDs .....	75
Listing Server .....	75
Define Unique PROC .....	76
PROC Customization .....	77
JCL Considerations .....	78
CA Endeavor SCM Auto-Populate Activity Log .....	79

## Chapter 6: Messages 81

Dynamic Symbolic Support Messages .....	81
SYM Messages .....	105
UTIL Messages .....	171

## Appendix A: Restrictions for PL/I 193

Symbolic Support Restrictions .....	193
-------------------------------------	-----

---



# Chapter 1: Introduction to Symbolic Support

---

This guide is intended as a reference for programmers using the symbolic support features of CA Application Quality and Testing Tools.

## What is Symbolic Support?

The term *symbolic support* refers to the use of source code information from application programs to enhance and simplify the use of CA Application Quality and Testing Tools products for z/OS.

Some of these products include:

- CA InterTest Batch
- CA InterTest for CICS
- CA Optimizer/II
- CA SymDump Batch
- CA SymDump for CICS

These products provide application programmers with the critical tools needed to improve productivity throughout the application life cycle. Symbolic support makes these products easier to learn and use by speaking to programmers using terms that they recognize and understand from their own source code.

For example, using symbolic support with an interactive debugger like CA InterTest Batch lets programmers do the following:

- Enter breakpoint commands right on the source listing display.
- Stop execution at every label in a program.
- Automatically display the values of referenced variables at each statement.
- Easily display the value of any program variable.
- Set conditional breakpoints based on variable values.
- View a trace of all previously executed source statements.

Symbolic support eliminates the need to manually locate variables in storage, compute program offsets for source statements, or determine which statements were executing. You do not need to keep program listings open while debugging. All of this is done for you automatically when you use symbolic support with the CA Application Quality and Testing Tools products for z/OS.

## How Does Symbolic Support Work?

When your application programs are compiled or assembled, symbolic information about the program is written to various reports in the output listing. A program called a postprocessor reads the output listing, collects the symbolic information, and stores it in a symbolic repository called a PROTSYM.

Using the listing postprocessors to collect symbolic information does not alter your program in any way. The listing produced by your compiler or assembler is used only as input. Your object module is not altered. Only the PROTSYM is updated.

After the symbolic information has been stored in the PROTSYM, you can access the information by any of the CA Application Quality and Testing Tools products to provide symbolic support for your application.

## Symbolic Support for Optimized Applications

CA Application Quality and Testing Tools supports programs that have been optimized, either by the COBOL compiler's OPTIMIZE option or by CA Optimizer or CA Optimizer/II. However, debugging and post mortem analysis of these programs can sometimes result in unexpected behavior.

**Note:** The PL/I compilers are optimizing compilers.

Often as part of the optimization process, a compiler will relocate individual instructions, statements, or even entire paragraphs so that the optimized program will run more efficiently. This means that some or all of the instructions generated for a given statement may be moved to another statement, or that some or all of the statements in a paragraph may be moved to another paragraph. When this type of optimization occurs, the resulting object program and corresponding listing may not accurately represent the relationship between the source statements and their generated object code, or even between a paragraph label and the statements contained within the paragraph. As a result, there may be times when the breakpoint intercept does not occur, or when the wrong sequence of statements appears to be executed while single-stepping, or when the abending object code does not correspond to the correct source statement. There may also be times when the debugger appears to highlight the wrong statement at a breakpoint intercept or the dump analysis identifies the wrong statement as the abending source statement.

These unexpected displays do not indicate that a program is being executed incorrectly or that an abend is being incorrectly analyzed. They simply indicate that the debugger or dump analyzer sometimes cannot accurately identify exactly which object code corresponds to which source statement, or which statement is contained within which paragraph.

The CA Application Quality and Testing Tools products use the information in the compiler-generated procedure map or offset report to establish the program offset for each statement and label in the program. During execution or abend processing, the debugger or abend analyzer recognizes the start of the new statement or label by matching the program offset of the currently executing instruction with the PROTSYM information obtained from the compiler listing. Therefore, the accuracy with which the debugger or abend analyzer can represent a breakpoint or other intercept or the abending statement is only as good as the information in the compiler listing.

Inaccuracies may include, but will not be limited to:

- Incorrect execution when using the SKIP, GO stmt# or CS stmt# commands
- Failure to stop at a breakpoint at a paragraph label or statement
- Unexpected or out of sequence highlighting of statements when single-stepping
- Incorrect identification of the statement which contains the abending object code

Additionally, application abends may result from the use of the SKIP, GO stmt# or CS stmt# commands because the optimized object code may have register requirements that do not support changes to the flow of control. These commands should be avoided when debugging an optimized program.

For the best debugging results, avoid using optimization whenever possible in your testing environment. Production applications may be compiled with optimization, and debugging these applications as they exist without recompiling is supported. However, be aware that you may experience some of the inaccuracies listed previously under these circumstances.

## Supported Compilers and Assemblers

Symbolic information is currently supported for programs compiled or assembled by the following IBM products:

- OS/VS COBOL
- OS PL/I
- VS COBOL II

- AD/CYCLE COBOL/370
- COBOL for MVS
- COBOL for VM
- Enterprise COBOL for z/OS
- Visual Age PL/I
- PL/I for MVS and VM
- Enterprise PL/I for z/OS
- High Level Assembler for MVS and VM and VSE
- Assembler H

## Considerations for Using the Integrated Preprocessors

The integrated CICS translator and integrated SQL coprocessor of Enterprise COBOL for z/OS are fully supported by the postprocessor. It should be noted, however, that duplicate statement numbers for those statements generated by the integrated preprocessors are not saved in the PROTSYM. The CA Application Quality and Testing Tools products required this modification to the saved listing. In addition, the compiler's LIST option is required to correctly load the symbolic information into the PROTSYM file.

The postprocessor also supports the integrated CICS and SQL preprocessors of PL/I for z/OS. However, programs that contain EXEC SQL INCLUDE statements for user-defined members still require a separate precompile step. (EXEC SQL INCLUDE statements for SQLCA and SQLDA are supported when using the integrated SQL preprocessor.) It should also be noted that duplicate statement numbers for those statements generated by the integrated preprocessors are not saved in the PROTSYM. The CA Application Quality and Testing Tools products required this modification to the saved listing.

The integrated INCLUDE and MACRO preprocessors of PL/I for z/OS are not supported. A separate precompile step is required when incorporating external files into your program.

## The PROTSYM File

The PROTSYM file is a VSAM relative record data set (RRDS) with an upper limit of approximately four million 2 KB data records and capable of storing symbolic information for up to 147,000 application programs at one time.

The PROTSYM file is defined by IDCAMS and must be initialized by program IN25UTIL before you can add symbolic information.

Member CAVHPROT in CAI.CAVHJCL contains sample JCL that you can use to allocate and initialize a PROTSYM file.

**Note:** The PROTSYM file cannot reside in the LSR pool.

## Sharing PROTSYM Files

Your PROTSYM files can be shared between CA Technologies products and across multiple systems and environments. A single PROTSYM file contains symbolic information for both CICS and batch programs.

Use RESERVE and DEQ macros when updating the PROTSYM file to allow sharing of the file between regions and systems. The resource major name used in the RESERVE and DEQ macros is INTERTST. If your installation uses a service that converts RESERVEs into cross-system ENQs, define the major name INTERTST to the service.

Depending on your needs, you can maintain more than one PROTSYM file at your installation. All of the CA Application Quality and Testing Tools products support the use of multiple PROTSYM files.

## Loading Symbolic Information

By modifying the JCL procedures used to compile or assemble your applications, you can automatically update the symbolic information in your PROTSYM file every time a program is rebuilt. This is the easiest way to help ensure that the symbolic information in your PROTSYM file matches the executable for every program. This is also the method that CA Technologies recommends for maintaining symbolic information.

Alternatively, you can save the listings from your compiles or assemblies and load the symbolic information later as needed. If you choose this method, you can load symbolic information into your PROTSYM file using a separate batch job. CA Technologies provides batch utilities that let you load one or more program listings residing in partitioned data sets (PDS or PDSE), CA Librarian, CA Panvalet, or CA Endeavor SCM format.

Some of the CA Application Quality and Testing Tools products provide additional online functionality for viewing and maintaining PROTSYM files. For more information about the online utilities for any CA Technologies product, see the *User Guide* for that product.



# Chapter 2: Creating a PROTSYM File

---

This chapter describes how to create a PROTSYM file.

## CAVHPROT

Member CAVHPROT in CAI.CAVHJCL contains sample JCL for defining and initializing a PROTSYM file. The INITIALIZE and UPDATE functions against a PROTSYM file are password protected and the default password is 12345678. To modify the password, run the member CAVHSOPT in CAI.CAVHJCL with a modified version of member IN25SOPT in CAI.CAVHMAC as input before you create your PROTSYM files.

**Note:** If you are installing one of the CA Testing and Fault Management products, be sure to follow the instructions for creating the PROTSYM file in the *Installation Guide* for the product you are installing. Some products may provide custom JCL members that have been tailored for use with the product.

CAVHPROT contains the following two steps:

- Step 1 (DEFSYM)—Invokes IDCAMS to define the PROTSYM file.
- Step 2 (LOAD)—Invokes IN25UTIL to initialize each of the PROTSYM records.

The following JCL for member CAVHPROT shows these two steps:

```
//CAVHPROT JOB
//DEFSYM EXEC PGM=IDCAMS,REGION=1024K
//SYSPRINT DD SYSOUT=*
//SYSIN DD *
DELETE $PROTSYM$ CLUSTER PURGE
SET MAXCC=0
DEFINE CLUSTER (NAME($PROTSYM$)
                REC($RECS$)
                CISZ(2048) /* DO NOT CHANGE */
                VOLUME($SYMVOL$)
                RECSZ(2040 2040)
                SHR(4 4)
                NUMBERED)
                DATA (NAME($PROTSYM$.DATA))
/*
//LOAD EXEC PGM=IN25UTIL,REGION=2048K
//STEPLIB DD DSN=$LOADLIB$,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=$PROTSYM$,DISP=SHR
//CARDS DD *
PASSWORD=$PASSWORD$
INITIALIZE
REPORT
/*
//
```

Make the following substitutions in member CAVHPROT:

Symbol	Description
\$PROTSYM\$	Is the fully-qualified name of your new PROTSYM library.
\$SYMVOL\$	The volume on which the PROTSYM resides.
\$RECS\$	Is the primary space allocation in records. (See Notes 1 and 2.)
\$PASSWORD\$	Is the one- to eight-character PROTSYM update password for your installation, from IN25SOPT. (See Note 3.)
\$LOADLIB\$	Product target library.

Submit the JCL to allocate and initialize a new PROTSYM file.

**Notes:**

1. Do not allocate any secondary space.
2. The space required depends on many factors including the size of your programs, the number of variables and labels, the average length of their names, and the LISTER options used for loading symbolic information. We recommend an initial allocation of 10,000 records. You can allocate new PROTSYM files as needed, and expand and reorganize existing files.
3. If you have not altered the installation default, specify PASSWORD=12345678
4. The PROTSYM share parameters must be SHR(4,4).
5. To allow multiple program version support, include the MAXPGMVER=parameter.  
Note:

**Note:** For more information about the MAXPGMVER parameter, see chapter "[Maintaining a PROTSYM File](#) (see page 63)."



# Chapter 3: Adding Symbolic Information

---

This chapter describes how to add symbolic information to your PROTSYM files using the following postprocessors:

Postprocessor	Description
IN25SYMC	Loads symbolic information for programs compiled using: <ul style="list-style-type: none"><li>■ OS/VS COBOL version 2.3 plus PTF8 or higher</li><li>■ CA Optimizer</li></ul>
IN25COB2	Loads symbolic information for programs compiled using: <ul style="list-style-type: none"><li>■ Enterprise COBOL for z/OS</li><li>■ IBM COBOL for VM</li><li>■ IBM COBOL for MVS and VM</li><li>■ AD/CYCLE COBOL/370</li><li>■ VS COBOL II</li><li>■ CA Optimizer/II</li></ul>
IN25SYMP	Loads symbolic information for programs compiled using: <ul style="list-style-type: none"><li>■ Enterprise PL/I for z/OS</li><li>■ IBM PL/I for MVS and VM</li><li>■ Visual Age PL/I</li><li>■ OS PL/I</li></ul>
IN25SYMA	Loads symbolic information for programs compiled using: <ul style="list-style-type: none"><li>■ High level Assembler for MVS and VM and VSE</li><li>■ Assembler H</li></ul>
IN25LINK	Reads IBM linkage editor output to collect and load subroutine mapping information for composite load modules.
IN25SYMD	Loads multiple COBOL, C, PL/I, and Assembler listings residing in PDS, PDSE, CA Librarian, CA Panvalet, or CA Endeavor SCM format.

## IN25SYMC

Use program IN25SYMC to load symbolic information for programs compiled using OS/VS COBOL or CA Optimizer.

You can execute IN25SYMC as a standalone batch job to load a single COBOL listing that has been previously saved to a permanent file, or add it to your existing OS/VS COBOL or CA Optimizer JCL procedure. The method you select depends entirely on the procedures at your own installation. Both methods are described in this section.

## IN25SYMC JCL

The following table describes the DD statements used by IN25SYMC:

DDname	Description
STEPLIB	The load library containing IN25SYMC.
INPUT	The listing that was written to SYSPRINT by the OS/VS COBOL compiler, or by CA Optimizer, during compilation.
OUTPUT	All or part of the original compiler listing is written to this file, depending on your request.
MESSAGE	Any messages produced by IN25SYMC during postprocessing are written here.
PROTSYM	The file to which the symbolic information is written.
CARDS	The input control statements that define the request. <b>Note:</b> If you are adding a new step for IN25SYMC to a JCL procedure, use program IN25PARM to write your input control statements to the CARDS file.

## IN25SYMC Options

Options are passed to IN25SYMC using a parameter statement in the CARDS DD. Specify the parameter statement as an in-stream control card, or when using a JCL procedure, generate it using program IN25PARM.

The following JCL shows these options:

```
//IN25PARM EXEC PGM=IN25PARM,PARM='parameter statement'  
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD  
//CARDS DD DISP=(,PASS),DSN=&&CARDS,UNIT=SYSDA,SPACE=(TRK,(1,1))
```

Parameter statements in the CARDS DD must begin in column 1.

The program name is the only required field on the parameter statement. This positional parameter defines the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.

In most cases, this name should be the same as the PROGRAM-ID. However, when loading symbolic information for use with CA InterTest for CICS, you must specify the name of the CICS program definition, or when using composite support, specify the monitor name.

The following example shows an in-stream parameter statement that you can use to save symbolic information using the name ORDEDIT:

```
//CARDS DD *  
ORDEDIT  
/*
```

## Controlling Printed Output with the CUTPRINT Option

Because you can load symbolic information from a permanent data set or a temporary listing file, you can also print all or part of the listing generated by the compiler.

Append the CUTPRINT option to your parameter statement to control printing of the compiler listing as follows:

### **,CUTPRINT=ALL**

Do not print any of the compiler listing.

### **,CUTPRINT=MAP**

Print the listing up to, but not including, the Data Division Map report.

### **,CUTPRINT=REF**

Print the listing up to, but not including, the cross reference of data names.

The following sample parameter statement saves symbolic information for program ORDEDIT and prints only the source code section of the compiler listing:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=MAP  
/*
```

**Note:** Specify the CUTPRINT parameter only when you do not want all or part of your listing printed. The entire listing is printed if this parameter is omitted.

## Saving Your Listing for Online Display with the LISTER Option

Append the LISTER option to your parameter statement to control which portion of your source listing is saved to the PROTSYM file as follows:

### **,LISTER=ALL**

Saves the entire OS/VS COBOL listing.

### **,LISTER=MAP**

Saves the OS/VS COBOL listing up to, but not including, the Data Division Map report.

### **,LISTER=REF**

Saves the OS/VS COBOL listing up to, but not including, the cross reference of data names.

The following sample parameter statement saves symbolic information for program ORDEDIT, does not print any of the listing, and saves the listing up to, but not including, the Data Division Map report to the PROTSYM file:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=ALL,LISTER=MAP  
/*
```

### **Notes:**

- If the LISTER parameter is omitted, no listing is saved in the symbolic file.
- The LISTER parameter is required for use with CA Optimizer, CA SymDump Batch, and CA InterTest Batch.
- To reduce overhead and save space in your PROTSYM file, we recommend that you specify LISTER=MAP when executing IN25SYMC.

## Setting Data as Nonpurgeable

You can mark any saved symbolic data for this program as nonpurgeable. If a program's data is marked as nonpurgeable, the data is not removed from the PROTSYM when deleting programs using a purge interval batch run. However, you can delete the data by program name. See the chapter "[Maintaining a PROTSYM File](#) (see page 63)" for instructions on deleting data from the symbolic file.

To mark data as nonpurgeable, add the NOPURGE option to your parameter statement as the last option.

The following sample parameter statement saves symbolic information for program ORDEDIT, prints the entire listing, saves the entire listing in the PROTSYM file, and does not let symbolic data be removed from the symbolic file by a purge interval batch run.

```
//CARDS DD *
ORDEDIT, LISTER=ALL, NOPURGE
/*
```

## Required OS/VS COBOL Options

The following compiler options are required to load symbolic information for OS/VS COBOL programs into the PROTSYM file:

Option	Description
CLIST or PMAP	Produces a condensed Procedure Division map or full Assembler Procedure Division map.
DMAP	Produces a Data Division map.
NONUM	Suppresses compiler-generated line numbers.
SXREF	Produces a cross-reference of data and paragraph names.
VERB	Produces a report of verb names.

The following compiler options are required to load symbolic information for a program compiled using CA Optimizer into the PROTSYM file:

Option	Description
DMAP or MDMAP	Produces a Data Division map or merged Data Division map.
MLIST	Produces a merged Procedure Division map.
NONUM	Suppresses compiler-generated line numbers.
XREF	Produces a cross-reference of data and paragraph names.

To use symbolic references in OS/VS COBOL, you must declare at least one data item in working storage.

## Executing IN25SYMC as a Standalone Program

Member CAVHSYMC in CAI.CAVHPROC contains sample JCL for executing postprocessor IN25SYMC as a standalone batch job. Use this member to load symbolic information from previously saved OS/VS COBOL listings.

```
//CAVHSYMC PROC PROTSYM=CAI.PROTSYM,
//          NAME=XXXXXXXX,
//          LISTLIB=USER.LISTLIB,
//          MEMBER=XXXXXXXX,
//          LISTER=ALL,
//          CUTPRINT=ALL
//*
//IN25PARM EXEC PGM=IN25PARM,REGION=512K,
//          PARM=' &MEMBER, LISTER=&LISTER, CUTPRINT=&CUTPRINT '
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//CARDS DD DSN=&&CARDS,DISP=(,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//IN25SYMC EXEC PGM=IN25SYMC,REGION=2M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=&PROTSYM
//INPUT DD DISP=SHR,DSN=&LISTLIB(&MEMBER)
//CARDS DD DSN=&&CARDS,DISP=(OLD,DELETE)
//OUTPUT DD SYSOUT=*,DCB=(LRECL=121,BLKSIZE=2440,RECFM=FBA)
//MESSAGE DD SYSOUT=*
//
```

You can override the following procedure variables:

Variable	Description
PROTSYM	Specifies the name of the symbolic file being updated.
NAME	Specifies the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.  In most cases, this name should be the same as the PROGRAM-ID. However, when loading symbolic information for use with CA InterTest for CICS, specify the name of the CICS program definition, or for composite support, specify the monitor name.
LISTLIB	Specifies the name of the partitioned data set containing the listing from the OS/VS COBOL compiler or CA Optimizer.
MEMBER	Specifies the name of the member in the listing library that contains the compiler listing for the program being added.

Variable	Description
LISTER	Specifies how much of the listing to write to the OUTPUT file.
CUTPRINT	Specifies how much of the listing to write to the OUTPUT file.

## Adding IN25SYMC to Your OS/VS COBOL Procedure

To automatically update the symbolic information in your PROTSYM file whenever a OS/VS COBOL program is compiled, you can add a postprocessor step directly to the JCL procedure that you use to compile your programs.

**Note:** These same steps also apply to your CA Optimizer procedure.

Follow these steps to update your existing compile procedure:

1. Ensure that your compile step specifies all of the required OS/VS COBOL options.
2. Change the DD statement so that a temporary disk file is created for your listing, if the SYSPRINT output from your compile step is written to SYSOUT.
3. Add a new IN25PARM step following your compile step to generate the parameter statement for the postprocessor.
4. Add a new IN25SYMC step to postprocess the listing from the compile step. The INPUT DD on this step refers to the same file as the SYSPRINT DD from the compile step.
5. Add a new IEBGENER step to print the compiler listing only if the compiler detects errors.

The following example shows modifications to a compile procedure:

```
//COB      EXEC PGM=IKFCBL00,REGION=4M,
//  PARM=' SOURCE, DMAP, SXREF, PMAP, VERB, NONUM, &OPTIONS'   <= 1

      (Your existing DD statements for OS/V5 COBOL)

//SYSPRINT DD DSN=&&LST,DISP=(NEW,PASS),                      <= 2
//          UNIT=SYSDA,SPACE=(CYL,(1,2))
//*
//*  GENERATE THE PARAMETER STATEMENT FOR IN25SYMC
//*
//CARDS    EXEC PGM=IN25PARM,REGION=1M,COND=(4,LT),           <= 3
//  PARM=' &MEMBER, LISTER=ALL '
//STEPLIB  DD DSN=CAI.CAVHLOAD,DISP=SHR
//CARDS    DD DSN=&&CARDS,DISP=(NEW,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//*  POST-PROCESS THE COMPILER LISTING
//*
//SYM      EXEC PGM=IN25SYMC,REGION=4M,COND=(4,LT)           <= 4
//STEPLIB  DD DSN=CAI.CAVHLOAD,DISP=SHR
//PROTSYM  DD DSN=USER.PROTSYM,DISP=SHR
//OUTPUT   DD SYSOUT=*,
//          DCB=(LRECL=121,BLKSIZE=2420,RECFM=FBA)
//INPUT    DD DSN=&&LST,DISP=(OLD,PASS)                        (See Note 1)
//CARDS    DD DSN=&&CARDS,DISP=(OLD,DELETE)                    (See Note 2)
//MESSAGE  DD SYSOUT=*
//*
//PRINT    EXEC PGM=IEBGENER,COND=(5,GT,COB)                 <= 5
//SYSUT1   DD DSN=&&LST,DISP=(OLD,DELETE)
//SYSUT2   DD SYSOUT=*
//SYSPRINT DD DUMMY
//SYSIN    DD DUMMY
```

**Notes:**

1. If the SYSPRINT DD on your compile step refers to a permanent data set, the INPUT DD for IN25SYMC must point to the same data set.
2. If you prefer to pass your parameter statement as an override in the invoking JCL, delete the CARDS step, delete this DD statement, and add SYM.CARDS DD to your invoking JCL member.

## IN25COB2

Use program IN25COB2 to load symbolic information for programs compiled using any of the following products:

- Enterprise COBOL for z/OS
- IBM COBOL for VM
- IBM COBOL for MVS and VM
- AD/CYCLE COBOL/370
- VS COBOL II
- CA Optimizer/II

**Note:** In this section, the term COBOL refers to any of the COBOL dialects supported by the IBM compilers listed previously.

Execute IN25COB2 as a standalone batch job to load a single COBOL listing that has been previously saved to a permanent file, or add it to your existing COBOL or CA Optimizer/II JCL procedure. The method you select depends entirely on the procedures at your own installation. Both methods are described in this section.

## IN25COB2 JCL

The following table describes the DD statements used by IN25COB2:

DDname	Description
STEPLIB	The load library containing IN25COB2.
INPUT	The listing that was written to SYSPRINT by the COBOL compiler, or by CA Optimizer/II, during compilation.
OUTPUT	All or part of the original compiler listing is written to this file, depending on your request.
MESSAGE	All messages produced by IN25COB2 during post processing are written to this file.
PROTSYM	The file to which the symbolic information is written.
CARDS	The input control statements that define the request. <b>Note:</b> If you are adding a new step for IN25COB2 to a JCL procedure, use program IN25PARM to write your input control statements to the CARDS file.

## IN25COB2 Options

Options are passed to IN25COB2 using a parameter statement in the CARDS DD. Specify the parameter statement as an in-stream control card, or when using a JCL procedure, generate it using program IN25PARM as follows:

```
//IN25PARM EXEC PGM=IN25PARM,PARM='parameter statement'  
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD  
//CARDS DD DISP=(,PASS),DSN=&&CARDS,UNIT=SYSDA,SPACE=(TRK,(1,1))
```

Parameter statements in the CARDS DD must begin in column 1.

The program name is the only required field on the parameter statement. This optional parameter defines the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.

In most cases, this name should be the same as the PROGRAM-ID. However, when loading symbolic information for use with CA InterTest for CICS, you must specify the name of the CICS program definition, or when using composite support, specify the monitor name.

The following example shows an in-stream parameter statement that can be used to save symbolic information using the name ORDEDIT:

```
//CARDS DD *  
ORDEDIT  
/*
```

## Controlling Printed Output with the CUTPRINT Option

Because you can load symbolic information from a permanent data set or a temporary listing file, you can also print all or part of the listing generated by the compiler.

Append the CUTPRINT option to your parameter statement to control printing of the compiler listing as follows:

**,CUTPRINT=ALL**

Do not print any of the compiler listing.

**,CUTPRINT=MAP**

Print the listing up to, but not including, the Data Division Map report.

**,CUTPRINT=REF**

Print the listing up to, but not including, the cross reference of data names.

The following sample parameter statement saves symbolic information for program ORDEDIT and prints only the source code section of the compiler listing:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=REF  
/*
```

**Note:** Specify the CUTPRINT parameter only when you do not want all or part of your listing printed. The entire listing is printed if this parameter is omitted.

## Saving Your Listing for Online Display with the LISTER Option

Append the LISTER option to your parameter statement to control which portion of your source listing is saved to the PROTSYM file, as follows:

### **,LISTER=ALL**

Saves the entire COBOL listing.

### **,LISTER=MAP**

Saves the COBOL listing up to, but not including, the Data Division map report.

### **,LISTER=REF**

Saves the COBOL listing up to, but not including, the cross reference of data names.

The following sample parameter statement saves symbolic information for program ORDEDIT, does not print any of the listing, and saves the listing up to, but not including, the Data Division map report to the PROTSYM file:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=ALL,LISTER=MAP  
/*
```

### **Notes:**

- If the LISTER parameter is omitted, no listing is saved in the symbolic file.
- The LISTER parameter is required for use with CA Optimizer/II, CA SymDump Batch, and CA InterTest Batch.
- To reduce overhead and save space in your PROTSYM file, we recommend that you specify LISTER=MAP when executing IN25COB2 unless compiling with Optimizer/II, which requires LISTER=MMAP.

## Setting Data as Nonpurgeable

You can mark any saved symbolic data for this program as nonpurgeable. If a program's data is marked as nonpurgeable, the data is not removed from the PROTSYM when deleting programs using a purge interval batch run. However, you can delete the data by program name. See the chapter "[Maintaining a PROTSYM File](#) (see page 63)" for instructions on deleting data from the symbolic file.

To mark data as nonpurgeable, add the NOPURGE option to your parameter statement as the last option.

The following sample parameter statement saves symbolic information for program ORDEDIT, prints the entire listing, saves the entire listing in the PROTSYM file, and does not let symbolic data be removed from the symbolic file by a purge interval batch run.

```
//CARDS DD *  
ORDEDIT, LISTER=ALL, NOPURGE  
/*
```

## Required COBOL Options

The following compiler options are required to load symbolic information for COBOL programs into the PROTSYM file:

Option	Description
MAP	Produces a Data Division map.
NONUMBER	Suppresses compiler-generated line numbers.
OFFSET or LIST*	Produces a condensed Procedure map or full Assembler Procedure map.
XREF	Produces a cross-reference of data and procedure names.
NOPT or OPT(0)**	Produces breakpoints synchronized with source.
NOSTGOPT	Prevents the compiler from discarding unreferenced data items. The NOSTGOPT option is only valid for COBOL 5.1 and above.

\* The LIST option is required when using the integrated CICS translator or integrated SQL coprocessor of COBOL for z/OS.

\*\* When a COBOL program is OPTIMIZED, your breakpoints may not get stopped exactly where you think they should because the optimization is adding or modifying the generated code, and it may not be synchronized with the related source statements in the listing.

The following compiler options are required to load symbolic information for a program compiled using CA Optimizer/II into the PROTSYM file:

Option	Description
INTERTST	Required only when optimizing programs that are monitored using CA InterTest for CICS.

Option	Description
MAP or MMAP	Produces a Data Division map or merged Data Division map.
MMAP	Required when optimizing programs that are monitored using CA InterTest for CICS.
MOFFSET	Produces a merged Procedure map.
NONUM	Suppresses compiler-generated line numbers.
XREF	Produces a cross-reference of data and paragraph names.

**Note:** If you are using CA Optimizer/II r7 or higher, you can use the SYM compile-time option to automatically load symbolic information into your PROTSYM file during optimization. When using the SYM option, add a PROTSYM DD statement to your compile/optimize step. No additional option requirements exist when using this method.

To use symbolic references in COBOL, you must declare at least one data item in working storage.

## Executing IN25COB2 as a Standalone Program

Member CAVHCOB2 in CAI.CAVHPROC contains sample JCL for executing postprocessor IN25COB2 as a standalone batch job. Use this member to load symbolic information from previously saved COBOL listings.

```
//CAVHCOB2 PROC PROTSYM=CAI.PROTSYM,
//          NAME=XXXXXXXX,
//          LISTLIB=USER.LISTLIB,
//          MEMBER=XXXXXXXX,
//          LISTER=ALL,
//          CUTPRINT=ALL
//*
//IN25PARM EXEC PGM=IN25PARM,REGION=512K,
//          PARM='&MEMBER,LISTER=&LISTER,CUTPRINT=&CUTPRINT'
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//CARDS DD DSN=&&CARDS,DISP=(,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//IN25COB2 EXEC PGM=IN25COB2,REGION=2M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=&PROTSYM
//INPUT DD DISP=SHR,DSN=&LISTLIB(&MEMBER)
//CARDS DD DSN=&&CARDS,DISP=(OLD,DELETE)
//OUTPUT DD SYSOUT=*,DCB=(LRECL=133,BLKSIZE=3990,RECFM=FBA)
//MESSAGE DD SYSOUT=*
//
```

You can override the following procedure variables:

Variable	Description
PROTSYM	Specifies the name of the symbolic file being updated.
NAME	<p>Specifies the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.</p> <p>In most cases, this name should be the same as the PROGRAM-ID. However, when loading symbolic information for use with CA InterTest for CICS, specify the name of the CICS program definition, or for composite support, specify the monitor name.</p>
LISTLIB	Specifies the name of the partitioned data set containing the listing from the COBOL II compiler or CA Optimizer/II.
MEMBER	Specifies the name of the member in the listing library that contains the compiler listing for the program being added.
LISTER	Specifies how much of the listing to save in the PROTSYM file.
CUTPRINT	Specifies how much of the listing to write to the OUTPUT file.

## Adding IN25COB2 to Your COBOL Procedure

To automatically update the symbolic information in your PROTSYM file whenever a COBOL program is compiled, you can add a postprocessor step directly to the JCL procedure that you use to compile your programs.

**Note:** These same steps also apply to the CA Optimizer/II procedure.

Follow these steps to update your existing compile procedure:

1. Ensure that your compile step specifies all of the required COBOL options.
2. Change the DD statement so that a temporary disk file is created for your listing, if the SYSPRINT output from your compile step is written to SYSOUT.
3. Add a new IN25PARAM step following your compile step to generate the parameter statement for the postprocessor.
4. Add a new IN25COB2 step to postprocess the listing from the compile step. The INPUT DD on this step refers to the same file as the SYSPRINT DD from the compile step.
5. Add a new IEBGENER step to print the compiler listing only if the compiler detects errors.

The following example shows modifications to a compile procedure:

```
//COB      EXEC PGM=IGYCRCTL,REGION=4M,
//  PARM='S,MAP,X,LIST,NONUM,&OPTIONS'          <= 1

      (Your existing DD statements for COBOL II)

//SYSPRINT DD DSN=&&LST,DISP=(NEW,PASS),        <= 2
//          UNIT=SYSDA,SPACE=(CYL,(1,2))
//*
//*  GENERATE THE PARAMETER STATEMENT FOR IN25COB2
//*
//CARDS    EXEC PGM=IN25PARM,REGION=1M,COND=(4,LT), <= 3
//  PARM=' &MEMBER,LISTER=ALL '
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//CARDS    DD DSN=&&CARDS,DISP=(NEW,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//*  POST-PROCESS THE COMPILER LISTING
//*
//SYM      EXEC PGM=IN25COB2,REGION=4M,COND=(4,LT) <= 4
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//PROTSYM DD DSN=USER.PROTSYM,DISP=SHR
//OUTPUT   DD SYSOUT=*,
//          DCB=(LRECL=133,BLKSIZE=3990,RECFM=FBA)
//INPUT    DD DSN=&&LST,DISP=(OLD,PASS)           (See Note 1)
//CARDS    DD DSN=&&CARDS,DISP=(OLD,DELETE)       (See Note 2)
//MESSAGE  DD SYSOUT=*
//*
//PRINT    EXEC PGM=IEBGENER,COND=(5,GT,COB)    <= 5
//SYSUT1   DD DSN=&&LST,DISP=(OLD,DELETE)
//SYSUT2   DD SYSOUT=*
//SYSPRINT DD DUMMY
//SYSIN    DD DUMMY
```

**Notes:**

1. If the SYSPRINT DD on your compile step refers to a permanent data set, the INPUT DD for IN25COB2 must point to the same data set.
2. If you prefer to pass your parameter statement as an override in the invoking JCL, delete the CARDS step, delete this DD statement, and add SYM.CARDS DD to your invoking JCL member.

## Controlling Printed Output with the CUTPRINT Option

Because you can load symbolic information from a permanent data set or a temporary listing file, you can also print all or part of the listing generated by the compiler.

Append the CUTPRINT option to your parameter statement to control printing of the compiler listing as follows:

**,CUTPRINT=ALL**

Do not print any of the compiler listing.

**,CUTPRINT=REF**

Print the listing up to, but not including, the cross reference of data names.

The following sample parameter statement saves symbolic information for program ORDEDIT and prints only the source code section of the compiler listing:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=REF  
/*
```

**Note:** Specify the CUTPRINT parameter only when you do not want all or part of your listing printed. The entire listing is printed if this parameter is omitted.

## Saving Your Listing for Online Display with the LISTER Option

Append the LISTER option to your parameter statement to control which portion of your source listing is saved to the PROTSYM file, as follows:

**,LISTER=ALL**

Saves the entire compiler listing.

**,LISTER=REF**

Saves the compiler listing up to, but not including, the cross reference of data names.

The following sample parameter statement saves symbolic information for program ORDEDIT, does not print any of the listing, and saves the listing up to, but not including, the Data Division map report to the PROTSYM file:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=ALL,LISTER=MAP  
/*
```

**Notes:**

- If the LISTER parameter is omitted, no listing is saved in the symbolic file.
- The LISTER parameter is required for use with CA Optimizer/II, CA SymDump Batch, and CA InterTest Batch.
- To reduce overhead and save space in your PROTSYM file, we recommend that you specify LISTER=MAP when executing IN25CPPR unless compiling with Optimizer/II, which requires LISTER=MMAP.

## Setting Data as Nonpurgeable

You can mark any saved symbolic data for this program as nonpurgeable. If a program's data is marked as nonpurgeable, the data is not removed from the PROTSYM when deleting programs using a purge interval batch run. However, you can delete the data by program name. See the chapter "[Maintaining a PROTSYM File](#) (see page 63)" for instructions on deleting data from the symbolic file.

To mark data as nonpurgeable, add the NOPURGE option to your parameter statement as the last option.

The following sample parameter statement saves symbolic information for program ORDEDIT, prints the entire listing, saves the entire listing in the PROTSYM file, and does not let symbolic data be removed from the symbolic file by a purge interval batch run.

```
//CARDS DD *
ORDEDIT, LISTER=ALL, NOPURGE
/*
```

## IN25SYMP

Use program IN25SYMP to load symbolic information for programs compiled using any of the following products:

- Enterprise PL/I for z/OS
- IBM PL/I for MVS and VM
- Visual Age PL/I
- OS PL/I

**Note:** In this section, the term PL/I refers to any of the PL/I dialects supported by the IBM compilers previously listed.

Execute IN25SYMP as a standalone batch job to load a single PL/I listing that has been previously saved to a permanent file, or add it to your existing PL/I JCL procedure. The method you select depends entirely on the procedures at your own installation. Both methods are described in this section.

## IN25SYMP JCL

The following table describes the DD statements used by IN25SYMP:

DDname	Description
STEPLIB	The load library containing IN25SYMP.

DDname	Description
INPUTT	The listing that was written to SYSPRINT by the PL/I compiler during compilation.
SYSPRINT	All or part of the original compiler listing is written to this file, depending on your request.
MESSAGE and MSGS	Messages produced by IN25SYMP during postprocessing are written to these files.
PROTSYM	The file to which the symbolic information is written.
CARDS	The input control statements that define the request. <b>Note:</b> If you are adding a new step for IN25SYMP to a JCL procedure, use program IN25PARM to write your input control statements to the CARDS file.

## IN25SYMP Options

Options are passed to IN25SYMP using a parameter statement in the CARDS DD. Specify the parameter statement as an in-stream control card, or when using a JCL procedure, generate it using program IN25PARM as follows:

```
//IN25PARM EXEC PGM=IN25PARM,PARM='parameter statement'  
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD  
//CARDS DD DISP=(,PASS),DSN=&&CARDS,UNIT=SYSDA,SPACE=(TRK,(1,1))
```

Parameter statements in the CARDS DD must begin in column 1.

The program name is the only required field on the parameter statement. This positional parameter defines the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.

When loading symbolic information for use with CA InterTest for CICS, you must specify the name of the CICS program definition, or when using composite support, specify the monitor name.

The following example shows an in-stream parameter statement that you can use to save symbolic information using the name ORDEDIT:

```
//CARDS DD *  
ORDEDIT  
/*
```

## Controlling Printed Output with the CUTPRINT Option

Because you can load symbolic information from a permanent data set or a temporary listing file, you can also print all or part of the listing generated by the compiler.

Append the CUTPRINT option to your parameter statement to control printing of the compiler listing as follows:

### **,CUTPRINT=ALL**

Prints none of the compile listing.

### **,CUTPRINT=REF**

Terminates printing after the XREF table.

### **,CUTPRINT=OFFSET**

Terminates printing after the table of offsets.

The following sample parameter statement saves symbolic information for program ORDEDIT and terminates printing after the XREF table:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=REF  
/*
```

**Note:** Specify the CUTPRINT parameter only when you do not want all or part of your listing printed. The entire listing is printed if you omit this parameter.

## Saving Your Listing for Online Display with the LISTER Option

Append the LISTER option to your parameter statement to control which portion of your source listing is saved to the PROTSYM file, as follows:

### **,LISTER=ALL**

Saves the entire PL/I listing.

### **,LISTER=REF**

Saves only the source and XREF sections.

### **,LISTER=OFFSET**

Saves the listing up to, and including, the table of offsets.

The following sample parameter statement saves symbolic information for program ORDEDIT, does not print any of the listing, and saves only the source and XREF sections of the listing:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=ALL,LISTER=REF  
/*
```

**Notes:**

- If the LISTER parameter is omitted, no listing is saved in the symbolic file.
- The LISTER parameter is required for use with CA Optimizer/II, CA SymDump Batch, and CA InterTest Batch.

## Setting Data as Nonpurgeable

You can mark any saved symbolic data for this program as nonpurgeable. If a program's data is marked as nonpurgeable, the data is not removed from the PROTSYM when deleting programs using a purge interval batch run. However, you can delete the data by program name. See the chapter "[Maintaining a PROTSYM File](#) (see page 63)" for instructions about deleting data from the symbolic file.

To mark data as nonpurgeable, add the NOPURGE option to your parameter statement as the last option.

The following sample parameter statement saves symbolic information for program ORDEDIT, prints the entire listing, saves the entire listing in the PROTSYM file, and does not let symbolic data be removed from the symbolic file by a purge interval batch run.

```
//CARDS DD *  
ORDEDIT,LISTER=ALL,NOPURGE  
/*
```

## Required PL/I Options

The following compiler options are required to load symbolic information for PL/I programs when using the OS PL/I or IBM PL/I for MVS and VM compiler:

AGGREGATE	NONUMBER
ATTRIBUTES(FULL)	OPTIONS
MAP	SOURCE
NEST	STMT or GOSTMT
NOGONUM	STORAGE
	XREF(FULL)

The following compiler options are required to load symbolic information for PL/I programs when using Enterprise PL/I for z/OS or Visual Age PL/I:

AGGREGATE	NOGONUM
ATTRIBUTES(FULL)	NOSTMT
LIMITS(NAME(31))	NUMBER
LIST	OPTIONS
MAP	SOURCE
NATLANG(ENU)	STORAGE
NEST	XREF(FULL)

**Notes:**

- Because of special considerations, if you must use the %NOPRINT compiler option, contact CA Support.
- For the CA Application Quality and Testing Tools products to support date/time stamp comparison between your symbolic information and your executables, you must select TSTAMP=YES when installing your PL/I compiler.
- CA InterTest Batch, CA SymDump Batch, and CA Optimizer/II display only controlled variables.
- When using the IBM PL/I for MVS and VM compiler, the ESD option is required for programs that have controlled variables.

## Executing IN25SYMP as a Standalone Program

Member CAVHSYMP in CAI.CAVHPROC contains sample JCL for executing postprocessor IN25SYMP as a standalone batch job. Use this member to load symbolic information from previously saved PL/I listings as follows:

```
//CAVHSYMP PROC PROTSYM=CAI.PROTSYM,
//          NAME=XXXXXXXX,
//          LISTLIB=USER.LISTLIB,
//          MEMBER=XXXXXXXX,
//          LISTER=ALL,
//          CUTPRINT=ALL
//*
//IN25PARM EXEC PGM=IN25PARM,REGION=512K,
//          PARM='&MEMBER,LISTER=&LISTER,CUTPRINT=&CUTPRINT'
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//CARDS DD DSN=&&CARDS,DISP=(,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//IN25SYMP EXEC PGM=IN25SYMP,REGION=2M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=&PROTSYM
//INPUTT DD DISP=SHR,DSN=&LISTLIB(&MEMBER)
//CARDS DD DSN=&&CARDS,DISP=(OLD,DELETE)
//SYSPRINT DD SYSOUT=*
//MESSAGE DD SYSOUT=*
//MSGS DD SYSOUT=*
//
```

You can override the following procedure variables:

Variable	Description
PROTSYM	Specifies the name of the symbolic file being updated.
NAME	Specifies the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.  When loading symbolic information for use with CA InterTest for CICS, specify the name of the CICS program definition, or for composite support, specify the monitor name.
LISTLIB	Specifies the name of the partitioned data set containing the listing from the PL/I compiler.
MEMBER	Specifies the name of the member in the listing library that contains the compiler listing for the program being added.
LISTER	Specifies how much of the listing to save in the PROTSYM file.

Variable	Description
CUTPRINT	Specifies how much of the listing to write to the OUTPUT file.

## Adding IN25SYMP to Your PL/I Procedure

To automatically update the symbolic information in your PROTSYM file whenever a PL/I program is compiled, add a postprocessor step directly to the JCL procedure you use to compile your programs.

Follow these steps to update your existing compile procedure:

1. Ensure that your compile step specifies all of the required PL/I options.
2. Change the DD statement so that a temporary disk file is created for your listing, if the SYSPRINT output from your compile step is written to SYSOUT.
3. Add a new IN25PARM step following your compile step to generate the parameter statement for the postprocessor.
4. Add a new IN25SYMP step to postprocess the listing from the compile step. The INPUTT DD on this step refers to the same file as the SYSPRINT DD from the compile step.
5. Add a new IEBGENER step to print the compiler listing only if the compiler detects errors.

The following example shows modifications to a compile procedure:

```
//PLI      EXEC PGM=IBMZPLI,REGION=4M,
//  PARM=( 'OBJ,X(F),A(F),OP,MAP,STG,AG,NEST,LIST',      <= 1
//          'NIS,S,NOPT,LIMITS(NAME(31)),FLAG(W)')

      (Your existing DD statements for PL/I)

//SYSPRINT DD DSN=&&LST,DISP=(NEW,PASS),                <= 2
//          UNIT=SYSDA,SPACE=(CYL,(1,2))
//*
//*  GENERATE THE PARAMETER STATEMENT FOR IN25SYMP
//*
//CARDS    EXEC PGM=IN25PARM,REGION=1M,COND=(4,LT),      <= 3
//  PARM=' &MEMBER,LISTER=ALL'
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//CARDS    DD DSN=&&CARDS,DISP=(NEW,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//*  POST-PROCESS THE COMPILER LISTING
//*
//SYM      EXEC PGM=IN25SYMP,REGION=4M,COND=(4,LT)      <= 4
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//PROTSYM DD DSN=USER.PROTSYM,DISP=SHR
//SYSPRINT DD SYSOUT=*
//INPUTT  DD DSN=&&LST,DISP=(OLD,PASS)                  (See Note 1)
//CARDS    DD DSN=&&CARDS,DISP=(OLD,DELETE)             (See Note 2)
//MESSAGE DD SYSOUT=*
//MSGGS   DD SYSOUT=*
//*
//PRINT   EXEC PGM=IEBGENER,COND=(5,GT,PLI)           <= 5
//SYSUT1  DD DSN=&&LST,DISP=(OLD,DELETE)
//SYSUT2  DD SYSOUT=*
//SYSPRINT DD DUMMY
//SYSIN   DD DUMMY
```

**Notes:**

1. If the SYSPRINT DD on your compile step refers to a permanent data set, the INPUTT DD for IN25SYMP must point to the same data set.
2. If you prefer to pass your parameter statement as an override in the invoking JCL, delete the CARDS step, delete this DD statement, and add SYM.CARDS DD to your invoking JCL member.

## IN25SYMA

Use program IN25SYMA to load symbolic information for Assembler programs into your PROTSYM file.

Execute IN25SYMA as a standalone batch job to load a single Assembler listing that has been previously saved to a permanent file, or add it to your existing Assembler JCL procedure. The method you select depends entirely on the procedures at your own installation. Both methods are described in this section.

## IN25SYMA JCL

The following table describes the DD statements used by IN25SYMA:

DDname	Description
STEPLIB	The load library containing IN25SYMA.
INPUT	The listing that was written to SYSPRINT by the Assembler.
OUTPUT	All or part of the original Assembler listing is written to this file, depending on your request.
MESSAGE	Messages produced by IN25SYMA during postprocessing are written to this file.
PROTSYM	The file to which the symbolic information is written.
CARDS	The input control statements that define the request. <b>Note:</b> If you are adding a new step for IN25SYMA to a JCL procedure, use program IN25PARM to write your input control statements to the CARDS file.

## IN25SYMA Options

Options are passed to IN25SYMA using a parameter statement in the CARDS DD. Specify the parameter statement as an in-stream control card, or when using a JCL procedure, generate it using program IN25PARM as follows:

```
//IN25PARM EXEC PGM=IN25PARM,PARM='parameter statement'
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//CARDS DD DISP=(,PASS),DSN=&&CARDS,UNIT=SYSDA,SPACE=(TRK,(1,1))
```

Parameter statements in the CARDS DD must begin in column 1.

The program name is the only required field on the parameter statement. This positional parameter defines the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.

In most cases, this name should be the same as the first CSECT in the Assembler listing. When loading symbolic information for use with CA InterTest for CICS, you must specify the name of the CICS program definition, or when using composite support, specify the monitor name.

The following example shows an in-stream parameter statement that can be used to save symbolic information using the name ORDEDIT:

```
//CARDS DD *  
ORDEDIT  
/*
```

## Controlling Printed Output with the CUTPRINT Option

Because you can load symbolic information from a permanent data set or a temporary listing file, you can also print all or part of the listing generated by the assembler.

Append the CUTPRINT option to your parameter statement to control printing of the assembler listing as follows:

### **,CUTPRINT=ALL**

Do not print any of the assembler listing.

### **,CUTPRINT=REF**

Stops printing the listing after the Cross Reference report.

The following sample parameter statement saves symbolic information for program ORDEDIT without printing any of the listing:

```
//CARDS DD *  
ORDEDIT,CUTPRINT=ALL  
/*
```

**Note:** Specify the CUTPRINT parameter only when you do not want all or part of your listing printed. The entire listing is printed if this parameter is omitted.

---

## Saving Your Listing for Online Display with the LISTER Option

Append the LISTER option to your parameter statement to control which portion of your source listing is saved to the PROTSYM file as follows:

### **,LISTER=ALL**

Saves the entire assembler listing.

### **,LISTER=REF**

Saves the listing up to, but not including, the Cross Reference report.

The following sample parameter statement saves symbolic information for program ORDEDIT while printing and saving the listing up to, but not including, the Cross Reference report:

```
//CARDS DD *  
ORDEDIT, CUTPRINT=REF, LISTER=REF  
/*
```

### **Notes:**

- If the LISTER parameter is omitted, no listing is saved in the symbolic file.
- The LISTER parameter is required for use with CA Optimizer/II, CA SymDump Batch, and CA InterTest Batch.

## Setting Data as Nonpurgeable

You can mark any saved symbolic data for this program as nonpurgeable. If a program's data is marked as nonpurgeable, the data is not removed from the PROTSYM when deleting programs using a purge interval batch run. However, you can delete the data by program name. See the chapter "[Maintaining a PROTSYM File](#) (see page 63)" for instructions on deleting data from the symbolic file.

To mark data as nonpurgeable, add the NOPURGE option to your parameter statement as the last option.

The following sample parameter statement saves symbolic information for program ORDEDIT, prints the entire listing, saves the entire listing in the PROTSYM file, and does not let symbolic data be removed from the symbolic file by a purge interval batch run.

```
//CARDS DD *  
ORDEDIT, LISTER=ALL, NOPURGE  
/*
```

## Required Assembler Options

The following listing options are required to load symbolic information for assembler programs:

<b>Option</b>	<b>Description</b>
DXREF	DSECT Cross-Reference
ESD	External Symbol Dictionary
NOBATCH	Only one assembler source program is in the input source file
USING	Using Map report
XREF(FULL) or XREF(SHORT)	Full cross-reference or cross-reference of referenced names

**Notes:**

- Do not suppress statements that define the start of a DSECT in the listing by PRINT OFF or PRINT NOGEN.
- High Level Assembler r2.0 users must also specify the LIST(121) option.
- High Level Assembler r4.0 users must specify the THREAD option. The NOTHREAD option is not supported.

## Executing IN25SYMA as a Standalone Program

Member CAVHSYMA in CAI.CAVHPROC contains sample JCL for executing postprocessor IN25SYMA as a standalone batch job. Use this member to load symbolic information from previously saved Assembler listings.

```
//CAVHSYMA PROC PROTSYM=CAI.PROTSYM,
//          NAME=XXXXXXXX,
//          LISTLIB=USER.LISTLIB,
//          MEMBER=XXXXXXXX,
//          LISTER=ALL,
//          CUTPRINT=ALL
//*
//IN25PARM EXEC PGM=IN25PARM,REGION=512K,
//          PARM='&MEMBER,LISTER=&LISTER,CUTPRINT=&CUTPRINT'
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//CARDS DD DSN=&&CARDS,DISP=(,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//IN25SYMA EXEC PGM=IN25SYMA,REGION=2M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=&PROTSYM
//INPUT DD DISP=SHR,DSN=&LISTLIB(&MEMBER)
//CARDS DD DSN=&&CARDS,DISP=(OLD,DELETE)
//OUTPUT DD SYSOUT=*, DCB=(RECFM=FBM,LRECL=121,BLKSIZE=2420)
//MESSAGE DD SYSOUT=*
//
```

You can override the following procedure variables:

Variable	Description
PROTSYM	Specifies the name of the symbolic file being updated.
NAME	Specifies the name that is used to store the symbolic information in the PROTSYM file. This name is used by the CA Application Quality and Testing Tools products to locate the symbolic information and is displayed when listing the contents of your PROTSYM.  In most cases, this is the name of the first CSECT in the assembler listing. When loading symbolic information for use with CA InterTest for CICS, specify the name of the CICS program definition, or for composite support, specify the monitor name.
LISTLIB	Specifies the name of the partitioned data set containing the Assembler listing.
MEMBER	Specifies the name of the member in the listing library that contains the Assembler listing for the program being added.

Variable	Description
LISTER	Specifies how much of the listing to save in the PROTSYM file.
CUTPRINT	Specifies how much of the listing to write to the OUTPUT file.

## Adding IN25SYMA to Your Assembler Procedure

To automatically update the symbolic information in your PROTSYM file whenever a program is assembled, add a postprocessor step directly to the JCL procedure that you use to assemble your programs.

Follow these steps to update your existing assembly procedure:

1. Be sure that your assemble step specifies all of the required Assembler options.
2. If the SYSPRINT output from your assemble step is written to SYSOUT, change the DD statement so that a temporary disk file is created for your listing.
3. Add a new IN25PARM step following your assemble step to generate the parameter statement for the postprocessor.
4. Add a new IN25SYMA step to postprocess the listing from the assemble step. The INPUT DD on this step refers to the same file as the SYSPRINT DD from the assemble step.
5. Add a new IEBGENER step to print the Assembler listing only if errors were detected during the assembly.

The following example shows modifications to an assembly procedure:

```
//ASM      EXEC PGM=ASMA90,REGION=4M,
//  PARM=' LIST,OBJECT,XREF(FULL),ESD'          <= 1

      (Your existing DD statements for the Assembler)

//SYSPRINT DD DSN=&&LST,DISP=(NEW,PASS),        <= 2
//          UNIT=SYSDA,SPACE=(CYL,(1,2))
//*
//*  GENERATE THE PARAMETER STATEMENT FOR IN25SYMA
//*
//CARDS    EXEC PGM=IN25PARM,REGION=1M,COND=(4,LT), <= 3
//  PARM=' &MEMBER,LISTER=ALL '
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//CARDS    DD DSN=&&CARDS,DISP=(NEW,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//*  POST-PROCESS THE COMPILER LISTING
//*
//SYM      EXEC PGM=IN25SYMA,REGION=4M,COND=(4,LT) <= 4
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//PROTSYM DD DSN=USER.PROTSYM,DISP=SHR
//OUTPUT   DD SYSOUT=*,DCB=(RECFM=FBM,LRECL=121,BLKSIZE=2420)
//INPUT    DD DSN=&&LST,DISP=(OLD,PASS)           (See Note 1)
//CARDS    DD DSN=&&CARDS,DISP=(OLD,DELETE)       (See Note 2)
//MESSAGE  DD SYSOUT=*
//*
//PRINT    EXEC PGM=IEBGENER,COND=(5,GT,ASM)    <= 5
//SYSUT1   DD DSN=&&LST,DISP=(OLD,DELETE)
//SYSUT2   DD SYSOUT=*
//SYSPRINT DD DUMMY
//SYSIN    DD DUMMY
```

**Notes:**

1. If the SYSPRINT DD on your compile step refers to a permanent data set, the INPUT DD for IN25SYMA must point to the same data set.
2. If you prefer to pass your parameter statement as an override in the invoking JCL, delete the CARDS step, delete this DD statement, and add SYM.CARDS DD to your invoking JCL member.

## IN25LINK

Use program IN25LINK to define the additional symbolic information required for testing composite modules using CA InterTest for CICS.

A composite module consists of separately compiled or assembled parts that are brought together under a single module name by the IBM Linkage Editor. In CICS, a composite module has only one CICS program definition. You can write the main program and the called subroutines in the same or different languages.

The Composite Support feature of CA InterTest for CICS lets you test the subroutines of a composite module as if they were separate programs with separate CICS program definitions. For more information about this feature, see the *CA InterTest for CICS User Guide*.

IN25LINK uses output from the IBM Linkage Editor and your own additional input cards to associate the subroutines of a composite module with the monitor names you define. Typically, this program is executed as a standalone batch job to load output from a single link step.

If the Symbolic File in the JCL PROTSYM DD statement was initialized to allow multiple program version support, the IN25LINK control statement information will be associated with the latest or most recently compiled program version specified by the *monitor-name*.

**Note:** While it is more efficient to use IN25LINK for composite support, you can provide the same information online using the CA InterTest for CICS COMPOSITE command or CNTL menu.

## IN25LINK JCL

The following table describes the DD statements used by IN25LINK:

DDname	Description
STEPLIB	The load library containing IN25LINK.
INPUT	The listing that was written to SYSPRINT by the IBM Linkage Editor.
OUTPUT	All or part of the original listing is written to this file, depending on your request.
MESSAGE	Messages produced by IN25LINK during postprocessing are written to this file.
PROTSYM	The file to which the symbolic information is written.

DDname	Description
CARDS	The input control statements that define the relationships between your monitor names and the subroutines of your composite module.

## IN25LINK Options

Options are passed to IN25LINK using parameter statements in the CARDS DD. Parameter statements in the CARDS DD must begin in column 1.

### Identifying the Composite Module

The first parameter card is *required*. It specifies the CICS program definition name of the composite module, beginning in column 1, as follows:

```
composite-name[,NOPURGE]
```

The program name specified in this parameter statement must be the same as the CICS program definition name of the composite module.

You can also specify the NOPURGE option on this statement. This option specifies that symbolic information for the composite module *cannot* be purged from the PROTSYM file during a purge interval batch job.

### Identifying the Main Program and Subroutines

Subsequent parameter cards optionally identify the main program and each subroutine that you want to test separately. These cards can be entered in any order and must specify two names, separated by commas, as follows:

```
link-name, monitor-name
```

*link-name* identifies the name of the control section as listed in the link-edit map, and must begin in column 1. For a PL/I program, specify the name of the compiler-generated control section that ends with '1'.

*monitor-name* specifies the name under which the program is monitored. Follow these rules in selecting a *monitor-name*:

- Each *monitor-name* must be unique.
- The *monitor-name* of a subroutine cannot be the same as a CICS program definition name.
- The *monitor-name* can be identical to the *link-name*.

Only the first parameter card is required; omit all subsequent cards. If you omit the subsequent parameter cards, only the name of the composite module is stored in the PROTSYM file. When you attempt to monitor the composite module with CA InterTest for CICS, you are prompted for additional composite information.

## Excluding Subroutines

By default, IN25LINK excludes subroutines with CEE, DFH, DLZ, IBM, IGZ, and ILB prefixes when it reads the link-edit map. Usually, you will not want to test these programs.

You can change the default exclusion rules using a parameter card, positioned anywhere in the CARDS file after the first card, beginning in column 1, as follows:

```
EXCLUDE=
```

(or)

```
EXCLUDE=name[ , name ,... , name ]
```

Specifying EXCLUDE without any names instructs IN25LINK not to exclude any subroutines.

Specifying EXCLUDE=xxxxxxx instructs IN25LINK to exclude subroutines whose names are represented by xxxxxxx. Specify the entire *link-name* to exclude a specific subroutine, or specify a prefix to exclude a group of subroutines.

For example, to exclude all subroutines with the prefix ACA1, specify:

```
EXCLUDE=ACA1
```

## Example

A composite module with the CICS program definition name BIGMOD consists of several separately compiled programs and library modules. Its main program is named MAINMOD and is written in COBOL.

BIGMOD also has three Assembler subroutines named SUBMODA, SUBMODB, and SUBMODC that you want to test separately. None of the subroutines has its own CICS program definition entry.

After assembling SUBMODA, SUBMODB, and SUBMODC, you loaded their symbolic information by executing postprocessor IN25SYMA. You selected monitor names of ASMMODA, ASMMODB, and ASMMODC for the subroutines.

Next, you compiled MAINMOD and loaded its symbolic information by executing postprocessor IN25COB2. You specified BIGMOD as the monitor name, matching the CICS program definition as required.

The linkage editor combines the main program and its three subroutines, creating the composite load module named BIGMOD. The link-edit map output for BIGMOD shows a main entry address of 160, that BIGMOD has been replaced in the load library, and that it contains the following modules:

Control Section	Origin	Length	Description
DFHECI	00	160	Command level COBOL stub
MAINMOD	160	78A8	Main program-COBOL
ILBOATB	7A08	11A	COBOL library module
ILBOCOM07B28	73		COBOL library module
SUBMODA 7CA0	1200		Subprogram-Assembler
SUBMODB 8EA0	100		Subprogram-Assembler
SUBMODC 9EA1	93		Subprogram-Assembler

Sample JCL for the link-edit step and IN25LINK is shown as follows:

```

/*
/* Link Edit Step
/*
//LKED      EXEC PGM=IEWL,.....
//SYSLIB   DD.....
//SYSLMOD  DD.....
//SYSUT1   DD.....
//SYSLIN   DD.....
//SYSPRINT DD DSN=&&INPUT,DISP=(,PASS),
// UNIT=SYSDA,SPACE=(TRK,(2,5)),
// DCB=(DSORG=PS,LRECL=121,BLKSIZE=2420,RECFM=FB)
/*
/* IN25LINK Step
/*
//POSTLINK EXEC PGM=IN25LINK,REGION=512K
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//INPUT   DD DSN=&&INPUT,DISP=(OLD,DELETE)
//MESSAGE DD SYSOUT=*
//OUTPUT  DD SYSOUT=*,
// DCB=(RECFM=FBA,LRECL=121,BLKSIZE=2420)
//PROTSYM DD DSN=INTRTST.PROTSYM,DISP=SHR
//CARDS   DD *
BIGMOD          CICS program definition name of composite module
MAINMOD,BIGMOD  link-name and monitor-name of main program
SUBMODA,ASMMODA link-name and monitor-name of subprogram
SUBMODB,ASMMODB link-name and monitor-name of subprogram
SUBMODC,ASMMODC link-name and monitor-name of subprogram
/*

```

## Required Linkage Editor Options

If you are using DFSMS 1.1, you must specify the MAP parameter on the link-edit step.

## Executing IN25LINK as a Standalone Program

Member CAVHLINK in CAI.CAVHPROC contains sample JCL for executing postprocessor IN25LINK as a standalone batch job. Use this member to load composite information from a previously saved Linkage Editor listing.

```
//CAVHLINK PROC PROTSYM=CAI.PROTSYM,
//          LISTLIB=USER.LISTLIB
//          MEMBER=XXXXXXXX
//*
//IN25LINK EXEC PGM=IN25LINK,REGION=2M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=&PROTSYM
//INPUT DD DISP=SHR,DSN=&LISTLIB(&MEMBER)
//OUTPUT DD SYSOUT=*,DCB=(LRECL=121,BLKSIZE=2440,RECFM=FBA)
//CARDS DD DDNAME=CARDS
//MESSAGE DD SYSOUT=*
```

You can override the following procedure variables:

Variable	Description
PROTSYM	Specifies the name of the symbolic file being updated.
LISTLIB	Specifies the name of the partitioned data set containing your saved IBM Linkage Editor output listings.
MEMBER	Specifies the name of the member in the listing library that contains the listing for the composite module.

When invoking this JCL procedure, you must include a CARDS DD statement in the invoking JCL.

## Adding IN25LINK to Your Link-Edit Procedure

To automatically update the symbolic information in your PROTSYM file whenever a program is link-edited, you can add a postprocessor step directly to the JCL procedure that you use to link-edit your programs.

Follow these steps to update your existing link-edit procedure:

1. Be sure that your link-edit step specifies all of the required link-edit options.
2. If the SYSPRINT output from your link-edit step is written to SYSOUT, change the DD statement so that a temporary disk file is created for your listing.
3. Add a new IN25PARAM step following your link-edit step to generate the parameter statement for the postprocessor.

4. Add a new IN25LINK step to postprocess the listing from the link-edit step. The INPUT DD on this step refers to the same file as the SYSPRINT DD from the link-edit step.
5. Add a new IEBGENER step to print the linkage editor listing only if errors were detected during the link.

The following example shows modifications to a link-edit procedure:

```
//LINK      EXEC PGM=IEWL,REGION=2M,
// PARM='LIST,LET,XREF,MAP'                                <= 1

      (Your existing DD statements for the link edit)

//SYSPRINT DD DSN=&&LST,DISP=(NEW,PASS),                    <= 2
//          UNIT=SYSDA,SPACE=(CYL,(1,2))
//*
//*  GENERATE THE PARAMETER STATEMENT FOR IN25LINK
//*
//CARDS     EXEC PGM=IN25PARM,REGION=1M,COND=(4,LT),        <= 3
// PARM='&MEMBER'
//STEPLIB  DD DSN=CAI.CAVHLOAD,DISP=SHR
//CARDS     DD DSN=&&CARDS,DISP=(NEW,PASS),
//          UNIT=SYSDA,SPACE=(TRK,(1,1))
//*
//*  POST-PROCESS THE LINK EDIT OUTPUT
//*
//SYM       EXEC PGM=IN25LINK,REGION=4M,COND=(4,LT)        <= 4
//STEPLIB  DD DSN=CAI.CAVHLOAD,DISP=SHR
//PROTSYM  DD DSN=USER.PROTSYM,DISP=SHR
//OUTPUT   DD SYSOUT=*,DCB=(RECFM=FBM,LRECL=121,BLKSIZE=2420)
//INPUT    DD DSN=&&LST,DISP=(OLD,PASS)                      (See Note 1)
//CARDS     DD DSN=&&CARDS,DISP=(OLD,DELETE)                 (See Note 2)
//MESSAGE  DD SYSOUT=*
//*
//PRINT    EXEC PGM=IEBGENER,COND=(5,GT,LINK)             <= 5
//SYSUT1   DD DSN=&&LST,DISP=(OLD,DELETE)
//SYSUT2   DD SYSOUT=*
//SYSPRINT DD DUMMY
//SYSIN    DD DUMMY
```

**Notes:**

1. If the SYSPRINT DD on your link-edit step refers to a permanent data set, the INPUT DD for IN25LINK must point to the same data set.
2. If you prefer to pass your parameter statement as an override in the invoking JCL, delete the CARDS step, delete this DD statement, and add SYM.CARDS DD to your invoking JCL member.

**Note:** Using this method, IN25PARM only generates the first parameter card identifying the name of the composite module. No subsequent cards are generated. This serves only to identify the name of the composite module, which is stored in the PROTSYM file. When you attempt to monitor the composite module with CA InterTest for CICS, you may be prompted for additional composite information.

## IN25SYMD

Use program IN25SYMD to load symbolic information from multiple COBOL, Assembler, C, or PL/I listings into your PROTSYM in a single run.

The following table describes the DD statements used by IN25SYMD:

<b>DDname</b>	<b>Description</b>
STEPLIB	The load library containing IN25SYMD.
PROTSYM	The file to which the symbolic information is written.
LISTLIB	The data set name of the PDS, PDSE, CA Librarian library, CA Panvalet library, or CA Endeavor SCM library containing the listings to be added.
REPORT	An execution summary is written to this file.
OPTIN	The input control statements that define the request.

If loading symbolic information from CA Endeavor SCM, the CA Endeavor SCM AUTHLIB and CONLIB must be either in LINKLIST or in the STEPLIB concatenation. When loading symbolic information from CA Librarian or CA Panvalet, the CA Librarian or CA Panvalet CAILIB must be either in Linklist or in the STEPLIB concatenation.

## IN25SYMD Options

Options are passed to the IN25SYMD using parameter statements in the OPTIN DD. Specify the parameter statements as an in-stream file.

Parameter statements contain one or more control statements, separated by commas, and each having the following syntax:

keyword=value

Specify the following option keywords to IN25SYMD:

Keyword	Description
LTPY	Identifies the library type of the listing library specified by the LISTLIB DD statement. This keyword is required. Valid values are: <ul style="list-style-type: none"><li>■ PDS—Partitioned data set (including PDSE)</li><li>■ SEQ—Sequential data set (see Note)</li><li>■ LIB—CA Librarian library</li><li>■ PAN—CA Panvalet library</li><li>■ NDV—CA Endeavor SCM library</li></ul>
FROM	Identifies the member name for single listings, the starting member name for a range of members, or a name prefix with trailing asterisk. This keyword is required.
TO	Identifies the last member name in a range of members.
MSG	Identifies the message reporting level. Valid values are: <ul style="list-style-type: none"><li>■ ALL—displays all messages.</li><li>■ RC—displays a one-line return code message for each program.</li><li>■ NONE—suppresses all messages.</li></ul>

**Note:** When LTPY=SEQ is specified, the sequential file contains only one program listing. Specify the symbolic name using the FROM keyword, omit the TO keyword, and change the LISTLIB DD name to INPUT.

When using LTPY=NDV, you must also change the EXEC card to the following JCL:

```
//STEP1 EXEC PGM=NDVRC1,PARM='IN25SYMD',REGION=4M
```

## Examples

This section contains postprocessor IN25SYMD examples.

### Example 1

All of the programs with the prefix PAY are loaded into the PROTSYM file from a CA Librarian library, with all of the messages displayed in the REPORT file.

```
//STEP1 EXEC PGM=IN25SYMD,REGION=4M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=USER.PROTSYM
//LISTLIB DD DISP=SHR,DSN=USER.LIBRARIAN.LIBRARY
//REPORT DD SYSOUT=*
//OPTIN DD *
        LTP=LIB, FROM=PAY*,MSG=ALL
/*
```

### Example 2

Program COBDEMO is loaded into the PROTSYM file from a sequential listing file, with messages suppressed. Note that the DD statement for the LISTLIB has been renamed to INPUT for LTP=SEQ.

```
//STEP1 EXEC PGM=IN25SYMD,REGION=4M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=USER.PROTSYM
//INPUT DD DISP=SHR,DSN=USER.SEQ.LISTING
//REPORT DD SYSOUT=*
//OPTIN DD *
        LTP=SEQ, FROM=COBDEMO,MSG=NONE
/*
```

### Example 3

Programs whose names begin with C, D, or E are loaded into the PROTSYM file from a partitioned data set. A one-line return code message is written to the REPORT file for each program.

```
//STEP1 EXEC PGM=IN25SYMD,REGION=4M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=USER.PROTSYM
//LISTLIB DD DISP=SHR,DSN=USER.PDS.LIBRARY
//REPORT DD SYSOUT=*
//OPTIN DD *
        LTP=PDS, FROM=C, TO=E9999999,MSG=RC
/*
```



# Chapter 4: Maintaining a PROTSYM File

---

This chapter describes how to maintain the PROTSYM file.

## IN25UTIL

The IN25UTIL batch utility program maintains and reports on the symbolic file.

This program runs in batch, separate from the postprocessors that are used to load symbolic information into the symbolic file.

## IN25UTIL JCL

Member CAVHUTIL in CAI.CAVHPROC contains the following sample JCL for executing IN25UTIL:

```
//          JOB
//IN25UTIL EXEC PGM=IN25UTIL,REGION=2M
//STEPLIB DD DISP=SHR,DSN=CAI.CAVHLOAD
//PROTSYM DD DISP=SHR,DSN=USER.PROTSYM
//OUTPUT DD SYSOUT=*,DCB=(LRECL=133,BLKSIZE=3990)
//MESSAGE DD SYSOUT=*
//CARDS DD *
(input cards go here)
/*
```

The following table describes the DD statements used by IN25UTIL:

DDname	Description
STEPLIB	The load library containing IN25UTIL.
PROTSYM	The file on which maintenance or reporting is being performed.
MESSAGE	Output and messages from IN25UTIL are written to this file.
OUTPUT	Output from the PRINT function is written to this file.
UNLOAD	Program is written to this file by the UNLOAD function.
RELOAD	Program is read from this file by the RELOAD function.
CARDS	Contains the function request statements.

## IN25UTIL Functions

IN25UTIL functions are requested using control statements in the CARDS file. All control statements in the CARDS file must begin in column 1.

**Note:** Some of the following functions support parameters that modify the function results. Supported parameters are noted in the function description. For complete parameter descriptions, see [IN25UTIL Parameters](#) (see page 71).

### **DELETE=*name***

Deletes all symbolic data for the program specified by name.

The PASSWORD control statement must precede the DELETE control statement.

You can use generic program names on the DELETE control statement. Use a trailing wildcard (\*) in the program name to delete all matching programs.

The DELETE function supports the following parameters: AFTERDATETIME, ALL, BEFOREDATETIME, DATETIME, NEWEST, OLDEST. You cannot use these parameters with a generic program name.

### **Example: Delete Symbolic Information by Program**

The following example deletes all symbolic data for program ORDEDIT and the oldest version of program TEST1. It also deletes all programs that start with COB.

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PASSWORD=12345678
DELETE=ORDEDIT,ALL
DELETE=TEST1,OLDEST
DELETE=COB*
/*
```

### **INITIALIZE**

Initializes the symbolic file. This function must always be run after a symbolic file is created using VSAM Access Method Services.

For a newly defined file, the IN25UTIL program preformats all records. If you perform this function for an existing file, all symbolic data is removed.

The PASSWORD control statement must precede the INITIALIZE control statement.

The INITIALIZE function supports the MAXPGMVER and USEDSPACEMSG parameters.

### Examples: Initialize a Symbolic File

The following example initializes a symbolic file without support for multiple program versions:

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PASSWORD=12345678
INITIALIZE
/*
```

The following example initializes a symbolic file that allows for up to three versions of each program:

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PASSWORD=12345678
INITIALIZE,MAXPGMVER=3
/*
```

#### **PASSWORD=*pw***

Specifies a password that is required when maintaining the symbolic file. You need to specify the password only once per execution, but it must precede the first update request.

The value specified must match the value of the SYMPSWD keyword in the IN25SOPT macro.

The default installation password is 12345678.

#### **PRINT=*name***

Prints the newest or most recent version of the program on the PROTSYM file specified by name. Ensure to provide the OUTPUT DDname.

The PRINT function supports the following parameters: AFTERDATETIME, ALL, BEFOREDATETIME, DATETIME, NEWEST, OLDEST.

**Example: Print a Program Listing**

The following example prints the newest saved listing for program ORDEDIT, all saved listings for program TEST1, and all listings for program TEST2 that were saved after 28 January, 2014:

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//OUTPUT DD SYSOUT=A,DCB=(LRECL=133,BLKSIZE=3990)
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PRINT=ORDEDIT
PRINT=TEST1,ALL
PRINT=TEST2,AFTERDATETIME=2014/01/28
/*
```

**PURGE=*nnn***

Removes symbolic data for any program that has not been compiled or assembled within the number of days specified by *nnn*, where *nnn* is a decimal number from 1 to 365.

The PASSWORD control statement must precede the PURGE control statement.

Data for programs loaded using the NOPURGE postprocessor option are not affected by this function.

**Example: Purge Symbolic Information by Age**

The following example purges all programs that have not been compiled or assembled within the last 20 days:

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PASSWORD=12345678
PURGE=20
/*
```

**RELOAD=*name***

Reloads all symbolic data from a dataset to the symbolic file for the program specified by *name*. To reload symbolic data for all programs, specify RELOAD=ALL. Ensure to provide the RELOAD DDname with the following DCB parameter:

```
DCB=(RECFM=FB,LRECL=2042,BLKSIZE=20420)
```

The PASSWORD control statement must precede the RELOAD control statement.

You can use generic program names on the RELOAD control statement. Use a trailing wildcard (\*) in the program name to reload all matching programs.

The RELOAD function supports the following parameters: AFTERDATETIME, ALL, BEFOREDATETIME, DATETIME, NEWEST, OLDEST. These parameters cannot be used with a generic program name.

You can rename a program that is being a reloaded by providing a new program name after the RELOAD control statement and any multiversion subparameters. You cannot rename a program when you specify a generic program name.

**Example: Reload Programs**

The following example reloads the newest version of program ORDEDIT and all versions that were processed in February, 2015. It also reloads the oldest version of ORDEDIT while renaming it to ORDEDIT2 and reloads all programs that start with COB.

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//RELOAD DD DISP=SHR,DSN=USER.UNLOAD,
//          DCB=(RECFM=FB,LRECL=2042,BLKSIZE=20420)
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PASSWORD=12345678
RELOAD=ORDEDIT
RELOAD=ORDEDIT,DATETIME=2015/02
RELOAD=ORDEDIT,OLDEST,ORDEDIT2
RELOAD=COB*
/*
```

**REPORT**

Produces a Symbolic File report that contains statistics and a detailed report on each program.

**Example: Generate Reports**

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
REPORT
/*
```

**UNLOAD=*name***

Unloads all symbolic data from the symbolic file to a dataset for the program specified by name. To unload symbolic data for all programs, specify UNLOAD=ALL. Ensure to provide the UNLOAD DDname with the following DCB parameter:

```
DCB=(RECFM=FB,LRECL=2042,BLKSIZE=20420)
```

The PASSWORD control statement must precede the UNLOAD control statement.

You can use generic program names on the UNLOAD control statement. Use a trailing wildcard (\*) in the program name to unload all matching programs.

The UNLOAD function supports the following parameters: AFTERDATETIME, ALL, BEFOREDATETIME, DATETIME, NEWEST. You cannot use these parameters with a generic program name.

**Example: Unload Programs**

The following example unloads all versions of program ORDEDIT that were processed after 31 December, 2014. It also unloads all programs that start with COB.

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//UNLOAD DD DSN=USER.UNLOAD,
//          DISP=(NEW,CATLG,CATLG),SPACE=(CYL,(5,10),RLSE),
//          DCB=(RECFM=FB,LRECL=2042,BLKSIZE=20420)
//CARDS DD *
UNLOAD=ORDEDIT,AFTERDATETIME=2014/12/31
UNLOAD=COB*
/*
```

**UPDATE**

Updates the values for the USEDSPACEMSG parameter. The PASSWORD control statement must precede the UPDATE control statement.

**Example: Update a PROTSYM Parameter**

The following example sets the USEDSPACEMSG parameter of the symbolic file to 80:

```
//UTILITY JOB
//STEP1 EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//MESSAGE DD SYSOUT=*
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PASSWORD=12345678
UPDATE,USEDSPACEMSG=80
/*
```

**Example: Reorganize the Symbolic File**

The following example reorganizes or changes the size of the symbolic file. This job unloads all programs, deletes and defines the symbolic file, initializes the symbolic file, reloads all programs, and generates a system report.

```
//UTILITY JOB
//UNLOAD EXEC PGM=IN25UTIL
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//SYSUDUMP DD SYSOUT=*
//MESSAGE DD SYSOUT=*
//UNLOAD DD DSN=USER.RELOAD,
//      DISP=(NEW,CATLG,CATLG),SPACE=(CYL,(5,10),RLSE),
//      DCB=(RECFM=FB,LRECL=2042,BLKSIZE=20420)
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
UNLOAD=ALL
/*
//IDCAMS EXEC PGM=IDCAMS,COND=(0,NE,UNLOAD)
//SYSUT1 DD UNIT=SYSDA,VOL=SER=SYMVOL,DISP=SHR
//SYSIN DD *
        DELETE 'CAI.PROTSYM'
        DEFINE CLUSTER (NAME(CAI.PROTSYM) -
                VOLUME(SYMVOL) -
                FILE(SYSUT1) -
                CYLINDERS(20) -
                CISZ(2048) -
                RECSZ(2040 2040) -
                SHR(4 4) -
                NUMBERED) -
        DATA (NAME(CAI.PROTSYM.DATA))
/*
//RELOAD EXEC PGM=IN25UTIL,COND=(0,NE,UNLOAD)
//STEPLIB DD DSN=CAI.CAVHLOAD,DISP=SHR
//SYSUDUMP DD SYSOUT=*
//MESSAGE DD SYSOUT=*
//RELOAD DD DISP=SHR,DSN=USER.RELOAD,
//      DCB=(RECFM=FB,LRECL=2042,BLKSIZE=20420)
//PROTSYM DD DSN=CAI.PROTSYM,DISP=SHR
//CARDS DD *
PASSWORD=12345678
INITIALIZE
RELOAD=ALL
REPORT
/*
```

## IN25UTIL Parameters

Some functions support parameters that modify the function results. The functions that support these parameters are noted in the function description.

### **AFTERDATETIME=YYYY/MM/DD HH:MM:SS**

Applies the function to all versions of the saved source listing for the program specified by *name* which were compiled after the specified date timestamp.

You can provide a partial timestamp by omitting time values starting from the smallest unit of time.

**Note:** A partial timestamp can also be provided for BEFOREDATETIME and DATETIME.

### **ALL**

Applies the function to all versions of the saved source listing for the program specified by *name*. Do not confuse the ALL parameter with the RELOAD=ALL and UNLOAD=ALL functions.

### **BEFOREDATETIME=YYYY/MM/DD HH:MM:SS**

Applies the function to all versions of the saved source listing for the program specified by *name* which were compiled before the specified date timestamp.

### **DATETIME=YYYY/MM/DD HH:MM:SS**

Applies the function to all versions of the saved source listing for the program specified by *name* which were compiled on the specified date timestamp.

### **MAXPGMVER**

Indicates the number of versions of a single program the PROTSYM will allow (up to 255). The default value is 1, which indicates no multiple program versions. For assembler programs, multiple program version support uses the HLASM compile date/time on the listing that has the format 2014/08/04 08.36. Hence, multiple program listings for the same program that are compiled within the same minute are not supported.

### **NEWEST**

Applies the function to the newest version of the saved source listing for the program specified by *name*.

### **OLDEST**

Applies the function to the oldest version of the saved source listing for the program specified by *name*.

**USEDSPACMSG**

Specifies the limit of used space in PROTSYM in percentage. When the limit is reached, the SYM070 message is issued. If the value equals 0, the SYM070 message is not issued.

**Default:** 0

**Values:** 0-99

**Note:** For syntactic examples of these parameters, see "Examples."

# Chapter 5: Dynamic Symbolic Support for CA Endeavor Software Change Manager

---

CA Technologies Application Quality and Testing Tools provides an automated way to update your PROTSYM files. This feature is named dynamic symbolic support. Dynamic symbolic support is available to all CA Endeavor SCM for Mainframe customers.

Dynamic symbolic support helps ensure that the correct symbolic is used for debugging, diagnostics, or measurements. This chapter contains the information required to use this feature.

This section contains the following topics:

[Testing Tools Supporting Dynamic Symbolic File Updating](#) (see page 73)

[Dynamic Symbolic Support Activation](#) (see page 74)

[Dynamic Symbolic Support Execution](#) (see page 74)

[Listing Server](#) (see page 75)

[Define Unique PROC](#) (see page 76)

[PROC Customization](#) (see page 77)

[JCL Considerations](#) (see page 78)

[CA Endeavor SCM Auto-Populate Activity Log](#) (see page 79)

## Testing Tools Supporting Dynamic Symbolic File Updating

The testing tools products that support the automatic updating of symbolic files (PROTSYM) include:

- CA InterTest Batch
- CA InterTest for CICS
- CA SymDump for CICS
- CA SymDump Batch

## Dynamic Symbolic Support Activation

When symbolic information is required for a program, the CA Technologies testing tools product looks for this information in the PROTSYM files specified for the program that is being debugged or reviewed.

If one of the PROTSYM entries matches the compile date and time, that entry in the PROTSYM is used. If a matching entry is not found, and if dynamic symbolic support is activated, the system attempts to locate the CA Endeavor SCM footprint and the listing associated with the load module library, from where the load module was loaded.

If a match is found, the system automatically post-processes the CA Endeavor SCM listing into a designated PROTSYM file so that the correct symbolics are used without any interruption or program setup.

Dynamic symbolic support is activated based on individual product installation and option settings. However, the service that dynamic symbolic support provides is centrally delivered through the symbolic common components. We recommend that you install only one copy of the symbolic common components.

## Dynamic Symbolic Support Execution

Dynamic symbolic support execution depends on whether your site has installed CA Endeavor SCM, and whether your installation uses a single CA Endeavor SCM site ID or multiple CA Endeavor SCM site IDs.

**More information:**

[Single Site ID](#) (see page 74)

[Multiple Site IDs](#) (see page 75)

### Single Site ID

Users with a single CA Endeavor SCM site ID have the following options:

- Have one copy of C1DEFLT.S.
- Run dynamic symbolic support in the address space of the CA Technologies testing tools product.

**Note:** To implement dynamic symbolic support in a testing tools environment, see the *Installation Guide* for the testing tools product that you are using.

## Multiple Site IDs

Users with multiple CA Endeavor SCM site IDs have the following options:

- Have multiple C1DEFLT.
- Allow dynamic symbolic support for multiple site IDs to be implemented using the Listing Server.

**Note:** If you are using dynamic symbolic support in a CICS environment, the Listing Server methodology is always used regardless of the number of site IDs.

## Listing Server

When dynamic symbolic support service is requested, Listing Server is spawned as a started task (STC) through CA CCI.

**Note:** Data set CAI.CAVHPROC contains a sample PROC that can be used to start the Listing Server.

## Define Unique PROC

Define a unique PROC in your PROCLIB for each CA Endeavor SCM site ID in your environment.

Each copy of the PROC must have the following PROCNAME:

*xxxxxxx*y

- *xxxxxxx* is the first seven characters of the PROCNAME defined in the testing tools product.
- *y*, the eighth character, is your CA Endeavor SCM site ID.

For example, if the first seven characters of the PROCNAME are INTNDVR and the CA Endeavor SCM site ID is 4, the PROCNAME defined in your PROCLIB is INTNDVR4.

**Note:** The first seven character names defined in your PROCLIB must match the PROCNAME defined to the CA Technologies testing tools product.

PROCNAME is defined in the following elements by product:

- CA InterTest Batch is defined in IN25SITE
- CA SymDump Batch is defined in CAOUXFDR
- CA InterTest for CICS is defined in IN25OPTS
- CA SymDump for CICS is defined in IN25OPTS
- CA Mainframe Application Tuner is defined in the TUNUDEF5 member of the option library

## PROC Customization

The sample PROC can be found in hlq.CAVHPROC. When modifying the PROC, consider the following recommendations:

- Specify MSGLEVEL=(1,1) on the JOB statement so that a more comprehensive view of the events leading up to a problem can be obtained. Set MSGCLASS to a class that does not get purged immediately after job termination. A sample JOB statement is shown next:

```
//INTNDV4 JOB (JOBACNT),MSGLEVEL=(1,1),MSGCLASS=X
```

- Remove the STEPLIB DD statement containing the yourhlq.cavhload data set name if the data sets that contain the symbolic common components are defined in the LINKLIST. A sample STEPLIB DD statement is shown next:

```
//STEPLIB DD DSN=yourHLQ.cavhload,DISP=SHR <== MODIFY
```

**Note:** The load module data sets containing symbolic common components must be APF-authorized.

- The MODLRESP DD statement specifies the model space allocation (for CA Endeavor for SCM response files) to override the default of (TRK, (5,5)). Depending on your requirement, you can override this limit to avoid SB37s. A sample MODLRESP DD statement is shown next:

```
//MODLRESP DD DUMMY,SPACE=(CYL,(1,1)) MODEL FOR RESPONSE DATASET
```

- The MODLLIST DD statement specifies the model space allocation (for CA Endeavor for SCM listing files) to override the default of (TRK, (5,5)). Depending on your requirement, you can override this limit to avoid SB37s. A sample MODLLIST DD statement is shown next:

```
//MODLLIST DD DUMMY,SPACE=(CYL,(5,5)) MODEL FOR LISTING DATASET
```

- The SRVPRINT DD statement is used to log CA CCI activities. The presence of SRVPRINT triggers logging information across all dynamic symbolic support components, including CA Endeavor for SCM activities, system assigned DDnames and space allocated for all the work files. A sample SRVPRINT DD statement is shown next:

```
//SRVPRINT DD SYSOUT=* <== COMMENT OUT TO TURN OFF LOGGING
```

**Note:** We strongly recommend that you do not comment out this DD statement because the information is critical for CA Technical Support to help you resolve any problems you encounter.

- The DSSLOG DD statement is used to log dynamic symbolic support-related diagnostic messages including Binder errors and CA CCI feedback messages. A sample DSSLOG DD statement is shown next:

```
//DSSLOG DD SYSOUT=* <== COMMENT OUT TO TURN OFF DSS LOGGING
```

**Note:** We strongly recommend that you do not comment out this DD statement because the information is critical for CA Technical Support to help you resolve any problems you encounter.

- The JOBLOG DD statement is used to trigger message extraction when any subtask encounters critical errors or abends. The extracted messages, including PSW and the registers when the abend occurred, are reported back to the remote host. A sample JOBLOG DD statement is shown next:

```
//JOBLOG DD SYSOUT=* <== REQUIRED FOR REPORTING REMOTE FAILURES
```

**Note:** We strongly recommend that you do not comment out this DD statement because the information is critical for CA Technical Support to help you resolve any problems you encounter.

If the data sets containing the CA Endeavor SCM C1DEFLT, CA Endeavor SCM CSIQLOAD (CONLIB), and CSIQAUTH (AUTHLIB) data sets are not defined in the LINKLIST, also define these data sets in the STEPLIB DD statement concatenation.

**Note:** CONLIB must be defined with a DDName of CONLIB, not part of the STEPLIB concatenation.

## JCL Considerations

For single C1DEFLT environment, in addition to the DD statements required to run the CA Technologies testing tools product, you must take the following actions:

- If the data sets containing the load module libraries of the symbolic common components are not defined in the LINKLIST, define them using the STEPLIB DD statement concatenation.

**Note:** The load module data sets containing symbolic common components must be APF-authorized.

If the data sets containing the CA Endeavor SCM C1DEFLT, CA Endeavor SCM CSIQLOAD (CONLIB), and CSIQAUTH (AUTHLIB) data sets are not defined in the LINKLIST, also define these data sets in the STEPLIB DD statement concatenation.

**Note:** CONLIB must be defined with a DDName of CONLIB, not part of the STEPLIB concatenation.

- Set//SRVPRINT DD SYSOUT=\* to trigger dynamic symbolic support related logging
- Set//DSSLOG DD SYSOUT=\* to receive the messages extracted from the list server when you have a multiple user environment.

**Note:** The DSSLOG DD statement is not required for a single C1DEFLT environment.

## CA Endeavor SCM Auto-Populate Activity Log

The following is a sample Auto Populate Activity Log that displays a list of activities with details such as date and time of each dynamic symbolic support event.

```

*** IN25NDVR STARTED AT: 05182011.15021439.
***   L O G   F I L E   DDNAME:SYS00045
*** ALLOCATING PROTSYM INPUTT FILE.
*** PROTSYM INPUTT FILE ALLOCATED. DDNAME: SYS00046 SPACE=(TRK,(50,50))
*** ALLOCATING PROTSYM OUTPUT FILE.
*** PROTSYM OUTPUT FILE ALLOCATED. DDNAME: SYS00047 SPACE=(TRK,(50,50))
*** ALLOCATING PROTSYM CARDS   FILE.
*** PROTSYM CARDS   FILE ALLOCATED. DDNAME: SYS00048 SPACE=(TRK,(01,01))
*** ALLOCATING PROTSYM MESSAGE FILE.
*** PROTSYM MESSAGE FILE ALLOCATED. DDNAME: SYS00049 SPACE=(TRK,(01,03))
*** ALLOCATING PROTSYM  MSGS  FILE.
*** PROTSYM MSGS   FILE ALLOCATED. DDNAME: SYS00050 SPACE=(TRK,(01,03))
*** ALLOCATING PROTSYM REPORT FILE.
*** PROTSYM REPORT FILE ALLOCATED. DDNAME: SYS00051 SPACE=(TRK,(01,03))
*** ALLOCATING NDVR MESSAGE FILE. *
*** NDVR MESSAGE FILE ALLOCATED. DDNAME: SYS00052  SPACE=(TRK,(01,03))
*** ALLOCATING RESPONSE FILE   ***
*** NDVR RESPONSE FILE ALLOCATED. DDNAME: SYS00053 SPACE=(TRK,(05,05))
*** ALLOCATING LISTING FILE.    ***
*** NDVR LISTING FILE USED AS INPUT TO PROTSYM POST PROCESSOR ALLOCATED. DDNAME:
SYS00054 SPACE=(CYL,(05,05))
** FOOTPRINT:
   @TT00LSQABASE   COBQAA05  COBCICS PRD    10104...15:35.0.....&\...\{.
*** CALLING ENDEVOR API FOR AEPRE OPTION ***
*** BALRING TO ENA$NDVR *****
*** ENDEVOR API STARTED AT:    15:02:14:57 NDVRELEM:COBQAA05  NDVRNAM2:COBQAA05
*** ENDEVOR API ENDED   AT:    15:02:17:05
*** ENDEVOR AEPRE API FUNCTION RETURNED RC 0 ***
*** ALLOCATING PROTSYM FILE. DSN:  AD1QA.SYMDUM85.GUI.NDVRSYM.NDV14
*** PROTSYM FILE ALLOCATED.    DDNAME: SYS00066
*** ADDING COBQAA05 AS COBQAA05 TO PROTSYM DSN: AD1QA.SYMDUM85.GUI.NDVRSYM.ND
*** IN25CDRV RETURN CODE = 0   ***
*** CALLING NDVR TO TERMINATE API ***
*** ENA$NDVR API TERMINATED. ***
*** IN25NDVR ENDED AT: 05182011.15021770.

```



# Chapter 6: Messages

---

This chapter contains messages produced by the symbolic postprocessors and the maintenance program IN25UTIL.

## Dynamic Symbolic Support Messages

### CAIN5900I

**mm/dd/yyyy hh:mm:ss IN25NDVR STARTED FOR PRGNNAME – pppppppp.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the Listing Server is retrieving the symbolic for program named pppppppp. This message is used to serve as a beginning bookmark for message extraction. All messages issued after this message are extracted by message extraction service.

**Action:**

None.

### CAIN5903E

**mm/dd/yyyy hh:mm:ss IN25NSRV CCI SPNPARM FAILED.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN25NSRV issued a CCI SPNPARM request. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5903E

**mm/dd/yyyy hh:mm:ss IN2NSRV CCI INIT FAILED.**

**Reason:**

This message is issued by IN2NSRV. where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. CCI INIT action has failed. This error occurred when IN2NSRV issued a CCI INIT request. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5904I

**mm/dd/yyyy hh:mm:ss IN2NSRV WAITING FOR WORK.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the Listing Server is waiting for work.

**Action:**

None.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN2NSRV RECVANY FAILED.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN2NSRV issued a CCI Receive Any request. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN2NSRV RECVANY FAILED, INVALID DATA.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN2NSRV issued a CCI Receive Any request and the data received are invalid. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN2NSRV RECVANY FAILED, RECEIVED NULLS.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN2NSRV issued a CCI Receive Any request and the data received contained all null values. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to inspect the block received. This could be the result of transmission error. If the problem persists contact CA Support.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN2NSRV RECVANY FAILED, INVALID LENGTH.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN2NSRV issued a CCI Receive Any request and length of the data block received was incorrect. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to inspect the length of data block received. This could be the result of transmission error. If the problem persists contact CA Support.

## CAIN5907E

**mm/dd/yyyy hh:mm:ss IN25NSRV SENDSPEC FAILED.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN25NSRV issued a CCI Send action. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the reasons for the failure. This could be the result of transmission error. If the problem persists contact CA Support.

## CAIN5908W

**mm/dd/yyyy hh:mm:ss IN25NSRV GETMAIN FAILED.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. The message indicated that GETMAIN for 32K of main storage has failed.

**Action:**

Make sure that you have specified a sufficiently large region size to meet the many main storage requirements of the Listing service.

## CAIN5909I

**mm/dd/yyyy hh:mm:ss IN25NSRV REQUEST RECEIVED FOR eeeeeeee.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that a listing request for element named eeeeeeee has been received.

**Action:**

None.

## CAIN5913I

**mm/dd/yyyy hh:mm:ss IN2NSRV SENDING RESPONSE****Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the request by message CAIN5909 has been serviced and response is being sent back to the remote host.

**Action:**

None.

## CAIN5930I

**mm/dd/yyyy hh:mm:ss IN2NSRV CCI FEEDBACK: feedback info.****Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is the message that is usually issued in conjunction with CCI-related error conditions. Feedback is a 256 bytes area containing CCI return codes, reason codes, and brief description associated with the error encountered.

**Action:**

Use the information provided in this message in conjunction with the failure message to diagnose the error.

## CAIN5950I

**mm/dd/yyyy hh:mm:ss IN2NSRV SHUTDOWN.****Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the Listing server is shutting down.

**Action:**

None.

## CAIN5970W

### **LINK TO IN25SPOL FAILED.**

#### **Reason:**

This message is issued by IN25NSRV indicating that LINK to IN25SPOL has failed. Message extraction will not be performed.

#### **Action:**

Determine that the data set containing IN25SPOL is either defined in the LINKLIST or is properly defined in the STEPLIB concatenations.

## CAIN5980E

### **CA SCM CRITICAL ERROR. ERROR CODE: eeee. REQUEST FOR pppppppp NOT SERVICED.**

#### **Reason:**

This message is issued by IN25NSRV and is used as an end bookmark for message extraction. All messages issued before this message are extracted by the message extraction service.

#### **Action:**

None.

## CAIN5990I

### **ALLOCATION OF LOG FILE FAILED. LOGGING DISABLED.**

#### **Reason:**

This message is issued by IN25FSYM, indicating that dynamic allocation for SRVPRINT DD has failed. Logging activities is disabled. This message is usually followed by IBM IKJ5635 message providing the dynamic allocation text unit that failed.

#### **Action:**

Determine and correct the cause for failure then retry the action.

## CAIN5990I

### **LINK TO IN25SPOL FAILED.**

#### **Reason:**

This message is issued by IN25NSRV. LINK SVC for IN25SPOL has failed. Message extraction will not be performed.

#### **Action:**

Make sure that the data set containing IN25SPOL is either defined in the LINKLIST or properly defined in the STEPLIB DD.

## CAIN5991W

### **HHMM DOES NOT MATCH.**

#### **Reason:**

This message is issued by IN25FSYM. The hour and minute of the timestamp found in the symbolic does not match the timestamp provided by the caller for the same symbolic. Requested action is not performed.

#### **Action:**

Provide the correct timestamp value and try the action again.

## CAIN5995E

### **NO PROTSYM SEARCH LIST PROVIDED.**

#### **Reason:**

This message is issued by IN25FSYM. User did not provide one or more PROTSYM data set names to perform symbolic search. Requested action is not performed.

#### **Action:**

Provide at least one or up to a maximum of eight PROTSYM fully qualified data set names to be used for symbolic search.

## CAIN6000E

**DYNAMIC UNALLOCATION FAILED FOR nnnnnnnn. RC= rr. RSN= ssssssss.**

**Reason:**

This message is issued by IN25FSYM. Dynamic unallocation of data set with nnnnnnnn DD name has failed. Return code from Dynamic Allocation is rr and the reason code is ssssssss.

**Action:**

Use the return code and reason code to determine the cause of the failure. Correct the error and retry the action.

## CAIN6010W

**LOAD OF pppppppp FAILED. RC= rr.**

**Reason:**

This message is issued by IN25FSYM. Loading of program named pppppppp has failed. The return code is rr.

**Action:**

Make sure that the data set containing the pppppppp program is in the LINKLIST or defined in the STEPLIB concatenation.

## CAIN6020W

**FAILED IN ROUTINE: rrrrrrrrr RC= rr.**

**Reason:**

This message is issued by IN25FSYM. Routine named rrrrrrrr has failed with a return code of rr. This message is usually associated with IN25SAPI and rrrrrrrr is the failed SAPI function.

**Action:**

Determine the error and retry the request.

## CAIN6070E

### **CRITICAL ERROR LD@DSSDSN INVALID VALUE.**

#### **Reason:**

This message is issued by IN25FSYM. The data set name provided in LD@DSSDSN is invalid.

#### **Action:**

LD@DSSDSN should contain a valid DD name to be used for DSS logging. It is usually specified as DSSLOG. Correct the DD name and retry the action.

## CAIN7000W

### **IN25NDVR MAJOR ERROR, LOG FILE NOT OPENED**

#### **Reason:**

SRVPRINT log file not opened. Endeavor activity log disabled.

#### **Action:**

We recommend that //SRVPRINT DD SYSOUT=\* be defined in the job's JCL so that relevant error can be captured to assist in problem analysis. This would avoid the need to recreate the error.

## CAIN7010I

### **IN25NDVR ALLOCATION OF LOG FILE FAILED.**

#### **Reason:**

Dynamic allocation of activity log has failed. This message is usually followed by IBM IKJ5635 message providing the dynamic allocation text unit that failed.

#### **Action:**

Determine and correct the cause of the error and retry the request.

## CAIN7020W

### **LOAD OF IN25DALC FAILED.**

#### **Reason:**

IN25NDVR encountered an error trying to LOAD IN25DALC. Endeavor List request will not be performed.

#### **Action:**

Make sure that the data set containing IN25DALC load module is either defined in the LINKLIST or is defined in the STEPLIB concatenation.

## CAIN7030W

### **LOAD OF ENA\$NDVR FAILED.**

#### **Reason:**

IN25NDVR cannot LOAD the Endeavor API. Endeavor List request will not be performed.

#### **Action:**

Make sure that Endeavor AUTHLIB and CONLIB data sets are either defined in the LINKLIST or defined in the job's JCL.

## CAIN8000W

### **JESMSG LG JCT MTTR FOUND.**

#### **Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicates that MTTR of JESMSG LG JCT was found.

#### **Action:**

None.

## CAIN8010I

### **JESYSMSG JCT MTTR FOUND.**

#### **Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicates that MTTR of JESMSG LG JCT was found.

#### **Action:**

None.

CAIN8020I

**ACQUIRED MSGLOG AND SYSMSG JCT**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This message indicates that the JCT for JESMSG LG and JESYSMSG have been acquired.

**Action:**

None.

CAIN8030W

**UNABLE TO ACQUIRE JCT OF EITHER JESMSG LG OR JESYSMSG.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicated that IN25SPOL was unable to acquire the JCT of either JESMSG LG or JESYSMSG. Message extraction will not be performed.

**Action:**

Contact CA Support with the information.

CAIN8040I

**STIMER WAIT FOR JQE UPDATE.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicated that IN25SPOL has issued a STIMER SVC to wait for JQE update to complete.

**Action:**

None.

## CAIN8050I

### **THERE ARE NO SJQES RETURNED.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSREQ did not return SJQES information. Message extraction will not be performed.

#### **Action:**

None.

## CAIN8060I

### **THERE ARE NO SOUTS RETURNED.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSREQ did not return SOUTS information. Message extraction will not be performed.

#### **Action:**

None.

## CAIN8070I

### **UNABLE TO ACCESS JOB QUEUE.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSREQ was unable to access JES job queue.

#### **Action:**

None.

## CAIN8080I

### **IN25SS71 LOAD FAILED.**

#### **Reason:**

This message is issued by IN25SPOL indicating that loading of IN25SS71 has failed.

#### **Action:**

Make sure that the data set containing IN25SS71 is either in the LINKLIST or the STEPLIB concatenation is properly defined.

CAIN8090I

**IN25SDSB LOAD FAILED.**

**Reason:**

This message is issued by IN25SPOL indicating that loading of IN25SDSB has failed.

**Action:**

Make sure that the data set containing IN25SDSB is either in the LINKLIST or the STEPLIB concatenation is properly defined

CAIN8091I

**jjjj IS THE PRIMARY JOB ENTRY SUBSYSTEM. SYSTEM ID FROM JQRYSSID ==> iiiii.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating that jjjj is the primary job entry subsystem whose id is iiiii.

**Action:**

None.

CAIN8092I

**dddddddd IS THE DDN OF jjjjjjjj RETURNED.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating dddddddd is the DD name of jjjjjjjj returned. jjjjjjjj can either be JESMSGGLG or JESYSMSG.

**Action:**

None.

## CAIN8093I

**ASSOCIATED DSN: datasetname.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating that the fully qualified data set name for the DD name cited in message CAIN8092 is datasetname.

**Action:**

None.

## CAIN8094I

**JOBNAME: jobname JOBID: iiiiii**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating that the active job name is jobname whose jobid is iiiiii.

**Action:**

None.

## CAIN8095I

**IEFSSREQ TYPE=QUERY FAILED. RETURN CODE= cccc REASON CODE= ssss**

**Reason:**

This message is issued by IN25SPOL indicating that IEFSSREQ type of query has failed with a return code of cccc and reason code of ssss.

**Action:**

Determine the cause of failure based on the return code and reason code.

CAIN8096I

**IEFSSI SUBFUNCTION 80 FAILED. SSOBRETN= rrrr STATREAS= ssss.**

**Reason:**

This message is issued by IN25SPOL indicating that IEFSSI subfunction 80 has failed. The subsystem return code is rrrr and reason code is ssss. Message extraction will not be performed.

**Action:**

Contact CA Support.

CAIN8097I

**JESMSG LG dddddddd NOT FOUND.**

**Reason:**

This message is issued by IN25SPOL indicating that dddddddd token for JESMSG LG is not found.

**Action:**

None.

CAIN8098W

**POSSIBLE CHAINING ERROR. SEE REG 8 FOR DETAILS.**

**Reason:**

This message is issued by IN25SPOL indicating that IN252POL was unable to locate SSVE control blocks via chaining through various JES control blocks. Message extraction will not be performed. General Purpose Register 8 points to the chain.

**Action:**

Contact CA Support.

## CAIN8100I

### **SPOOL READ FUNCTION CURRENTLY DOES NOT SUPPORT JES3 AT BELOW ZOS 01.11.01 LEVEL.**

**Reason:**

This message is issued by IN25SPOL indicating that spool read function does not support JES3 at a level below ZOS 01.11.01 level. Message extraction will not be performed.

**Action:**

None.

## CAIN8100I

### **STARTING MSGLOG00 PROCESS.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that message extraction of JESMSGLG is being started.

**Action:**

None.

## CAIN8110I

### **STARTING SYSMMSG00 PROCESS.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that message extraction of JESYSMSG is being started.

**Action:**

None.

CAIN8120I

**OBTAINED JCT FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71. It is an informational message indicating that JCT information was obtained from in-storage buffer.

**Action:**

None.

CAIN8120I

**OBTAINED IOT FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71. This is an informational message indicating that IOT information was obtained from in-storage buffer.

**Action:**

None.

CAIN8130E

**INVALID REQUEST.**

**Reason:**

This message is issued by IN25SS71. This is a should not occur error.

**Action:**

Contact CA Support.

CAIN8140W

**FAILED TO LOCATE PDDBS FOR BOTH JESMSG LG AND JESYSMSG.**

**Reason:**

This message is issued by IN25SS71 indicating that it cannot locate the PDDBs for JESMSG LG and JESYSMSG.

**Action:**

Contact CA Support.

## CAIN8150I

### **JESMSG LG BUFR IS EMPTY**

**Reason:**

This message is issued by IN25SS71 indicating that the JESMSG LG buffer is empty. Message extraction cannot be performed.

**Action:**

None.

## CAIN8160I

### **MSGLOG OBTAINED FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that JESMSG LG messages were extracted from in-storage buffer.

**Action:**

None.

## CAIN8170I

### **MSGLOG READ FROM LAST TRACK.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that JESMSG LG messages were extracted from the last track specified in MTTR.

**Action:**

None.

CAIN8180I

**MSGLOG RECORD COUNT EXHAUSTED.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that JESMSGLOG messages extraction has exhausted its record count.

**Action:**

None.

CAIN8190I

**SYSMSG RECORD COUNT IS ZERO.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that JESYSMSG record count is zero.

**Action:**

None.

CAIN8200I

**SYSMSG OBTAINED FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that JESYSMSG information was extracted from in-storage buffer.

**Action:**

None.

## CAIN8210I

### **SYSMSG RECORD COUNT EXHAUSTED.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that JESYSMSG messages extraction has exhausted its record count.

**Action:**

None.

## CAIN8230I

### **SYSMSG READ FROM LAST TRACK.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that JESYSMSG messages were extracted from the last track specified in MTTR.

**Action:**

None.

## CAIN8240E

### **SUBSYSTEM FUNCTION 71 SPOOL READ FOR JCT FAILED. RC= rrrr SSOBRETN= cccc SSJIRETN= ssss.**

**Reason:**

This message is issued by IN25SS71 indicating that IEFSSREQ subfunction 71 has failed reading the JCT. The return code is rrrr, subsystem reason code is cccc, subsystem return code is ssss. Message extraction is not performed.

**Action:**

Contact CA Support with the error message.

## CAIN8260W

### **OUTPUT DCB OPEN FAILED.**

**Reason:**

This message is issued by IN25SS71 indicating that open attempt of output DCB for JOBLOG DD statement has failed. Message extraction will not be performed.

**Action:**

Determine the reason for open failure. DD statement: `//JOBLOG DD SYSOUT=*` may be missing.

## CAIN8270I

### **NO MORE SYSOUT FROM JES.**

**Reason:**

This message is issued by IN25SS71 indicating end of file condition has reached.

**Action:**

None.

## CAIN8300I

### **JCT RETREIVAL ERROR.**

**Reason:**

This message is issued by IN25SDSB indicating there was an error retrieving job's JCT. Message extraction will not be performed.

**Action:**

None.

## CAIN8310I

### **IOT RETRIEVAL ERROR.**

**Reason:**

This message is issued by IN25SDSB indicating there was an error retrieving job's IOT. Message extraction will not be performed.

**Action:**

None.

## CAIN8320I

### **OBTAINED IOT FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SDSB when CA Technical Support requests for diagnostic messages. The message indicated that job's IOT information was obtained from in-storage buffer.

**Action:**

None.

## CAIN8330E

### **JESMSG LG ALLOCATION FAILED. MSGLOG NOT COLLECTED.**

**Reason:**

This message is issued by IN25SDSB indicating that dynamic allocation of JESMSG LG data set name has failed. Message extraction will not be performed.

**Action:**

None.

## CAIN8340E

### **JESYSMSG ALLOCATION FAILED. SYSMSG NOT COLLECTED.**

**Reason:**

This message is issued by IN25SDSB indicating dynamic allocation of JESYSMSG data set name has failed. Message extraction will not be performed.

**Action:**

None.

## CAIN8350W

### **FAILED TO LOCATE PDDBS FOR BOTH JESMSG LG AND JESYSMSG.**

**Reason:**

This message is issued by IN25SDSB indicating that attempts to locate the PDDBs for JESMSG LG and JESYSMSG has failed. Message extraction will not be performed.

**Action:**

None.

CAIN8360I

**SUBSYSTEM FUNCTION 71 SPOOL READ FOR JCT FAILED. RC= rrrr SSOBRETN= ssss  
SSJIRETN=nnnn**

**Reason:**

This message is issued by IN25SDSB indicating that IEFSSREQ subfunction 71 has failed reading the JCT. The return code is rrrr, subsystem reason code is ssss, subsystem return code is nnnn. Message extraction is not performed.

**Action:**

Contact CA Support with this message.

CAIN8380I

**JESMSGLG ALLOCATED. DDNAME: dddddddd**

**Reason:**

This message is issued by IN25SDSB when CA Technical Support requests for diagnostic messages. The message provides the dynamic allocation returned DDNAME as dddddddd.

**Action:**

None.

CAIN8390I

**JESMSGLG DYNAMIC ALLOCATION FAILED. RC/RSN: rrrr/sss**

**Reason:**

This message is issued by IN25SDSB indicating that dynamic allocation of SYSOUT for JESMSGLG has failed. The dynamic allocation return code is rrrr, its reason code is ssss. This message is usually followed by IBM IKJ5635 message providing the dynamic allocation text unit that failed. Message extraction will not be performed.

**Action:**

Determine and correct the cause for the failure, than retry the request.

## CAIN8400W

### **INPUT DCB OPEN FAILED.**

#### **Reason:**

This message is issued by IN25SDSB indicating that open of input DCB has failed. The two input data sets involved are JESMSG LG and JESYSMSG. When these data sets were allocated successfully, open should not fail. Message extraction will not be performed.

#### **Action:**

Determine and correct the cause of the failure, and retry the request.

## CAIN8410I

### **INPUT DDNAME: sys END OF FILE**

#### **Reason:**

This message is issued by IN25SDSB indicating the end of file condition for DD named sys has reached.

#### **Action:**

None.

## CAIN8410W

### **OUTPUT DCB OPEN FAILED.**

#### **Reason:**

This message is issued by IN25SDSB indicating that open of JOBLOG SYSOUT has failed.

#### **Action:**

Verify that //JOBLOG DD SYSOUT=\* is defined in the job's JCL.

## SYM Messages

### SYM002

**LISTER= OPTION INVALID, NO LISTING SAVED**

**Reason:**

The LISTER option was invalid.

**Action:**

Correct the LISTER option and resubmit your job stream.

### SYM003

**CUTPRINT= OPTION INVALID, LISTING WILL BE PRINTED**

**Reason:**

The CUTPRINT option was invalid.

**Action:**

Correct the CUTPRINT option and resubmit your job stream.

### SYM004

**SYMBOLIC INFORMATION HAS BEEN SET AS NON-PURGABLE**

**Reason:**

The NOPURGE option was specified on the parameter statement.

**Action:**

None.

### SYM005

**PARAMETER OPTIONS INVALID, SYMBOLIC STEP NOT RUN**

**Reason:**

An invalid option was specified on the parameter statement.

**Action:**

Correct the parameter statement and resubmit your job stream.

## SYM006

### **LISTER=XXX REQUESTED**

**Reason:**

This identifies the LISTER option specified.

**Action:**

None.

## SYM007

### **CUTPRINT=XXX REQUESTED**

**Reason:**

This identifies the CUTPRINT option specified.

**Action:**

None.

## SYM008

### **CONTROL STATEMENT IS MISSING - JOB TERMINATED**

**Reason:**

No parameter statement was found.

**Action:**

Correct the parameter statement and resubmit your job stream.

## SYM009

### **PROTSYM HAS REACHED MAXIMUM NUMBER OF PROGRAMS**

**Reason:**

The symbolic file has exceeded the maximum number of program entries.

**Action:**

Delete some programs for your file and resubmit your job stream, or define a new PROTSYM file and then resubmit your job stream using the new file.

SYM010

**PROCESSING HAS BEGUN FOR PROGRAM NAME - XXXXXXXX**

**Reason:**

Program xxxxxxxx will be processed and its output will reside on the symbolic file.

**Action:**

None.

SYM011

**SEQUENCE NUMBERS ARE NOT IN ASCENDING SEQUENCE. JOB WILL BE TERMINATED - CONTACT CA**

**Reason:**

This is an internal verification check error.

**Action:**

Contact CA Support.

SYM012

**RECORD COUNT ERROR AT XXXXXXXX**

**Reason:**

This is an internal verification check error.

**Action:**

Contact CA Support.

SYM013

**QQQ ERROR R15 = X'YY' ERROR CODE = X'ZZ'**

**Reason:**

A VSAM request, *qqq*, has resulted in an error. The maximum number of program entries has been reached. This usually indicates a corrupted symbolic file.

**Action:**

Contact CA Support.

## SYM014

### **PROTSYM OUT OF SPACE**

**Reason:**

The symbolic file has exceeded the maximum number of records.

**Action:**

Delete some programs for your file or increase the size of your symbolic file. Then resubmit your job stream. Or, define a new PROTSYM file and then resubmit your job stream using the new file.

## SYM015

### **DD STATEMENT MISSING FOR PROTSYM**

**Reason:**

The DD statement for the symbolic file could not be found.

**Action:**

Correct the JCL and resubmit the job stream.

## SYM016

### **ENQ ERROR - CODE = X'YY'**

**Reason:**

In VSE, an error occurred when an SVC 63 (ENQ) was issued. This is normally caused by a NOT FOUND condition for the symbolic file.

**Action:**

Check the JCL and correct. If you still cannot determine the cause of this error, contact CA Support.

## SYM017

### **UTILITY IN PROGRESS ON PROTSYM FILE - JOB TERMINATED**

**Reason:**

The CA InterTest batch utility program was processing the symbolic file at the same time that the postprocessor step was running.

**Action:**

First ensure that the last UTILITY run was successful. To turn off this indicator, run a UTILITY job with a REPORT function.

## SYM018

### **MAIN STORAGE NOT AVAILABLE - INCREASE REGION SIZE**

**Reason:**

A GETMAIN (MVS) or GETVIS (VSE) request has failed due to insufficient storage.

**Action:**

Resubmit the job stream with a larger region size.

## SYM019

### **PROGRAM ABENDED 111 AT DISPLACEMENT XXXXX**

**Reason:**

A condition has occurred that required a termination with a dump.

**Action:**

Contact CA Support.

## SYM020

### **SYMBOLIC FILE UPDATED SUCCESSFULLY**

**Reason:**

The postprocessor has ended successfully and the program has been added to the symbolic file.

**Action:**

None.

## SYM021

### **XXXXXX SOURCE STATEMENTS SAVED**

**Reason:**

On a successful completion, the number of source statements, `xxxxxxx`, displays.

**Action:**

None.

## SYM022

### **YYYY TOTAL RECORDS INSERTED INTO SYMBOLIC FILE**

**Reason:**

On a successful completion, the total number of records added to the symbolic file, `yyyy`, displays.

**Action:**

None.

## SYM023

### **POST-PROCESSOR TERMINATED**

**Reason:**

The CA InterTest postprocessor program has ended.

**Action:**

None.

## SYM024

### **NPUT FILE PROCESSED**

**Reason:**

The CA InterTest postprocessor program has read all of the data passed to it in the INPUT data set.

**Action:**

None.

## SYM025

### **PROCEDURE NAMES CROSS-REFERENCE NOT FOUND**

**Reason:**

The procedure names cross-reference output area was not found.

**Action:**

Without this area, CA InterTest is unable to process any requests using a PARAGRAPH NAME. If PARAGRAPH NAMES are needed, correct the COBOL options and resubmit the job stream.

## SYM026

### **INPUT FILE IS EMPTY**

**Reason:**

The data set specified by the INPUT JCL statement was empty.

**Action:**

Correct and resubmit the job stream.

## SYM027

### **CAPEX OPTION ERROR - MLIST MUST BE SPECIFIED**

**Reason:**

The required CA Optimizer (CAPEX) option MLIST was not specified.

**Action:**

Correct and resubmit the job stream.

## SYM028

### **COBOL COMPILER OPTIONS ARE INCORRECT - XXXX - NOT FOUND**

**Reason:**

Area xxxxx could not be found in the COBOL listing. For working storage, at least one data item must be declared.

**Action:**

Correct COBOL compiler options or add a working storage data item to produce the required area and resubmit the job stream.

## SYM029

### **XXXXX NOT REQUESTED - PROCESSING TERMINATED**

**Reason:**

The required COBOL II option, xxxxx, was not specified.

**Action:**

Correct and resubmit the job stream.

## SYM030

### **NO CSECT FOUND - PLEASE REMOVE ANY PRINT NOGEN STATEMENTS THAT MIGHT PREVENT THE CSECT STATEMENT FROM BEING PRINTED**

**Reason:**

After examining the entire Assembler listing, no labeled CSECT could be found.

**Action:**

Correct and resubmit the job stream.

## SYM031

### **INPUT IS FROM COMMAND TRANSLATOR**

**Reason:**

The input passed to the CA InterTest postprocessor program was generated by the CICS command translator and not by the compiler or Assembler.

**Action:**

Correct the procedure so that the passed output is from the compiler/Assembler.

## SYM032

### **OPEN FOR INPUT FAILED**

**Reason:**

The INPUT file could not be opened. Check the printed output for additional error messages that may have been produced by the operating system.

**Action:**

Correct the JCL and resubmit the job stream.

### SYM033

#### **OPEN FOR OUTPUT FAILED**

**Reason:**

The OUTPUT file could not be opened. Check the printed output for additional error messages that may have been produced by the operating system.

**Action:**

Correct the JCL and resubmit the job stream.

### SYM034

#### **OPEN FOR CARDS FAILED**

**Reason:**

The CARDS file could not be opened. Check the printed output for additional error messages that may have been produced by the operating system.

**Action:**

Correct the JCL and resubmit the job stream.

### SYM035

#### **NO CROSS-REFERENCE FOUND - SYMBOLIC NAMES CANNOT BE USED**

**Reason:**

The Cross-Reference area could not be found in the Assembler listing. Without this area, symbolic names cannot be resolved.

**Action:**

Resubmit the job stream with the XREF (SHORT) or XREF (FULL) Assembler parameter.

### SYM036

#### **PASSED PARAMETER STATEMENTS**

**Reason:**

The next group of printed lines will be an echo of all the parameter statements read by the postprocessor.

**Action:**

None.

## SYM038

### **XXX LINK-EDITOR MAP RECORD(S) HAVE BEEN ADDED TO ENTRY**

**Reason:**

The IN25LINK program has added xxx linkage editor records to an existing symbolic entry.

**Action:**

None.

## SYM039

### **NO LINK-EDITOR ENTRY FOUND FOR XXXXXXXX**

**Reason:**

The link-name, xxxxxxxx, specified on an IN25LINK postprocessor control card could not be found in the output produced by the linkage editor.

**Action:**

You can do **one** of the following:

- Ignore the error.
- Correct the parameter card and resubmit the job stream.
- Use the CNTL Composite Support menu to add the information online. If the LISTER parameter is omitted, no listing is saved in the symbolic file.

## SYM040

### **THE FOLLOWING OPTIONS WERE NOT SPECIFIED**

**Reason:**

The list of options following this message was not specified. Without these options, some CA InterTest facilities may not function.

**Action:**

Correct the JCL and resubmit the job stream.

## SYM042

**NO STATEMENT INFORMATION WAS FOUND IN THE PASSED LISTING****Reason:**

The postprocessor program could not find the data needed to process the statement information.

- For a COBOL program, this data is produced by the CLIST or PMAP compiler option.
- For a COBOL II program, this data is produced by the OFFSET or LIST compiler option.
- For a CA Optimizer program, this data is produced by the MLIST option.
- For a CA Optimizer/II program, this data is produced by the MOFFSET option.

The following are some of the conditions that may cause this error:

- Errors in the compile which cause the suppression of the data.
- Incorrect compiler options.
- Compiler control statements that suppress the needed data.

**Action:**

Determine why the required area was suppressed. Correct and resubmit the job stream.

## SYM043

**THE CSECT NAMED XXXXXXXX WAS NOT FOUND IN THE EXTERNAL SYMBOL DICTIONARY****Reason:**

In a VSE Assembler, a CSECT statement named xxxxxxxx was found, but that name could not be found in the ESD list.

**Action:**

Correct the JCL and resubmit the job stream.

## SYM044

### **INPUT DATA WAS NOT PRODUCED BY THE LINKAGE-EDITOR**

**Reason:**

The data passed to the IN25LINK postprocessor using the INPUT JCL statement did not contain the output produced by the linkage editor step, or the linkage editor PARM=MAP is not in effect.

**Action:**

Correct the JCL and resubmit the job stream.

## SYM045

### **INVALID POWER PARAMETER FORMAT**

**Reason:**

The POWER parameter was specified incorrectly.

**Action:**

Correct the parameter card and resubmit the job stream.

## SYM046

### **INVALID POWER CLASS SPECIFIED (NOT A - Z)**

**Reason:**

The POWER LST class specified on the parameter card was not an alphabetic character.

**Action:**

Correct the parameter card and resubmit the job stream.

## SYM047

### **INVALID POWER JOB NAME**

**Reason:**

The name specified in the POWER parameter is invalid.

**Action:**

Correct the parameter card and resubmit the job stream.

## SYM048

**IN25PWRI, POWER INTERFACE MODULE, WAS NOT FOUND****Reason:**

The CA InterTest module, IN25PWRI, was not found in the load library specified in the JCL. This module is required when using the VSE/POWER LST queue.

**Action:**

You can do *one* of the following:

- Change the JCL to point to a load library that contains the IN25PWRI module.
- Change the JCL to use SYSLST instead of POWER.

## SYM049

**IN25OPTS MODULE NOT FOUND - DEFAULTS ARE USED****Reason:**

Module IN25OPTS was not found in the load library specified in the JCL.

**Action:**

If the default POWER options can be used, no action is required. However, we recommend that the correct IN25OPTS module be added to the load library.

## SYM050

**POWER INTERFACE IS NOT ACTIVE****Reason:**

The POWER parameter was specified incorrectly.

**Action:**

Correct the parameter card and resubmit the job stream.

## SYM051

**SYNTAX ERROR IN WH= OPTION****Reason:**

A syntax error was found in the CA Realia/II Workbench Host Option parameter.

**Action:**

Correct the parameter card and resubmit the job stream.

## SYM052

### **WH= SOURCE FILE OPTION IS INCORRECT**

**Reason:**

An error was found in the CA Realia/II Workbench Host Option parameter.

**Action:**

Correct the parameter card and resubmit the job stream.

## SYM053

### **WH= MEMBER NAME IS MISSING OR INCORRECT**

**Reason:**

An error was found in the CA Realia/II Workbench Host Option parameter.

**Action:**

Correct the parameter and resubmit the job stream.

## SYM054

### **REALIA WORKBENCH HOST OPTION WAS REQUESTED WITHOUT HAVING A LISTER OPTION SPECIFIED**

**Reason:**

The LISTER option was not specified in the CA Realia/II Workbench Host Option parameter.

**Action:**

The LISTER=ALL option is set by default.

## SYM055

### **REALIA WORKBENCH HOST OPTION INTERFACE MODULE WAS NOT LINKED WITH THIS MODULE**

**Reason:**

The CA Realia/II Workbench Host Option Interface Module was not linked.

**Action:**

Correct and resubmit the job.

SYM056

**A CA LMP RIMSTAT ERROR HAS BEEN DETECTED**

**Reason:**

The CA License Management Program is not properly installed.

**Action:**

Ensure that you have the proper level of CA Common Services for z/OS installed.

SYM057

**CSECT NAME 'XXXXXXXX' IS GT 8 BYTES. CSECT IGNORED**

**Reason:**

CSECT name is greater than 8 bytes.

**Action:**

Correct and resubmit the job.

SYM058

**HLASM OPTION "LIST(133|MAX)" IS NOT SUPPORTED. USE OPTION "LIST(121)".**

**Reason:**

HLASM option LIST(133|MAX) is not supported.

**Action:**

Correct the option by using LIST(121).

SYM059

**HLASM OPTION "NOTHREAD" IS NOT SUPPORTED. USE OPTION "THREAD".**

**Reason:**

The NOTHREAD option is not supported.

**Action:**

Correct the option by using the THREAD option (IBM default).

SYM070

**JOBNAME=jobname, USER=userid, SYMBOLIC FILE XXX.XXXX.XXXX.XXXX IS XX% FULL.**

**Reason:**

The message informs you that the user specified limit for used space in the symbolic file was reached.

**Action:**

None.

SYM090

**ATTEMPT TO UPDATE SAM RECORD VIA DATA RPL**

SYM091

**ATTEMPT TO UPDATE DATA RECORD VIA SAM RPL**

SYM092

**ATTEMPT TO UPDATE DIRECTORY RECORD VIA DATA RPL**

SYM093

**ATTEMPT TO UPDATE DATA RECORD VIA DIRECTORY RPL**

SYM094

**NO ENQ IS SET FOR A XXXXXX**

SYM095

**DIRECTORY RECORD IS CORRUPTED**

SYM097

**MISMATCH ON AVAILABLE FREE RECORDS IN ONE SAM**

SYM099

**MAXPGMVER WAS REACHED - OLDEST VERSION HAS BEEN DELETED TO PROCESS CURRENT REQUEST.**

## SYM Messages 2-11

### Symbolic Post-Processor Program Messages

#### SYM960

**MAX SAM RECS EXCEEDED. PROTSYM FILE MAY BE CORRUPTED**

#### SYM961

**MAX DIR RECS EXCEEDED. PROTSYM FILE MAY BE CORRUPTED**

**Reason:**

Error messages SYM090 to SYM097, and SYM960 to SYM961 are produced by a special checkout procedure.

This procedure looks for conditions that corrupt the symbolic file. If any of the conditions are found, one of the above messages is issued, and the batch processor program abends.

**Action:**

For assistance in handling these errors, contact CA Support.

#### SYMP001I

**\*\*\*\* INTERTEST VERSION ID: x.x COMPILED: dd mm yy hh:mm:ss**

**Reason:**

This reason is informative. It identifies the version and compile date and time for the PL/I postprocessor program, IN25SYMP.

**Action:**

None.

#### SYMP002I

**INTERTEST - PL/I POSTCOMPILER RUN FOR PROGRAM: progname**

**Reason:**

This reason is informative during initialization of IN25SYMP. Processing for the requested program has begun.

**Action:**

None.

### SYMP003I

**LISTER RECORDS ADDED TO PROTSYM FILE: nn**

**Reason:**

This reason is informative during termination of IN25SYMP. The number of records used on the PROTSYM file for listing information displays.

**Action:**

None.

### SYMP004I

**SYMBOLIC RECORDS ADDED TO PROTSYM FILE: nn**

**Reason:**

This reason is informative during termination of IN25SYMP. The number of records used on the PROTSYM file for symbolic information displays.

**Action:**

None.

### SYMP005I

**IN25ASMP RETURN CODE ON FINAL PROCESSING: nn**

**Reason:**

This reason is informative. The final return code from routine IN25ASMP displays.

**Action:**

None.

### SYMP006I

**IN25SYMP RETURN CODE ON FINAL PROCESSING: nn**

**Reason:**

This reason is informative. The final return code from routine IN25SYMP displays.

**Action:**

None.

## SYMP101W

**BLOCK NAME CANNOT BE RESOLVED. VARIABLE AND PARAMETER RESOLUTION MAY BE AFFECTED. DRC=n BLOCK NAME= blockname**

**Reason:**

A variable was found in the variable storage map section of the compiler output whose associated block cannot be identified.

**Action:**

Contact CA Support with program listings.

## SYMP102W

**VARIABLE DISPLACEMENT CANNOT BE DETERMINED. DRC=n, VARIABLE NAME= variable name**

**Reason:**

A variable was found in the variable storage map section of the compiler output whose associated attributes could not be identified.

**Action:**

Make sure all data names are unique within each block.

## SYMP103W

**PARAMETER DISPLACEMENT CANNOT BE DETERMINED. DRC=n, PARAMETER NAME= parameter name**

**Reason:**

A parameter passed to a procedure could not be resolved and will not be available to the CORE transaction, or an associated block could not be determined.

**Action:**

Make sure all data names are unique within each block and that no procedure or entry statements are suppressed by %NOPRINT. Check for other error messages.

## SYMP104W

**BASED/DEFINED VAR PTR/BASE CANNOT BE FOUND. DRC=n, VARIABLE NAME=  
variable name POINTER NAME = pointer name**

**Reason:**

The pointer associated with a BASED variable or the base variable of a redefined variable (see message SYMP115W) could not be resolved. The pointer name can be the name of the associated pointer or the base area for the redefinition.

**Action:**

Try simplifying the expression of the base area. For example, use the following syntax to declare a redefined variable:

```
...BASED( ADDR( variable) )
```

or

```
...DEFINED base_variable...
```

Also, make sure the variable does not refer to a subscripted array element or qualified name.

## SYMP105W

**ADDRESSES OF THE FOLLOWING BASED VARIABLES CANNOT BE DETERMINED FROM  
THE PL/I CROSS REFERENCE. IN ORDER TO ACCESS THESE VARIABLES ON-LINE, YOU  
MUST SPECIFY A QUALIFIED NAME IN THE INTERTEST CORE COMMAND.**

**Reason:**

One or more BASED (\*) variables were found in the PL/I cross reference. IN25SYMP was unable to determine the pointer to the variables specified.

**Action:**

This reason is informative only. When attempting to view the variable online with CA InterTest for CICS, you must use the POINTER option in the CORE command.

## SYMP106W

**ADDRESSES OF THE BASED STRUCTURES CONTAINING THE FOLLOWING VARIABLES COULD NOT BE DETERMINED. IN ORDER TO ACCESS THESE VARIABLES ON-LINE, YOU MUST SPECIFY A QUALIFIED NAME IN THE INTERTEST CORE COMMAND.**

**Reason:**

A SYMP105W message was issued for the major structure containing the variable names.

**Action:**

This reason is informative only. When attempting to view the variable online with CA InterTest for CICS, you must use the POINTER option in the CORE command.

## SYMP107W

**THE FOLLOWING PL/I COMPILER OPTION IS REQUIRED IN ORDER FOR IN25SYMP TO PROCESS CORRECTLY compiler option.**

**Reason:**

The listed PL/I compiler option was not specified.

**Action:**

Be sure that the following options were specified to the PL/I compiler:

AGGREGATE	OPTIONS
ATTRIBUTES(FULL)	SOURCE
MAP	STMT or GOSTMT
NEST	STORAGE
OFFSET	XREF(FULL)

If all of the previous options were not specified, code the appropriate options and rerun the job.

If all of the previous options were specified, ensure that the options section is included in the PL/I compiler listing and that the output of the compiler was directed to the INPUTT DD statement, or that the compiler terminated with a return code of 8 or less.

## SYMP108W

**\*\*\* WARNING: "%NOPRINT" OPTION SPECIFIED. \*\*\***

**Reason:**

The NOPRINT option was specified on the control card. This option suppresses checking for the occurrence of the preprocessor control statement %NOPRINT. If the use of this facility suppresses the listing of PROCEDURE or ENTRY statements that contain parameter lists, or suppresses the listing of the final END statement of the program, the results may be unpredictable. Possible effects include the inability to resolve parameter variables properly, as well as possible abnormal termination of SYMP.

**Action:**

Remove the NOPRINT option or ensure required information is not suppressed.

**Note:** Indiscriminate use of this option could cause program failure or incorrect results.

## SYMP110W

**STRUCTURE NAME "IN" ENCOUNTERED WHILE SCANNING CROSS  
REFERENCE/ATTRIBUTE LIST VARIABLE: variable name STATEMENT NO: statement  
number**

**Reason:**

While resolving structure nesting information, the identified variable in the specified statement number was found in a major or minor structure named IN. If this is not true, the variable may not be properly resolved.

**Action:**

None, if the previous condition described is correct. Otherwise, contact CA Support.

## SYMP111W

**UNABLE TO DETERMINE LENGTH OF DATA ITEM. "REFER" OPTION NOT SUPPORTED  
FOR BASED VARIABLES. VARIABLE: variable name STATEMENT NO: statement number**

**Reason:**

Dynamically sized items are not supported. Examples include string parameters that inherit their size from the calling block, automatic strings whose length is an expression, and based strings whose length is specified by the REFER option. Such variables may not be available to the CORE transaction when debugging.

**Action:**

None.

## SYMP112W

**UNEXPECTED CONVERSION ERROR WHILE PROCESSING THE CROSS REFERENCE/ATTRIBUTE LIST FOR: VARIABLE: variable name STATEMENT NO: statement number**

**Reason:**

An unanticipated error occurred during processing of the attribute list.

**Action:**

Contact CA Support.

## SYMP113W

**LABEL DISPLACEMENT CANNOT BE DETERMINED FOR: xxxxxxxx**

**Reason:**

The indicated label could not be associated with its block.

**Action:**

Make sure label names are unique. Check the statement/offset table for missing or out-of-order entries. Do not use END *block-name* statements to close multiple blocks.

## SYMP114W

**NO STORAGE WILL BE ALLOCATED FOR THE FOLLOWING VARIABLES. THE VARIABLES CANNOT BE ACCESSED.**

List of variables

**Reason**

The PL/I compiler has not allocated storage for these variables. This is normally the result of the variables not being referenced or their values never being used.

**Action**

Informational only. No action is necessary.

## SYMP115W

**THE FOLLOWING LINE CONTAINS "%NOPRINT" WHICH COULD PREVENT PROPER RESOLUTION OF SOME VARIABLES.**

input compiler record

**Reason:**

Use of the compiler option %NOPRINT may cause the suppression of information needed to resolve variables properly.

**Action:**

Make sure %NOPRINT does not suppress the printing of:

- PROCEDURE or ENTRY statements containing parameter lists.
- Declarations of redefined variables using expressions, such as:

```
...BASED( ADDR( variable ) )  
...DEFINED base_variable...
```

## SYMP116W

**THE FOLLOWING "DEFINED" STRUCTURE IS NESTED TOO DEEPLY TO PROPERLY RESOLVE ITS LENGTH: structure**

**Reason:**

This error occurs only with a structure nesting depth that exceeds 16, which is not currently allowed by any version of the PL/I compiler.

**Action:**

None.

## SYMP117W

**LENGTH OF DEFINED STRUCTURE "structure" CANNOT BE RESOLVED DUE TO CONTAINED ARRAY "array"**

**Reason:**

When a CORE command displays the specified DEFINED structure containing an array or a substructure that contains an array, the area displayed is correct, but it is limited to the correct length. This error occurs only with a structure nesting depth that exceeds 16, which is not currently allowed by any version of the PL/I compiler.

**Action:**

None.

## SYMP118W

**VARIABLE "element name" IS A DUPLICATE NAME WITHIN A STRUCTURE. STRUCTURE, "structure name", IS DECLARED IN STATEMENT statement number DRC = n.**

**Reason:**

A duplicate name was found in a structure. All names must be unique within a major structure. If not, the following problems can occur:

- Selection of an incorrect variable
- Incorrect attributes for a variable
- Incorrect resolution of parameters
- System errors not apparently related to these variables

**Action:**

Assign unique names.

## SYMP119W

**NO AUTOMATIC VARIABLES FOUND FOR PROCEDURE procname PARAMETER parameter CANNOT BE RESOLVED DRC = n.**

**Reason:**

No AUTOMATIC variables were declared for the specified procedure. Parameters cannot be resolved for any PL/I procedure unless AUTOMATIC variables are declared in it.

**Action:**

You can circumvent this restriction by declaring an AUTOMATIC variable. This variable does not have to be referenced.

## SYMP120W

**STRUCTURE INFORMATION FOR: variable-name IS INVALID. SPECIFY CONNECT ATTRIBUTE, OTHERWISE ONLINE STRUCTURE REQUEST WILL SHOW INVALID INFORMATION. STATEMENT #: nnn**

**Reason:**

The CONNECT attribute is missing from the named variable, found in the specified statement number. When the CONNECT attribute is missing, CA InterTest and CA SymDump cannot properly format the variable.

**Action:**

Redefine the variable with the CONNECT attribute.

## SYMP121W

**COMPILER EXTERNAL SYMBOL DICTIONARY NOT AVAILABLE. ADDRESSES OF THE FOLLOWING CONTROLLED VARIABLES CANNOT BE DETERMINED.**

List of variable names

**Reason:**

The External Symbol Dictionary is not in the compiler listings. As a result it is not possible to determine the address of controlled variables. Therefore they cannot be displayed.

**Action:**

Informational only. If you desire to display controlled variables, recompile with the ESD option.

## SYMP122W

**THE FOLLOWING VARIABLES CAN ONLY BE ACCESSED THROUGH CA INTERTEST BATCH.**

List of variables

**Reason:**

The information required to locate these variables is not available in a CICS environment.

**Action:**

Informational only. These variables cannot be displayed by CA InterTest.

## SYMP123W

**THE FOLLOWING EXTERNAL VARIABLES CANNOT BE ACCESSED THROUGH CA INTERTEST BATCH DUE TO THE RENT OPTION.**

**Reason:**

The information necessary to locate external variables for reentrant compiled programs is not available and therefore cannot be displayed.

**Action:**

Informational only. No action is necessary.

## SYMP124W

### **THE POINTER FOR A BASED ADDR VARIABLE CAN NOT HAVE MORE THAN 3 SUBSCRIPTS**

VARIABLE NAME = *variable\_name*

#### **Reason:**

CA InterTest for CICS and CA InterTest Batch do not support variables with more than three subscripts.

#### **Action:**

Informational only. These variables cannot be displayed.

## SYMP125W

### **CURRENTLY, THE FOLLOWING VARIABLES CAN NOT BE PROPERLY DISPLAYED BY INTERTEST/CICS and INTERTEST BATCH.**

List of variables

#### **Reason:**

CA InterTest for CICS and CA InterTest Batch cannot support variables with BASED ADDRESS variables with subscripts.

#### **Action:**

Informational only. These variables cannot be displayed.

## SYMP126W

### **THE FOLLOWING VARIABLES RESIDE WITHIN AN UNNAMED STRUCTURE AND MAY NOT BE QUALIFIED**

List of variables

#### **Reason:**

The indicated variables are defined within a structure that was defined with a name of '\*'. Since the variable name '\*' cannot be referenced, the structure name cannot be used as qualifier.

#### **Action:**

Informational only. If the variable names indicated are not unique, the variables may not be displayable by the CA Application Quality and Testing Tools.

## SYMP182W

**UNABLE TO OBTAIN TIMESTAMP INFORMATION FROM LISTING, CURRENT DATE/TIME WILL BE USED. PARAMETER parameter CANNOT BE RESOLVED DRC = n.**

**Reason:**

The compiler generated timestamp cannot be found in the SYSPRINT listing used as input. The date and time of the postprocessor's execution is used in place of the compiler timestamp.

**Action:**

Contact CA Support.

**Note:** For messages SYMP500 to SYMP599, you are advised to contact CA Support. Provide the message number, text, and DRC code (if available). Also provide the IN25SYMP version ID and compile date and time (see message SYMP001I) and the release number of the PL/I compiler you are using.

## SYMP500E

**ERROR SCANNING SOURCE FOR COMMENTS/LITERALS STATEMENT NUMBER:  
statement number COMMENT/LITERAL SCAN FLAGS: xxxxxxxx**

**Reason:**

An error occurred while scanning for comments and literals. If comments or literals contain text that resembles a PROCEDURE or ENTRY statement with parameters, some parameter variables may not be properly resolved.

**Action:**

Make sure comments and literals do not contain text as previously described. Check message SYMP103W. Contact CA Support if this error occurs.

## SYMP501E

**UNABLE TO DETERMINE BEGINNING STATEMENT NUMBER FOR BLOCK. ANY VARIABLES DECLARED IN THIS BLOCK PRIOR TO THE INDICATED STATEMENT NUMBER WILL NOT BE RESOLVED. xxxxxxxx AT STATEMENT:statement number**

**Reason:**

An error occurred while identifying the beginning statement number for a block. Variables declared between the beginning of the block and the statement number may not be properly resolved.

**Action:**

Place an executable statement before the first variable declaration in this block. Contact CA Support if this error occurs.

## SYMP502E

**EXPECTED "IN..." NOT FOUND WHILE SCANNING CROSS REFERENCE/ATTRIBUTE LIST VARIABLE variable STATEMENT NO: statement number**

**Reason:**

An error occurred while resolving structure nesting. Structure elements may not be properly resolved.

**Action:**

Contact CA Support.

## SYMP503E

**WARNING - THE FOLLOWING LINE ASSUMED TO BE PART OF COMPILER INFORMATORY MESSAGE AND IGNORED:**

input compiler record DRC = n

**Reason:**

The specified compiler input record was ignored.

**Action:**

Contact CA Support.

## SYMP503E

**WARNING - THE FOLLOWING LINE ASSUMED TO BE A REPETITION OF VARIABLE MAP COLUMN HEADINGS:**

input compiler record DRC = n

**Reason:**

The specified compiler input record was assumed to repeat variable map column headings.

**Action:**

Contact CA Support.

## SYMP503E

**WARNING - THE FOLLOWING LINE ASSUMED TO IDENTIFY COMPILER DIAGNOSTIC MESSAGES SECTION:**

input compiler record DRC = n

**Reason:**

The specified compiler input record was assumed to identify the compiler's diagnostic messages section.

**Action:**

Contact CA Support.

## SYMP503E

**WARNING - THE FOLLOWING LINE CONTAINS TITLE IN UNEXPECTED POSITION - ASSUMED TO LIST STATEMENT OFFSETS:**

input compiler record DRC = n

**Reason:**

The specified compiler input record contains a title in an unexpected position. This line is assumed to list statement offsets.

**Action:**

Contact CA Support.

## SYMP503E

**WARNING - THE FOLLOWING LINE CONTAINS UNEXPECTED DECIMAL OFFSET - HEX VALUE WILL BE USED:**

input compiler record DRC = n

**Reason:**

The specified compiler input record contains a decimal offset. The hexadecimal value will be used instead.

**Action:**

Contact CA Support.

## SYMP504E

**UNEXPECTED STRUCTURE NESTING DEPTH OF n EXCEEDS PREVIOUS COMPILER LIMIT IN STATEMENT `statement number`**

**Reason:**

The nesting depth exceeds the limit in the specified compiler statement.

**Action:**

Contact CA Support.

## SYMP505E

**BLOCK NOT FOUND FOR VARIABLE `variable`, DECLARED IN STATEMENT NO. `nn`**

**Reason:**

The block for the specified variable could not be found.

**Action:**

Contact CA Support.

## SYMP507E

**STATEMENT OUT OF EXPECTED RANGE FOR BLOCK `block name`**

**Reason:**

The statement was out of the expected range for the specified block.

**Action:**

Contact CA Support.

## SYMP508E

**SEARCH FAILED FOR: variable DRC = n**

**Reason:**

The specified variable could not be found.

**Action:**

Contact CA Support.

## SYMP509E

**INCLUDE OF USER FILES THROUGH INTEGRATED PREPROCESSOR NOT SUPPORTED.  
USE SEPARATE PREPROCESSOR STEP**

**Reason:**

The integrated INCLUDE and MACRO preprocessors of PL/I for z/OS are not supported. If you are using the integrated SQL preprocessor, programs that contain EXEC SQL INCLUDE statements for user-defined members still require a separate preprocessor step. (EXEC SQL INCLUDE statements for SQLCA and SQLDA are supported when using the integrated SQL preprocessor.)

**Action:**

Use a separate preprocessor step to incorporate external files into your program.

## SYMP599E

**UNEXPECTED CHAR IN MARGIN DELIMITER POSITION M, L, MACRO, MRGCHR: aaa,  
bbb, ccc, ddd DRC = n.**

**Reason:**

An unexpected character was found in the margin delimiter position.

**Action:**

Contact CA Support.

SYMP599E

**"aaaa" POSITIONED AT BLANK STRING: "portion of listing line" DRC = n.**

**Reason:**

*aaaa* was positioned at a blank.

**Action:**

Contact CA Support.

SYMP599E

**"IN" FOUND AT INVALID LOCATION STRING: "portion of listing line" DRC = n.**

**Reason:**

An IN structure was found at an invalid location.

**Action:**

Contact CA Support.

SYMP599E

**VARIABLE "variable", DECLARED IN STATEMENT statement number, IS ALREADY RESOLVED DRC = n.**

**Reason:**

The specified variable is already resolved.

**Action:**

Contact CA Support.

SYMP599E

**AGGREGATE NAME NOT MATCHED aggregate name DRC = n.**

**Reason:**

The specified aggregate name was not found.

**Action:**

Contact CA Support.

## SYMP599E

### **FORWARD SCAN FAILED TO RESOLVE BLOCK OUTERMOST BLOCK ASSUMED DRC = n.**

**Reason:**

The block could not be resolved. The outermost block is assumed.

**Action:**

Contact CA Support.

## SYMP599E

### **STRUCTURE PROCESSING ERROR variable name**

**Reason:**

An error has occurred in recording a variables structure position while processing the aggregate table.

**Action:**

This can occur if the PL/I compile abnormally terminates or terminates with a return code greater than eight. Check these conditions and if they occur, correct them and rerun the job. If neither has occurred, contact CA Support with the complete job output.

## SYMP599E

### **STORAGE DESCRIPTOR NAME NOT MATCHED variable name**

**Reason:**

A variable name in the storage offset table could not be matched.

**Action:**

This can occur if the PL/I compile abnormally terminates or terminates with a return code greater than eight. Check these conditions and if they occur, correct them and rerun the job. If neither has occurred, contact CA Support with the complete job output.

## SYMP801E

**nn STATEMENTS ENCOUNTERED; PROGRAMS WITH MORE THAN 10,000 STATEMENTS NOT SUPPORTED. RESULTS WILL BE UNPREDICTABLE, WITH SEVERE ERRORS LIKELY.**

**Reason:**

Because of a bug in the PL/I compiler that truncates high order digits from statement numbers in the statement/offset table, programs with over 9,999 statements cannot be supported completely. This message is usually accompanied by other error messages. Online debugging will be affected significantly.

**Action:**

None.

## SYMP901S

**THE PL/1 COMPILER OPTIONS LISTED PREVIOUSLY WERE NOT SPECIFIED AND HAVE CAUSED IN25SYMP TO TERMINATE**

**Reason:**

One or more SYMP107W messages were issued.

**Action:**

Ensure that the following options were specified to the PL/I compiler:

AGGREGATE	OPTIONS
ATTRIBUTES(FULL)	SOURCE
MAP	STMT or GOSTMT
NEST	STORAGE
OFFSET	XREF(FULL)

See the SYMP107W messages for the specific options missing.

If all options were not specified, code the appropriate options and rerun the job.

If all of the previous options have been specified, ensure that the options section is included in the PL/I compiler listing and that the output of the compiler was directed to the INPUTT DD statement, or that the compiler terminated with a return code of 8 or less.

## SYMP902S

**UNEXPECTED TERMINATION OF COMPILER OUTPUT HAS OCCURRED DRC = n.**

**Reason:**

While scanning the PL/I compiler output, an end-of-file condition was raised for the INPUTT DD statement.

**Action:**

Check that all the PL/I options required by IN25SYMP were set, or that the compiler terminated with a return code of 8 or less. Correct the problem and rerun the compile and IN25SYMP.

## SYMP903S

**UNEXPECTED ERROR DETECTED. ERROR CORE=nnnn DRC = n.**

**Reason:**

A PL/I error condition occurred that IN25SYMP was not designed to handle.

**Action:**

Check the PL/I ONCODEs and take the appropriate suggested action. If unsuccessful, contact CA Support with the dump.

## SYMP904S

**IN25ASMP FUNCTION FAILED. FUNCTION CODE= n DRC = n.**

**Reason:**

The routine that does I/O to the PROTSYM file returned with a non-zero return code.

**Action:**

Check the error messages from IN25ASMP and take appropriate action, and then rerun the job. This error usually indicates a problem with the PROTSYM file. If this is the first use of the PROTSYM file, check the job that initialized the file for normal completion. If this is not the first use of the file, check for a physical or logical error on the file. The MESSAGE DD statement contains more information.

**Note:** Function code 8 usually means the file is full.

SYMP905S

**ERROR ENCOUNTERED ON FILE INPUTT, ERROR CODE = nnnn DRC = n.**

**Reason:**

An error has occurred trying to open the INPUTT file.

**Action:**

Ensure that the ddname DLBL INPUTT points to a file that contains the output listing of the PL/I compiler.

SYMP906S

**ERROR ENCOUNTERED ON FILE SYSPRINT, ERROR CODE = nnnn DRC = n.**

**Reason:**

An error has occurred attempting to open the SYSPRINT file.

**Action:**

Ensure that the ddname DLBL SYSPRINT is coded in your JCL.

SYMP908S

**SUBSCRIPT OVERFLOW IN TABLE T4 DRC = n.**

**Reason:**

The internal table used to keep track of variable information has exceeded its limits. This error is usually caused when the Attribute and Cross Reference section of the compile output could not be found by IN25SYMP.

**Action:**

This can occur if the compiler options ATTRIBUTE(FULL) and XREF(FULL) were not specified, or if the PL/I compile abnormally terminates or terminates with a return code greater than 8. Check for these conditions and if they occur, correct and rerun the job. If neither has occurred, contact CA Support with the dump.

## SYMP909S

### **SUBSCRIPT OVERFLOW IN TABLE T5 DRC = n.**

#### **Reason:**

The internal table used to keep track of PROC BLOCKS has exceeded its limits.

This error is usually caused when the Storage Requirements section of the compile output could not be found by IN25SYMP. This can occur if the compiler option STORAGE was not specified, or if the PL/I compile has abnormally terminated or terminated with a return code greater than 8.

#### **Action:**

Check for these conditions and if they occur, correct and rerun the job. If neither has occurred, contact CA Support with the dump.

## SYMP910S

### **SUBSCRIPT OVERFLOW IN TABLE T6 DRC = n.**

#### **Reason:**

An internal table used to keep track of information about statements has overflowed.

#### **Action:**

This occurs under several conditions. If reorder has been specified in the procedure block, remove the reorder option.

This can also occur if many source statement lines contain multiple PL/I statements (for example, A=B; C=D; E=F;). In this case, separate the PL/I statements into multiple source lines.

This can also occur if the PL/I preprocessor command %NOPRINT was specified. In this case, remove the %NOPRINT command.

## SYMP911S

**SUBSCRIPT OVERFLOW IN TABLE T6A DRC = n.****Reason:**

An internal table used to keep track of information about statements has overflowed.

**Action:**

This occurs under several conditions. If reorder has been specified in the procedure block, remove the reorder option.

This can also occur if a large number of source statement lines contain multiple PL/I statements (for example, A=B; C=D; E=F;). In this case, separate the PL/I statements into multiple source lines.

This can also occur if the PL/I preprocessor command %NOPRINT was specified. In this case, remove the %NOPRINT command.

## SYMP912S

**INPUT FROM THE PL/I COMPILER CONTAINS AN INVALID STATEMENT NUMBER IN COLUMNS 1-8 OF THE RECORD.****Reason:**

An error was detected while attempting to find the largest PL/I statement number.

**Action:**

Check compiler output and the line listed. Correct the problem and rerun the job.

## SYMP916S

**UNEXPECTED ERROR ENCOUNTERED DURING PHASE 1 DRC = n.****Reason:**

An error has occurred during phase 1 of IN25SYMP processing.

**Action:**

Check the job log for operating system or PL/I error indicators. Correct and rerun the job.

## SYMP917S

**DOS INITIALIZATION FAILED IN "ASMP"; POST-PROCESSOR SYMP WILL BE TERMINATED DRC = n.**

**Reason:**

For VSE only. Usually, a control card is missing or invalid. Or, there may be a problem with the symbolic file or with the JCL for the MESSAGE file.

**Action:**

Correct the control card, symbolic file, or JCL.

## SYMP919S

**END OF FILE ENCOUNTERED FOR "INPUTT" DURING PHASE 1 OF PRE-PROCESSOR DRC = n.**

**Reason:**

An end-of-file condition occurred during the phase 1 scan of the PL/I compiler output.

IN25SYMP prints the compiler output and terminates processing. This condition can occur when the PL/I compiler detects program errors that would prohibit successful compilation.

**Action:**

Refer to the PL/I compiler output for error messages.

## SYMP920S

**"CDLOAD" FAILED FOR "IN25ASMP". RETURN CODE = nnnn**

**Reason:**

VSE only. The VSAM I/O routine, IN25ASMP, could not be dynamically loaded. Possible causes include incorrect installation or partition JCL that does not allow sufficient storage for loading this phase.

**Action:**

Check that the specified phase is in the execution phase library and that there is adequate storage.

## SYMP921S

**POWER SPOOL RETRIEVAL FAILURE: ATTEMPT NUMBER: request****Reason:**

For VSE/POWER only. A POWER spool retrieval failed. This message identifies the request. If only one job gets this error, the JCL for the job is probably incorrect. If all jobs get this error, the product may not have been properly installed and customized.

**Action:**

Check the JCL and, if necessary, the installation and customization.

## SYMP922S

**INCOMPLETE COMPILER OUTPUT DUE TO ERRORS HAS CAUSED TERMINATION OF IN25SYMP OPTION CAUSING PL/1 COMPILER TERMINATION WAS: option****Reason:**

The PL/I compiler options NOSYNTAX and NOCOMPILE can prevent the normal completion of the compilation process, either conditionally, depending on the severity of the errors, or unconditionally. IN25SYMP terminates immediately when it recognizes an aborted compilation.

**Action:**

Usually, correction of compilation errors resolves this problem.

## SYMP923S

**TABLE SIZE EXCEEDS HALFWORD LIMIT FOR: name****Reason:**

An internal table has exceeded the limit of the halfword index. The postprocessor program terminated to prevent subsequent errors. This situation should not occur for programs with significantly less than 32,767 statements. Because support is limited to programs with less than 10,000 statements, this situation is unlikely to occur.

**Action:**

Contact CA Support.

## SYMP924S

### **SUBSCRIPT OVERFLOW IN TABLE T7**

**Reason:**

The internal table used to keep track of variable displacements has exceeded its limits.

**Action:**

This can occur if the PL/I compile abnormally terminates or terminates with a return code greater than eight. Check these conditions and if they occur, correct them and rerun the job. If neither has occurred, contact CA Support with the complete job output.

## SYMP925S

### **SUBSCRIPT OVERFLOW IN TABLE T10**

**Reason:**

The internal table used to keep track of the pseudo register information for controlled variables has exceeded its limits.

**Action:**

This error is usually caused when the Attribute and Cross Reference section of the compile output could not be found by IN25SYMP.

This can occur if the compiler options ATTRIBUTE(FULL) and XREF(FULL) were not specified, or the if PL/I compile abnormally terminated or terminates with a return code greater than eight. Check these conditions and if they occur, correct and rerun the job. If neither has occurred, contact CA Support with the complete job output.

## SYMP926S

### **SUBSCRIPT OVERFLOW IN TABLE T11**

**Reason:**

The internal table used to keep track of external symbol dictionary entries has exceeded its limits.

**Action:**

This can occur if the compiler option ESD was not specified, or the PL/I compiler abnormally terminated or terminates with a return code greater than eight. Check these conditions and if they occur, correct and rerun. If neither has occurred, contact CA Support with the complete job output.

## SYMP999S

### **UNEXPECTED ERROR CODE. nnn PROCESSING TERMINATED**

**Reason:**

An undocumented error code has forced termination of IN25SYMP.

**Action:**

Contact CA Support.

## CAIN5990I

### **ALLOCATION OF LOG FILE FAILED. LOGGING DISABLED.**

**Reason:**

This message is issued by IN25FSYM, indicating that dynamic allocation for SRVPRINT DD has failed. Logging activities is disabled. This message is usually followed by IBM IKJ5635 message providing the dynamic allocation text unit that failed.

**Action:**

Determine and correct the cause for failure then retry the action.

## CAIN5991W

### **HHMM DOES NOT MATCH.**

**Reason:**

This message is issued by IN25FSYM. The hour and minute of the timestamp found in the symbolic does not match the timestamp provided by the caller for the same symbolic. Requested action is not performed.

**Action:**

Provide the correct timestamp value and try the action again.

## CAIN5995E

### **NO PROTSYM SEARCH LIST PROVIDED.**

#### **Reason:**

This message is issued by IN25FSYM. User did not provide one or more PROTSYM data set names to perform symbolic search. Requested action is not performed.

#### **Action:**

Provide at least one or up to a maximum of eight PROTSYM fully qualified data set names to be used for symbolic search.

## CAIN6000E

### **DYNAMIC UNALLOCATION FAILED FOR nnnnnnnn. RC= rr. RSN= ssssssss.**

#### **Reason:**

This message is issued by IN25FSYM. Dynamic allocation of data set with nnnnnnnn DD name has failed. Return code from Dynamic Allocation is rr and the reason code is ssssssss.

#### **Action:**

Use the return code and reason code to determine the cause of the failure. Correct the error and retry the action.

## CAIN6000W

### **DYNAMIC UNALLOCATION FAILED FOR dddddddd RC=rr. RSN=sssssss.**

#### **Reason:**

This message is issued by IN25FSYM. Dynamic unallocation of dddddddd DD name has failed. The Dynamic Unallocation return code is rr and reason code is ssssssss.

#### **Action:**

Use the return code and reason code to determine the cause of the failure. Correct the error and retry the action. If the error persists contact CA Support.

## CAIN6010W

**LOAD OF pppppppp FAILED. RC= rr.**

**Reason:**

This message is issued by IN25FSYM. Loading of program named pppppppp has failed. The return code is rr.

**Action:**

Make sure that the data set containing the pppppppp program is in the LINKLIST or defined in the STEPLIB DD.

## CAIN6020W

**FAILED IN ROUTINE: rrrrrrrrr RC= rr.**

**Reason:**

This message is issued by IN25FSYM. Routine named rrrrrrrr has failed with a return code of rr. This message is usually associated with IN25SAPI and rrrrrrrr is the failed SAPI function.

**Action:**

Determine the error and retry the request.

## CAIN6070E

**CRITICAL ERROR LD@DSSDSN INVALID VALUE.**

**Reason:**

This message is issued by IN25FSYM. The data set name provided in LD@DSSDSN is invalid.

**Action:**

LD@DSSDSN should contain a valid DD name to be used for DSS logging. It is usually specified as DSSLOG. Correct the DD name and retry the action.

## CAIN5990I

### **LINK TO IN25SPOL FAILED.**

#### **Reason:**

This message is issued by IN25NSRV. LINK SVC for IN25SPOL has failed. Message extraction will not be performed.

#### **Action:**

Make sure that the data set containing IN25SPOL is either defined in the LINKLIST or properly defined in the STEPLIB DD.

## CAIN5980E

### **CA SCM CRITICAL ERROR. ERROR CODE: rrrr. REQUEST FOR mmmmmmmm NOT SERVICED.**

#### **Reason:**

This message is issued by IN25NSRV. This indicated that CA SCM Endeavor for mainframe encountered a critical error. The error code is rrrr. Symbolic request for element named mmmmmmmm is not serviced.

#### **Action:**

Use the rrrr error code in conjunction with the SRVPRINT log and DSSLOG to determine the cause, correct the error and redo the request.

## CAIN5900I

### **mm/dd/yyyy hh:mm:ss IN25NDVR STARTED FOR PRGNNAME – pppppppp.**

#### **Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the Listing Server is retrieving the symbolic for program named pppppppp. This message is used to serve as a beginning bookmark for message extraction. All messages issued after this message is extracted by message extraction service.

#### **Action:**

None.

## CAIN5903E

**mm/dd/yyyy hh:mm:ss IN25NSRV CCI SPNARM FAILED.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN25NSRV issued a CCI SPNARM request. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5903E

**mm/dd/yyyy hh:mm:ss IN25NSRV CCI INIT FAILED.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. CCI INIT action has failed. This error occurred when IN25NSRV issued a CCI INIT request. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5904I

**mm/dd/yyyy hh:mm:ss IN25NSRV WAITING FOR WORK.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the Listing Server is waiting for work.

**Action:**

None.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN25NSRV RECVANY FAILED.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN25NSRV issued a CCI Receive Any request. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN25NSRV RECVANY FAILED, INVALID DATA.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN25NSRV issued a CCI Receive Any request and the data received are invalid. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the cause of the error, correct the error and do the request again.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN25NSRV RECVANY FAILED, RECEIVED NULLS.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN25NSRV issued a CCI Receive Any request and data received contained all null values. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to inspect the block received. This could be the result of transmission error. If the problem persists contact CA Support.

## CAIN5905E

**mm/dd/yyyy hh:mm:ss IN2NSRV RECVANY FAILED, INVALID LENGTH.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN2NSRV issued a CCI Receive Any request and length of the data block received was incorrect. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to inspect the length of data block received. This could be the result of transmission error. If the problem persists contact CA Support.

## CAIN5907E

**mm/dd/yyyy hh:mm:ss IN2NSRV SENDSPEC FAILED.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This error occurred when IN2NSRV issued a CCI Send action. Message CAIN5930 is usually issued in conjunction with this message.

**Action:**

Examine feedback area provided in message CAIN5930 to determine the reasons for the failure. This could be the result of transmission error. If the problem persists contact CA Support.

## CAIN5908W

**mm/dd/yyyy hh:mm:ss IN2NSRV GETMAIN FAILED.**

**Reason:**

This message is issued by IN2NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. The message indicated that GETMAIN for 32K of main storage has failed.

**Action:**

Make sure that you have specified a sufficiently large region size to meet the many main storage requirements of the Listing service.

## CAIN5909I

**mm/dd/yyyy hh:mm:ss IN25NSRV REQUEST RECEIVED FOR eeeeeeee.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that a listing request for element named eeeeeeee has been received.

**Action:**

None.

## CAIN5913I

**mm/dd/yyyy hh:mm:ss IN25NSRV SENDING RESPONSE**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the request by message CAIN5909 has been serviced and response is being sent back to the remote host.

**Action:**

None.

## CAIN5930I

**mm/dd/yyyy hh:mm:ss IN25NSRV CCI FEEDBACK: feedback info.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is the message that is usually issued in conjunction with CCI related error conditions. Feedback is a 256 bytes area containing CCI return codes, reason codes, and brief description associated with the error encountered.

**Action:**

Use the information provided in this message in conjunction with the failure message to diagnose the error.

## CAIN5950I

**mm/dd/yyyy hh:mm:ss IN25NSRV SHUTDOWN.**

**Reason:**

This message is issued by IN25NSRV where mm/dd/yyyy hh:mm:ss indicates the date and time when the message was issued. This is an informational message indicating that the Listing server is shutting down.

**Action:**

None.

## CAIN5970W

**LINK TO IN25SPOL FAILED.**

**Reason:**

This message is issued by IN25NSRV indicating that LINK to IN25SPOL has failed. Message extraction will not be performed.

**Action:**

Determine that the data set containing IN25SPOL is either defined in the LINKLIST or is properly defined in the STEPLIB concatenations.

## CAIN5980E

**==>CA SCM CRITICAL ERROR. ERROR CODE: eeee. REQUEST FOR pppppppp NOT SERVICED.**

**Reason:**

This message is issued by IN25NSRV and is used as an end bookmark for message extraction. All messages issued before this message are extracted by the message extraction service.

**Action:**

None.

## CAIN8000W

### **JESMSGLG JCT MTTR FOUND.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicates that MTTR of JESMSGLG JCT was found.

**Action:**

None.

## CAIN8010I

### **JESYSMSG JCT MTTR FOUND.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicates that MTTR of JESMSGLG JCT was found.

**Action:**

None.

## CAIN8020I

### **ACQUIRED MSGLOG AND SYSMSG JCT**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This message indicates that the JCT for JESMSGLG and JESYSMSG have been acquired.

**Action:**

None.

CAIN8030W

**UNABLE TO ACQUIRE JCT OF EITHER JESMSG LG OR JESYSMSG.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicated that IN25SPOL was unable to acquire the JCT of either JESMSG LG or JESYSMSG. Message extraction will not be performed.

**Action:**

Contact CA Support with the information.

CAIN8040I

**STIMER WAIT FOR JQE UPDATE.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. The message indicated that IN25SPOL has issued a STIMER SVC to wait for JQE update to complete.

**Action:**

None.

CAIN8091I

**jjjj IS THE PRIMARY JOB ENTRY SUBSYSTEM. SYSTEM ID FROM JQRYSSID ==> iiiii.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating that jjjj is the primary job entry subsystem whose id is iiiii.

**Action:**

None.

## CAIN8092I

**ddddddd IS THE DDN OF jjjjjjj RETURNED.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating ddddddd is the DD name of jjjjjjj returned. jjjjjjj can either be JESMSG LG or JESYSMSG.

**Action:**

None.

## CAIN8093I

**ASSOCIATED DSN: datasetname.**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating that the fully qualified data set name for the DD name cited in message CAIN8092 is datasetname.

**Action:**

None.

## CAIN8094I

**JOBNAME: jobname JOBID: iiiiii**

**Reason:**

This message is issued by IN25SPOL when CA Technical Support requested diagnostic messages. This is an informational message indicating that the active job name is jobname whose jobid is iiiiii.

**Action:**

None.

## CAIN8098W

### **POSSIBLE CHAINING ERROR. SEE REG 8 FOR DETAILS.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IN252POL was unable to locate SSVE control blocks via chaining through various JES control blocks. Message extraction will not be performed. General Purpose Register 8 points to the chain.

#### **Action:**

Contact CA Support.

## CAIN8050I

### **THERE ARE NO SJQES RETURNED.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSREQ did not return SJQES information. Message extraction will not be performed.

#### **Action:**

None.

## CAIN8060I

### **THERE ARE NO SOUTS RETURNED.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSREQ did not return SOUTS information. Message extraction will not be performed.

#### **Action:**

None.

## CAIN8070I

### **UNABLE TO ACCESS JOB QUEUE.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSREQ was unable to access JES job queue.

#### **Action:**

None.

## CAIN8080I

### **IN25SS71 LOAD FAILED.**

#### **Reason:**

This message is issued by IN25SPOL indicating that loading of IN25SS71 has failed.

#### **Action:**

Make sure that the data set containing IN25SS71 is either in the LINKLIST or the STEPLIB concatenation is properly defined.

## CAIN8090I

### **IN25SDSB LOAD FAILED.**

#### **Reason:**

This message is issued by IN25SPOL indicating that loading of IN25SDSB has failed.

#### **Action:**

Make sure that the data set containing IN25SDSB is either in the LINKLIST or the STEPLIB concatenation is properly defined.

## CAIN8095I

### **IEFSSREQ TYPE=QUERY FAILED. RETURN CODE= cccc REASON CODE= ssss**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSRQ type of query has failed with a return code of cccc and reason code of ssss.

#### **Action:**

Determine the cause of failure based on the return code and reason code.

## CAIN8096I

### **IEFSSI SUBFUNCTION 80 FAILED. SSOBRETN= rrrr STATREAS= ssss.**

#### **Reason:**

This message is issued by IN25SPOL indicating that IEFSSI subfunction 80 has failed. The subsystem return code is rrrr and reason code is ssss. Message extraction will not be performed.

#### **Action:**

Contact CA Support.

CAIN8097I

**JESMSGLG ddddddd NOT FOUND.**

**Reason:**

This message is issued by IN25SPOL indicating that ddddddd token for JESMSGLG.

**Action:**

None.

CAIN8100I

**SPOOL READ FUNCTION CURRENTLY DOES NOT SUPPORT JES3 AT BELOW ZOS 01.11.01 LEVEL.**

**Reason:**

This message is issued by IN25SPOL indicating that spool read function does not support JES3 at a level below ZOS 01.11.01 level. Message extraction will not be performed.

**Action:**

None.

CAIN8100I

**STARTING MSGLOG00 PROCESS.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that message extraction of JESMSGLG is being started.

**Action:**

None.

## CAIN8110I

### **STARTING SYSMSG00 PROCESS.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating that message extraction of JESYSMSG is being started.

**Action:**

None.

## CAIN8120I

### **OBTAINED JCT FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71. It is an informational message indicating that JCT information was obtained from in-storage buffer.

**Action:**

None.

## CAIN8120I

### **OBTAINED IOT FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71. This is an informational message indicating that IOT information was obtained from in-storage buffer.

**Action:**

None.

CAIN8160I

**MSGLOG OBTAINED FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating the JESMSGLOG messages were extracted from in-storage buffer.

**Action:**

None.

CAIN8170I

**MSGLOG READ FROM LAST TRACK.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating the JESMSGLOG messages were extracted from the last track specified in MTTR.

**Action:**

None.

CAIN8180I

**MSGLOG RECORD COUNT EXHAUSTED.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating the JESMSGLOG messages extraction has exhausted its record count.

**Action:**

None.

## CAIN8190I

### **SYSMSG RECORD COUNT IS ZERO.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating the JESYSMSG record count is zero.

**Action:**

None.

## CAIN8200I

### **SYSMSG OBTAINED FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating the JESYSMSG information was extracted from in-storage buffer.

**Action:**

None.

## CAIN8210I

### **SYSMSG RECORD COUNT EXHAUSTED.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating the JESYSMSG messages extraction has exhausted its record count.

**Action:**

None.

## CAIN8230I

### **SYSMSG READ FROM LAST TRACK.**

**Reason:**

This message is issued by IN25SS71 when CA Technical Support requests diagnostic messages. This is an informational message indicating the JESYSMSG messages were extracted from the last track specified in MTTR.

**Action:**

None.

## CAIN8130E

### **INVALID REQUEST.**

**Reason:**

This message is issued by IN25SS71. This is a should not occur error.

**Action:**

Contact CA Support.

## CAIN8140W

### **FAILED TO LOCATE PDDBS FOR BOTH JESMSGLG AND JESYSMSG.**

**Reason:**

This message is issued by IN25SS71 indicating that it cannot locate the PDDBs for JESMSGLG and JESYSMSG.

**Action:**

Contact CA Support.

## CAIN8150I

### **JESMSGLG BUFR IS EMPTY**

**Reason:**

This message is issued by IN25SS71 indicating that the JESMSGLG buffer is empty. Message extraction cannot be performed.

**Action:**

None.

## CAIN8240E

**SUBSYSTEM FUNCTION 71 SPOOL READ FOR JCT FAILED. RC= rrrr SSOBRETN= cccc  
SSJIRETN= ssss.**

**Reason:**

This message is issued by IN25SS71 indicating that IEFSSREQ subfunction 71 has failed reading the JCT. The return code is rrrr, subsystem reason code is cccc, subsystem return code is ssss. Message extraction is not performed.

**Action:**

Contact CA Support with the error message.

## CAIN8260W

**OUTPUT DCB OPEN FAILED.**

**Reason:**

This message is issued by IN25SS71 indicating that open attempt of output dcb for JOBLOG DD statement has failed. Message extraction will not be performed.

**Action:**

Determine the reason for open failure. DD statement: //JOBLOG DD SYSOUT=\*

## CAIN8270I

**NO MORE SYSOUT FROM JES.**

**Reason:**

This message is issued by IN25SS71 indicating end of file condition has reached.

**Action:**

None.

CAIN8320I

**OBTAINED IOT FROM INSTOR BUFFER**

**Reason:**

This message is issued by IN25SDSB when CA Technical Support requests for diagnostic messages. The message indicated that job's IOT information was obtained from in-storage buffer.

**Action:**

None.

CAIN8380I

**JESMSGLG ALLOCATED. DDNAME: dddddddd**

**Reason:**

This message is issued by IN25SDSB when CA Technical Support requests for diagnostic messages. The message provides the dynamic allocation returned DDNAME as dddddddd.

**Action:**

None.

CAIN8300I

**JCT RETREIVAL ERROR.**

**Reason:**

This message is issued by IN25SDSB indicating there was an error retrieving job's JCT. Message extraction will not be performed.

**Action:**

None.

### CAIN8310I

**IOT RETRIEVAL ERROR.**

**Reason:**

This message is issued by IN25SDSB indicating there was an error retrieving job's IOT. Message extraction will not be performed.

**Action:**

None.

### CAIN8330E

**JESMSG LG ALLOCATION FAILED. MSGLOG NOT COLLECTED.**

**Reason:**

This message is issued by IN25SDSB indicating that dynamic allocation of JESMSG LG data set name has failed. Message extraction will not be performed.

**Action:**

None.

### CAIN8340E

**JESYSMSG ALLOCATION FAILED. SYSMSG NOT COLLECTED.**

**Reason:**

This message is issued by IN25SDSB indicating dynamic allocation of JESYSMSG data set name has failed. Message extraction will not be performed.

**Action:**

None.

### CAIN8350W

**FAILED TO LOCATE PDDBS FOR BOTH JESMSG LG AND JESYSMSG.**

**Reason:**

This message is issued by IN25SDSB indicating that attempts to locate the PDDBs for JESMSG LG and JESYSMSG has failed. Message extraction will not be performed.

**Action:**

None.

## CAIN8360I

**SUBSYSTEM FUNCTION 71 SPOOL READ FOR jct FAILED. RC= rrrr SSOBRETN= ssss  
SSJIRETN=nnnn**

**Reason:**

This message is issued by IN25SDSB indicating that IEFSSREQ subfunction 71 has failed reading the JCT. The return code is rrrr, subsystem reason code is cccc, subsystem return code is ssss. Message extraction is not performed.

**Action:**

Contact CA Support with this message.

## CAIN8390I

**JESMSGLG DYNAMIC ALLOCATION FAILED. RC/RSN: rrrr/ssss**

**Reason:**

This message is issued by IN25SDSB indicating that dynamic allocation of SYSOUT for JESMSGLG has failed. The dynamic allocation return code is rrrr, its reason code is ssss. This message is usually followed by IBM IKJ5635 message providing the dynamic allocation text unit that failed. Message extraction will not be performed.

**Action:**

Determine and correct the cause for the failure, than retry the request.

## CAIN8400W

**INPUT DCB OPEN FAILED.**

**Reason:**

This message is issued by IN25SDSB indicating that open of input dcb has failed. The two input data sets involved are JESMSGLG and JESYSMSG. When these data sets were allocated successfully, open should not fail. Message extraction will not be performed.

**Action:**

Determine and correct the cause of the failure, and retry the request.

## CAIN8410W

### **OUTPUT DCB OPEN FAILED.**

**Reason:**

This message is issued by IN25SDSB indicating that open of JOBLOG SYSOUT has failed.

**Action:**

Verify that //JOBLOG DD SYSOUT=\* is defined in the job's JCL.

## CAIN8410I

### **INPUT DDNAME: sys E N D O F F I L E**

**Reason:**

This message is issued by IN25SDSB indicating the end of file condition for DD named sys has reached.

**Action:**

None.

## CAIN7000W

### **IN25NDVR MAJOR ERROR, LOG FILE NOT OPENED**

**Reason:**

SRVPRINT log file not opened. Endeavor activity log disabled.

**Action:**

We recommend that //SRVPRINT DD SYSOUT=\* be defined in the job's JCL so that relevant error can be captured to assist in problem analysis. This would avoid the need to recreate the error.

## CAIN7010I

### **IN25NDVR ALLOCATION OF LOG FILE FAILED.**

**Reason:**

Dynamic allocation of activity log has failed. This message is usually followed by IBM IKJ5635 message providing the dynamic allocation text unit that failed.

**Action:**

Determine and correct the cause of the error and retry the request.

## CAIN7020W

**LOAD OF IN25DALC FAILED.****Reason:**

IN25NDVVR encountered an error trying to LOAD IN25DALC. Endeavor List request will not be performed.

**Action:**

Make sure that the data set containing IN25DALC load module is either defined in the LINKLIST or is defined in the STEPLIB concatenation.

## CAIN7030W

**LOAD OF ENA\$NDVVR FAILED.****Reason:**

IN25NDVVR cannot LOAD the Endeavor API. Endeavor List request will not be performed.

**Action:**

Make sure that Endeavor AUTHLIB and CONLIB data sets are either defined in the LINKLIST or defined in the job's JCL.

## UTIL Messages

## UTIL001

**X...X****Reason:**

This message is an echo of the input request. The request is indicated by x...x.

**Action:**

None.

## UTIL002

### **INITIALIZATION COMPLETED**

**Reason:**

The symbolic file has been initialized.

**Action:**

None.

## UTIL003

### **XXXXXXXX DELETED FROM SYMBOLIC FILE**

**Reason:**

Program xxxxxxxx was deleted from the symbolic file.

**Action:**

None.

## UTIL004

### **XXXXXXXX UNLOADED FROM SYMBOLIC FILE**

**Reason:**

Program xxxxxxxx has been unloaded from the symbolic file.

**Action:**

None.

## UTIL005

### **XXXXXXXX RELOADED TO SYMBOLIC FILE**

**Reason:**

Program xxxxxxxx was reloaded to the symbolic file.

**Action:**

None.

UTIL006

**XXXXXXXX RELOADED TO SYMBOLIC FILE AND HAS BEEN RENAMED TO YYYYYYYY**

**Reason:**

Program xxxxxxxx was reloaded to the symbolic file with the name yyyyyyyy.

**Action:**

None.

UTIL007

**UNLOAD PROCESSING COMPLETED**

**Reason:**

The UNLOAD function completed.

**Action:**

None.

UTIL008

**RELOAD PROCESSING COMPLETED**

**Reason:**

The RELOAD function completed.

**Action:**

None.

UTIL009

**PURGE PROCESSING COMPLETED - XXXXX RECORDS HAVE BEEN FREED**

**Reason:**

The PURGE function completed and freed up the number of records indicated by xxxxx.

**Action:**

None.

## UTIL010

### **DEVICE NOW CLOSED**

**Reason:**

The device, specified by a CLOSE function, closed. Any subsequent requests for this device cause that device to open at load point.

**Action:**

None.

## UTIL011

### **INTERTEST BATCH UTILITY RUN COMPLETED SUCCESSFULLY**

**Reason:**

All requested functions have been performed and the symbolic file was updated successfully.

**Action:**

None.

## UTIL012

### **RELOAD PROCESSING STARTED FOR PROGRAM XXXXXXXX**

**Reason:**

The RELOAD function began for program xxxxxxxx.

**Action:**

None.

## UTIL047

### **XXXXXXXX MUST BE DELETED**

**Reason:**

While processing program xxxxxxxx, a condition occurred that indicated that data for the program was corrupted.

**Action:**

Delete this program.

## UTIL048

**XXXXXXXX CANNOT BE UNLOADED****Reason:**

Program xxxxxxxx was found to be corrupted and could not be unloaded.

**Action:**

None.

## UTIL049

**XXXXXXXX HAS ZERO RECORDS - ENTRY BYPASSED****Reason:**

Program xxxxxxxx was found to be corrupted.

**Action:**

Complete the following steps:

1. Delete the program from the symbolic file.
2. Using the UTILITY job, run an UNLOAD=ALL request.
3. Using the UTILITY job, run an INITIALIZE request.
4. Using the UTILITY job, run a RELOAD=ALL request, using the file created in step 2 as input.
5. Resubmit the original job.

## UTIL050

**PASSWORD MISSING - REQUEST IGNORED****Reason:**

The function requested requires a PASSWORD parameter card. Only this request is ignored.

**Action:**

Add a PASSWORD parameter card as the first parameter card in the job stream and resubmit the job.

## UTIL051

### **PASSWORD INCORRECT**

**Reason:**

The password provided on the PASSWORD parameter card does not match the password that was generated by the SYMPSWD parameter in IN25SOPT. The job is terminated.

**Action:**

Change the password specified by the PASSWORD parameter card to match the generated password and resubmit the entire job stream.

## UTIL052

### **INVALID REQUEST**

**Reason:**

The function requested is invalid. This condition may be caused by a misspelled option or invalid input. The job is terminated.

**Action:**

Correct the requested function and resubmit the entire job stream.

## UTIL053

### **XXXXXXXXX CANNOT FIT ON FILE - PROGRAM IS BYPASSED**

**Reason:**

The symbolic file did not contain enough free space to handle a RELOAD function for program xxxxxxxx. The program is bypassed.

**Action:**

Complete the following steps:

1. Using the UTILITY job, run an UNLOAD=ALL request.
2. Delete the symbolic file using IDCAMS.
3. Run an IDCAMS DEFINE for the symbolic file with a larger space allocation. Remember that a secondary space allocation is not permitted.
4. Using the UTILITY job, run an INITIALIZE request.
5. Using the UTILITY job, run a RELOAD=ALL request, using the file created in step 1 as input.
6. Resubmit the original job.

Or:

1. Using the UTILITY job, run a PURGE request to free up space.
2. Resubmit the original job.

#### UTIL054

##### **PURGE INTERVAL INVALID OR MISSING - REQUEST NOT PROCESSED**

**Reason:**

The PURGE request did not specify a number of days or the number of days specified was not within the range of 1 through 365. This request is ignored.

**Action:**

Correct the PURGE request and resubmit the job.

#### UTIL055

##### **PROGRAM NOT FOUND IN FILE OR WAS NOT USABLE**

**Reason:**

The program specified for a requested function was not found in the symbolic file or was unusable. This request is ignored.

**Action:**

Run a REPORT function. If the program is found, delete it and resubmit the original job.

#### UTIL056

##### **PROGRAM NAME IS GREATER THAN 8 CHARACTERS LONG - REQUEST IGNORED**

**Reason:**

The program specified for a requested function contained more than eight characters. This request is ignored.

**Action:**

Correct the requested function and resubmit the job.

## UTIL057

### **SYMBOLIC FILE IS EMPTY - PLEASE RUN INITIALIZATION AS FIRST STEP**

**Reason:**

The symbolic file did not contain the required control records. The job is terminated.

**Action:**

Using the UTILITY job, run an INITIALIZE request.

## UTIL058

### **VSAM RECORD LENGTH NOT = 2040**

**Reason:**

The symbolic file was created with a wrong record size. The job is terminated.

**Action:**

Follow the instructions in [Creating a PROTSYM File](#) (see page 17) for creating a PROTSYM file.

## UTIL059

### **NO LISTER INFORMATION FOR THIS PROGRAM - PRINT= REQUEST IGNORED**

**Reason:**

The program specified by the PRINT request did not contain any saved source. This request is ignored.

**Action:**

None.

## UTIL060

### **REQUEST FOR VIRTUAL STORAGE FAILED**

**Reason:**

The request for GETMAIN or GETVIS storage failed. The job is terminated.

**Action:**

Resubmit the entire job stream, using a bigger region size or run the job in a larger partition.

## UTIL061

**OPEN FAILURE FOR UNLOAD DEVICE****Reason:**

The open request for the device to be used for an UNLOAD function failed.

**Action:**

Correct the JCL and resubmit the job.

## UTIL062

**OPEN FAILURE FOR RELOAD DEVICE****Reason:**

The open request for the device to be used for a RELOAD function failed.

**Action:**

Correct the JCL and resubmit the job.

## UTIL063

**UNLOAD=ALL HAS BEEN RUN - ALL OTHER UNLOAD REQUESTS ARE IGNORED****Reason:**

An UNLOAD request has been made after an UNLOAD=ALL request. This request is ignored.

**Action:**

Resubmit the UNLOAD request which was rejected in a separate job stream.

## UTIL064

**INPUT FROM RELOAD FILE IS INVALID****Reason:**

Data being retrieved for a RELOAD request was not in the correct format. This condition may be caused by invalid JCL or by data that was overlaid since its creation by the UNLOAD request. This request is ignored.

**Action:**

If invalid JCL caused the error, correct the JCL and resubmit the request. If invalid data caused the error, the problem is not correctable.

## UTIL065

### **RELOAD FILE IS EMPTY**

**Reason:**

An end-of-file condition occurred on the first read from the RELOAD device. This condition occurs when the file is empty. This request is ignored.

**Action:**

If invalid JCL caused the error, correct the JCL and resubmit the request; otherwise, the problem is not correctable.

## UTIL066

### **XXXXXXXX ALREADY EXISTS IN FILE: RELOAD FOR THIS PROGRAM IGNORED**

**Reason:**

The program to be reloaded already exists on the file. This request is ignored.

**Action:**

Delete the program, using a DELETE request, and resubmit the RELOAD request.

## UTIL067

### **xxxxxxx yyyy ERROR R15 = X'rr' ERROR CODE = X'ee'**

**Reason:**

A VSAM error occurred while running the UTILITY program. The message contains the following information:

- xxxxxxx is the name of the symbolic file.
- yyyy is the type of request (OPEN, GET, or PUT).
- rr is the return code, in hexadecimal.
- ee is the error code, in hexadecimal.

The job may or may not be terminated, depending on the function requested and when the error occurred.

**Action:**

Using the information from the message, find the explanation of the error in the VSAM guide that contains the error messages. Handle the error as described in your guide.

## UTIL068

**SEQUENCE NUMBER NOT FOUND****Reason:**

While processing a request, an internal record key was not found. This condition indicates a corrupted file.

**Action:**

Delete the program that caused the problem.

## UTIL070

**RECORD COUNT ERROR AT ENDREQ****Reason:**

An internal check of the file has failed. This condition indicates a corrupted file. The job is terminated with a dump.

**Action:**

For assistance, contact CA Support.

## UTIL071

**UNLOAD OR RELOAD NOT SPECIFIED****Reason:**

A CLOSE request was made but did not specify UNLOAD or RELOAD. The job is terminated.

**Action:**

Correct the CLOSE request and resubmit the entire job stream.

## UTIL072

**ERROR OCCURRED WHILE READING RELOAD DEVICE (DOS)****Reason:**

The system detected an error condition while reading a record from the device pointed to by SYS005. The job is terminated.

**Action:**

Determine the cause of the error, correct the problem, and resubmit the entire job stream.

## UTIL073

### **ERROR OCCURRED WHILE WRITING TO UNLOAD DEVICE (DOS)**

**Reason:**

The system detected an error condition while writing a record to the device pointed to by SYS005. The job is terminated.

**Action:**

Determine the cause of the error, correct the problem, and resubmit the entire job stream.

## UTIL074

### **ERROR OCCURRED WHILE READING PARAMETER CARDS (DOS)**

**Reason:**

The system detected an error condition while reading a control card. The job is terminated.

**Action:**

Determine the cause of the error, correct the problem, and resubmit the entire job stream.

## UTIL075

### **ENQ ERROR: CODE = X'yy' (DOS)**

**Reason:**

An error occurred while issuing a SVC 63 (lock) request. The job is terminated.

**Action:**

For assistance, contact CA Support.

## UTIL076

**REQUESTED DATA SPACE EXCEEDS MAXIMUM FOR FILE****Reason:**

The symbolic file has been defined with a size that exceeds its capacity. The maximum size of this file is about 4,000,000 2 KB records. The job is terminated.

**Action:**

This error is usually caused by defining the file with a secondary space allocation. If this is the case, redefine the file without a secondary allocation and initialize it.

## UTIL077

**INTERTEST BATCH UTILITY RUN UNSUCCESSFUL  
ALL UPDATES HAVE BEEN BACKED-OUT****Reason:**

This message is produced on any error condition that terminates the job. If this message is produced, all requested functions, even if they were correct, are backed out.

**Action:**

After the error condition is corrected, you must resubmit the entire job stream.

## UTIL078

**INTERTEST BATCH UTILITY RUN UNSUCCESSFUL  
UPDATES HAVE NOT BEEN BACKED-OUT****Reason:**

This message is produced when an error condition, which is not serious, has occurred. If this message is produced, only the requests that were in error are ignored and all valid requests were performed.

**Action:**

Review the output for any previous error messages, resolve those errors, and try again.

## UTIL079

### **PROGRAM NOT FOUND IN RELOAD FILE - REQUEST IGNORED**

**Reason:**

The program specified by a RELOAD request was not found in the reload file.

**Action:**

None.

## UTIL080

### **VSAM CI SIZE NOT = 2048**

**Reason:**

The symbolic file was created with the wrong CI size.

**Action:**

Recreate the symbolic file with the correct CI size.

## UTIL094

### **CANNOT BE RELOADED DUE TO PROTSYM FRAGMENTATION**

**Reason:**

When reloading program xxxxxxxx it became too fragmented to add to the file properly. The program was not added to the file.

**Action:**

Complete the following steps:

1. Using the UTILITY job, run an UNLOAD=ALL request.
2. Delete the symbolic file using IDCAMS.
3. Run an IDCAMS DEFINE for the symbolic file with a larger space allocation. Remember that a secondary space allocation is not permitted.
4. Using the UTILITY job, run an INITIALIZE request.
5. Using the UTILITY job, run a RELOAD=ALL request, using the file created in step 1 as input.
6. Resubmit the original job.

Or:

1. Using the UTILITY job, run a PURGE request to free up space.
2. Resubmit the original job.

UTIL095

**CHAIN TO NEXT DIRECTORY IS CORRUPTED**

UTIL096

**MISMATCH ON TOTAL AVAILABLE FREE RECORDS**

UTIL097

**MISMATCH ON AVAILABLE FREE RECORDS IN ONE SAM**

UTIL098

**INCORRECT NUMBER OF DIRECTORIES ON INPUT**

UTIL099

**INCORRECT NUMBER OF DIRECTORIES ON OUTPUT****Reason:**

Messages UTIL095 through UTIL099 are produced by the special checkout procedure. This procedure checks for a corrupted symbolic file.

If a corrupted file is found at the start of the job, one of the above messages displays. If a corrupted file is found at the end of the job, one of the above messages displays, an attempt is made to back out all updates, and the IN25UTIL program abends.

**Action:**

In response to these messages, try the following procedures before contacting CA Technical Support:

1. Run the IN25UTIL program to unload the existing data.
2. Recreate the symbolic file from scratch, using IDCAMS.
3. Run the IN25UTIL program to initialize the symbolic file.
4. Run the IN25UTIL program to reload the symbolic file with the saved data.

At this point, the symbolic file should be repaired. If the problem still exists, contact CA Support.

## UTIL100

### **\*WARNING\* PROTSYM IS NOT COMPATIBLE WITH INTERTEST RELEASES BELOW 5.4**

**Reason:**

You are attempting to use an r5.4 symbolic file with an earlier CA InterTest release. The new, larger symbolic files can only be used with r5.4 and higher; they are not downward compatible with earlier CA InterTest releases.

**Action:**

For CA InterTest releases prior to r5.4, only use symbolic files created with a pre-5.4 release.

## UTIL101

### **INVALID RECORD ON FILE. UNLOAD AND RELOAD OF FILE RECOMMENDED**

**Reason:**

An invalid record has been encountered on the PROTSYM during a utility function.

**Action:**

Reorganize your PROTSYM by doing an UNLOAD=ALL followed by a RELOAD=ALL to remove the bad record.

## UTIL102

### **x22 CANCEL, ABEND PERCOLATED**

**Reason:**

A system cancel event occurred while IN25UTIL was executing.

**Action:**

Capture the dump if needed.

## UTIL103

### **RECOVERY FAILURE, SOC1 GENERATED**

**Reason:**

A VSAM request failed.

**Action:**

Capture and save the SOC1 dump and contact CA Support.

## UTIL104

**INVALID DATE FORMAT - REQUEST IGNORED****Reason:**

The DATETIME, BEFOREDATETIME, or AFTERDATETIME parameter was specified with an incorrect value or in an incorrect format. The date must exist, and its value should follow a yyyy/mm/dd hh:mm:ss format. The year is required, while all other fields are optional.

**Action:**

Correct the value and resubmit the request.

## UTIL105

**YEAR CONTAINS NON NUMERIC DATA - REQUEST IGNORED****Reason:**

The year specified for a DATETIME, BEFOREDATETIME, or AFTERDATETIME parameter contains a value which is not numeric.

**Action:**

Correct the value and resubmit the request.

## UTIL106

**MONTH CONTAINS NON NUMERIC DATA - REQUEST IGNORED****Reason:**

The month specified for a DATETIME, BEFOREDATETIME, or AFTERDATETIME parameter contains a value which is not numeric.

**Action:**

Correct the value and resubmit the request.

## UTIL107

### **DAY CONTAINS NON NUMERIC DATA - REQUEST IGNORED**

**Reason:**

The day specified for a DATETIME, BEFOREDATETIME, or AFTERTATETIME parameter contains a value which is not numeric.

**Action:**

Correct the value and resubmit the request.

## UTIL108

### **HOOR EXCEEDS MAXIMUM VALUE - REQUEST IGNORED**

**Reason:**

The hour specified for a DATETIME, BEFOREDATETIME, or AFTERTATETIME parameter contains a value which is greater than or equal to 24.

**Action:**

Correct the value and resubmit the request.

## UTIL109

### **HOOR CONTAINS NON NUMERIC DATA - REQUEST IGNORED**

**Reason:**

The hour specified for a DATETIME, BEFOREDATETIME, or AFTERTATETIME parameter contains a value which is not numeric.

**Action:**

Correct the value and resubmit the request.

## UTIL110

### **MINUTE EXCEEDS MAXIMUM VALUE - REQUEST IGNORED**

**Reason:**

The minute specified for a DATETIME, BEFOREDATETIME, or AFTERTATETIME parameter contains a value which is greater than or equal to 60.

**Action:**

Correct the value and resubmit the request.

## UTIL111

**MINUTE CONTAINS NON NUMERIC DATA - REQUEST IGNORED****Reason:**

The minute specified for a DATETIME, BEFOREDATETIME, or AFTERDATETIME parameter contains a value which is not numeric.

**Action:**

Correct the value and resubmit the request.

## UTIL112

**SECOND EXCEEDS MAXIMUM VALUE - REQUEST IGNORED****Reason:**

The second specified for a DATETIME, BEFOREDATETIME, or AFTERDATETIME parameter contains a value which is greater than or equal to 60.

**Action:**

Correct the value and resubmit the request.

## UTIL113

**SECOND CONTAINS NON NUMERIC DATA - REQUEST IGNORED****Reason:**

The second specified for a DATETIME, BEFOREDATETIME, or AFTERDATETIME parameter contains a value which is not numeric.

**Action:**

Correct the value and resubmit the request.

## UTIL114

**INVALID PARAMETER FORMAT - REQUEST IGNORED****Reason:**

A parameter value was in an incorrect format or contained invalid characters.

**Action:**

Correct the value and resubmit the request.

## UTIL115

### **NON NUMERIC DATA ENTERED - MAXPGMVER HAS BEEN SET TO 1**

**Reason:**

A parameter value contained a value which was not numeric.

**Action:**

Correct the value and resubmit the request.

## UTIL116

### **MAXPGMVER WAS REACHED - RELOAD FOR THIS PROGRAM IGNORED**

**Reason:**

The maximum number of program versions has been reached for the current program being reloaded.

## UTIL117

### **MAXPGMVER WAS HIGHER THAN ALLOWED - MAXPGMVER HAS BEEN SET TO 255.**

**Reason:**

Valid value range for MAXPGMVER is 1-255.

## UTIL118

### **MAXPGMVER CANNOT BE ZERO - MAXPGMVER HAS BEEN SET 1.**

**Reason:**

Valid value range for MAXPGMVER is 1-255.

## UTIL119

### **INVALID DATA ENTERED - USEDSPACEMSG HAS BEEN SET TO 0.**

**Reason:**

The valid value range for USEDSPACEMSG is 0-99.

## UTIL120

### **FUNCTION NOT SUPPORTED IN THE VERSION OF PROTSYM.**

**Reason:**

You used a function that is not supported in the current version of PROTSYM.

**Action:**

None.

## UTIL121

### **INVALID DATA ENTERED - REQUEST IGNORED.**

**Reason:**

A parameter value did not fall in a valid range.

**Action:**

Correct the value and resubmit the request.

## UTIL122

### **MULTIVERSION SUBPARAMETERS NOT VALID FOR GENERIC PROGRAM NAMES**

**Reason:**

A multiversion subparameter was used in conjunction with a generic program name.

**Action:**

Remove multiversion subparameters or provide a complete program name.



# Appendix A: Restrictions for PL/I

---

This appendix lists the restrictions that you must take into consideration when using symbolic support in CA InterTest for CICS and CA SymDump for CICS.

## Symbolic Support Restrictions

Follow these restrictions when using symbolic support:

- Controlled Variables are not supported. For example:

```
DCL A CTL;
```

In the DCL above, there would be no symbolic support and `CORE='A'` would not work.

- Use of redefine is not supported. For example:

```
DCL A CHAR(10);  
DCL B DEF A;
```

In the example above, displaying B with CORE would not work.

- Adjusted variables are not supported. For example:

```
PROC1 : PROC;  
DCL SIZE BIN FIXED(15,0) INIT(10);  
PROC2 : PROC;  
DCL ARRAY(SIZE) BIN(15,0);  
END;  
END;
```

In the example above, an array could not be displayed using CORE.

- Individual array entries are not supported. For example:

```
CORE= 'A(5)'
```

This array entry will not work.

- Duplicate symbol names in the same PROC are not supported. For example:

```
DCL A CHAR(5);
DCL 1 Z,
2 P BIN FIXED,
2 A BIN FIXED;
```

Using the previous example, when CORE='A' is issued, unpredictable results occur. However, the same variable name in different PROCs is supported. For example:

```
PROC1 : PROC;
DCL A CHAR;
PROC2 : PROC;
DCL A BIN FIXED;
```

In the previous example, if CORE='A' were issued in 'PROC1', then the value of 'A' for 'PROC1' would be displayed. If 'PROC2' had been executed to display the value of 'A' in 'PROC2', use the following command: CORE='PROC2:A'.

- Variables that use the PL/I ALLOC and FREE commands can be looked at with CORE only after the ALLOC executes and before the FREE executes. For example:

```
DCL A BASED(P);      ... cannot view "A".
ALLOC A;            ... can use CORE to view "A".
FREE A;             ... can no longer view "A".
```

- Variables declared in a block can't be viewed until the execution of that PROC's PROC/BEGIN statement. For example:

```
PROC2 : PROC;
DCL Z CHAR; ... cannot view "P".
      ... can view "Z"..
PROC2 : PROC;
DCL P CHAR; ... can view "P".
      ... can view "Z"..
```

- At least one automatic variable must be declared in a program for symbolics to function.
- Only one label can appear on a PROC statement. For example:

```
LABEL1 : LABEL2 : PROC ;
```

This is not supported.

Use of the PL/I pre-processor options %NOPRINT, NUMBER, GONUM, and MARGINI is prohibited. If you must use %NOPRINT, call CA.